



CUSTOMER COPY

REV.	DESCRIPTION	BY/DATE	CHECK/DATE	APPROVED/DATE
1.0	Ori.	08/20/02'		

- NOTES:
- 1.0. MATERIAL:
 - 1.1. HOUSING: PBT G.F. UL 94V-0
 - 1.2. CONTACT: COPPER ALLOY
 - 1.3. SHELL: STEEL
 - 2.0. RATING:
 - 2.1. VOLTAGE: 30VAC(R.M.S.)
 - 2.2. CURRENT: 1.0 AMPERE MIN.
 - 2.3. TEMPERATURE: -55°C TO +105°C
 - 3.0. ELECTRIC CHARACTERISTIC:
 - 3.1. CONTACT RESISTANCE: 30 MILLIOHMS MAX.
 - 3.2. INSULATION RESISTANCE: 1,000 MEGOHMS MIN.
 - 3.3. DIELECTRIC WITHSTANDING VOLTAGE: 500 VAC

General Tolerance		Angle Tolerance		Dwg	Date	COMOSS® GOMOSS ELECTRONIC CO., LTD. 4F., No. 11, Chung-Hsin St., ShuLin 238, Taipei, Taiwan R.O.C.			
.X	±0.15	.X°	±1.0°	David	08/20/02'				
.XX	±0.10	.XX°	±0.5°	Design	Date	Item USB CONNECTOR			
.XXX	±0.05	.XXX°	±0.2°	Samdy	09/05/02'				
SHEET 1/2				CHK	Date	USB B/MALE LONG SHELL CRIMPING TYPE			
FINISH SEE ORDER INFORMATION				William	09/05/02'				
Scale	N/A	Unit:	mm	APPR	Date	Dwg. No.	A0271	SIZE	A3
						Part No.	USB-4MBESXXXX	REV	1.0



CUSTOMER COPY

ASSEMBLY PROCESS:






Table:

D	INSULATOR	THERMOPLASTIC, GLASS FILLED UL 94V-0	TBA
C	CONTACT	COPPER ALLOY	TBA
B	UPPER SHELL	STEEL	TBA
A	MAIN SHELL	STEEL	TBA
ITEM	DESCRIPTION	MATERIAL	P/N

General Tolerance .X ±0.15 .XX ±0.10 .XXX ±0.05		Angle Tolerance .X° ±1.0° .XX° ±0.5° .XXX° ±0.2°		Dwg David	Date 08/20/02'	COMOSS® GOMOSS ELECTRONIC CO., LTD. 4F., No. 11, Chung-Hsin St., ShuLin 238, Taipei, Taiwan R.O.C.	
SHEET 2/2		Design Samdy		Date 09/05/02'			
FINISH SEE ORDER INFORMATION		CHK William		Date 09/05/02'	Item USB CONNECTOR USB B/MALE LONG SHELL CRIMPING TYPE		
Scale N/A	Unit: mm	APPR	Date	Dwg. No. A0271			
				Part No. USB-4MBESXXXX	REV. 1.0		