Problem 8

a)

Prefix Match	Link Interface
11100000 00	0
11100000 01000000	1
1110000	2
11100001 1	3
otherwise	3

b) Prefix match for first address is 5th entry: link interface 3
Prefix match for second address is 3rd entry: link interface 2
Prefix match for third address is 4th entry: link interface 3

Problem 9

Destination Address Range	Link Interface
00000000 through 00111111	0
01000000 through 01011111	1
01100000 through 01111111	2
10000000 through 10111111	2
11000000 through 11111111	3

number of addresses for interface 0 = $2^6 = 64$

number of addresses for interface 1 = $2^5 = 32$

number of addresses for interface 2 = $2^6 + 2^5 = 64 + 32 = 96$

number of addresses for interface 3 = $2^6 = 64$

Problem 10

Destination Address Range	Link Interface
11000000 through (32 addresses) 11011111	0
10000000 through(64 addresses) 10111111	1
11100000 through (32 addresses) 11111111	2
00000000 through (128 addresses) 01111111	3

Problem 11

223.1.17.0/26
223.1.17.128/25

223.1.17.64/28

Notes: The above choices are NOT unique. Two important things to remember:

a. Always start assigning Blocks for the largest subnet (in this case it is B)
b. Make sure that subnets do NOT overlap (i.e., all IP addresses are unique)

Problem 12

Destination Address	Link Interface
200.23.16/21	0
200.23.24/24	1
200.23.24/21	2
otherwise	3

Problem 13

Destination Address	Link Interface
11100000 00 (224.0/10)	0
11100000 01000000 (224.64/16)	1
1110000 (224/7)	2
11100001 1 (225.128/9)	3
otherwise	3

Problem 14

Any IP address in range 128.119.40.128 to 128.119.40.191

Four equal size subnets: 128.119.40.64/28, 128.119.40.80/28, 128.119.40.96/28, 128.119.40.112/28

Problem 15

From 214.97.254/23, possible assignments are

a) Subnet A: 214.97.255/24 (256 addresses)
Subnet B: 214.97.254.0/25 - 214.97.254.0/29 (128-8 = 120 addresses)
Subnet C: 214.97.254.128/25 (128 addresses)

Subnet D: 214.97.254.0/31 (2 addresses)
Subnet E: 214.97.254.2/31 (2 addresses)
Subnet F: 214.97.254.4/30 (4 addresses)

b) To simplify the solution, assume that no datagrams have router interfaces as ultimate destinations. Also, label D, E, F for the upper-right, bottom, and upper-left interior subnets, respectively.

Router 1

Longest Prefix Match	Outgoing Interface
11010110 01100001 11111111	Subnet A
11010110 01100001 11111110 0000000	Subnet D
11010110 01100001 11111110 000001	Subnet F

Router 2

Longest Prefix Match	Outgoing Interface
11010110 01100001 11111111 0000000	Subnet D
11010110 01100001 11111110 0	Subnet B
11010110 01100001 11111110 0000001	Subnet E

Router 3

Longest Prefix Match	Outgoing Interface
11010110 01100001 11111111 000001	Subnet F
11010110 01100001 11111110 0000001	Subnet E
11010110 01100001 11111110 1	Subnet C

Just a note here:” In the final exam, /31 Block will NIOT be allowed (i.e., the smallest block is /30). ?31 block is used by “some” ISPs to assign IP addresses for “point-to-point” interfaces, say for two routers connected directly)

Problem 3

Step	N'	D(t),p(t)	D(u),p(u)	D(v),p(v)	D(w),p(w)	D(y),p(y)	D(z),p(z)
0	x	∞	∞	3,x	6,x	6,x	8,x
1	xv	7,v	6,v	3,x	6,x	6,x	8,x
2	xvu	7,v	6,v	3,x	6,x	6,x	8,x
3	xvuw	7,v	6,v	3,x	6,x	6,x	8,x
4	xvuwy	7,v	6,v	3,x	6,x	6,x	8,x
5	xvuwyt	7,v	6,v	3,x	6,x	6,x	8,x
6	xvuwytz	7,v	6,v	3,x	6,x	6,x	8,x

Problem 5

Cost to

		u	v	x	y	z
	v	∞	∞	∞	∞	∞
From	x	∞	∞	∞	∞	∞
	z	∞	6	2	∞	0

Cost to

		u	v	x	y	z
	v	1	0	3	∞	6
From	x	∞	3	0	3	2
	z	7	5	2	5	0

Cost to

		u	v	x	y	z
	v	1	0	3	3	5
From	x	4	3	0	3	2
	z	6	5	2	5	0

Cost to

		u	v	x	y	z
	v	1	0	3	3	5
From	x	4	3	0	3	2
	z	6	5	2	5	0