

Iterative Hessian Sketch for Constrained Least-Squares

Lydia Hsu, Shuaiwen Wang

December 10, 2018

Paper: *Iterative Hessian Sketch: Fast and Accurate Solution Approximation for Constrained Least-Squares*

- Consider the **constrained least-squares**

$$x_{ls} := \arg \min_{x \in C} \frac{1}{2} \|Ax - y\|_2^2$$

where C : constraint; $A \in \mathbb{R}^{n \times p}$: design matrix; y : response.

- Consider the **constrained least-squares**

$$x_{ls} := \arg \min_{x \in C} \frac{1}{2} \|Ax - y\|_2^2$$

where C : constraint; $A \in \mathbb{R}^{n \times p}$: design matrix; y : response.

- Issue: when n large, computationally **expensive**;

- Consider the **constrained least-squares**

$$x_{ls} := \arg \min_{x \in C} \frac{1}{2} \|Ax - y\|_2^2$$

where C : constraint; $A \in \mathbb{R}^{n \times p}$: design matrix; y : response.

- Issue: when n large, computationally **expensive**;
- Idea: substitute A with its “sketched” version SA ;

- Consider the **constrained least-squares**

$$x_{ls} := \arg \min_{x \in C} \frac{1}{2} \|Ax - y\|_2^2$$

where C : constraint; $A \in \mathbb{R}^{n \times p}$: design matrix; y : response.

- Issue: when n large, computationally **expensive**;
- Idea: substitute A with its “sketched” version SA ;
- $S \in \mathbb{R}^{m \times n}$: sketching matrix; $ES^\top S = I_n$.

Common sketching matrices

- sub-Gaussian: $S_{ij} \sim_{iid} \frac{1}{\sqrt{m}} \mathcal{N}(0, 1);$

Common sketching matrices

- sub-Gaussian: $S_{ij} \sim_{iid} \frac{1}{\sqrt{m}} \mathcal{N}(0, 1)$;
- random row sampling: randomly select m rows from I_n (rescaled by $\sqrt{\frac{n}{m}}$);

Common sketching matrices

- sub-Gaussian: $S_{ij} \sim_{iid} \frac{1}{\sqrt{m}} \mathcal{N}(0, 1)$;
- random row sampling: randomly select m rows from I_n (rescaled by $\sqrt{\frac{n}{m}}$);
- randomized orthogonal system: randomly select m rows from an orthogonal matrix H (rescaled by $\sqrt{\frac{n}{m}}$);

- Sketch not only A , but also y :

$$x_{cs} := \arg \min_{x \in C} \frac{1}{2} \|SAx - Sy\|_2^2$$

- Sketch not only A , but also y :

$$x_{CS} := \arg \min_{x \in C} \frac{1}{2} \|SAx - Sy\|_2^2$$

- Classical sketch is **sub-optimal**: assume a linear ground truth $y = Ax_* + w$:

$$\|x_{CS} - x_*\| \sim \|x_{IS} - x_*\| \quad \Rightarrow \quad m = \Theta(n)$$

- Sketch not only A , but also y :

$$x_{CS} := \arg \min_{x \in C} \frac{1}{2} \|SAx - Sy\|_2^2$$

- Classical sketch is **sub-optimal**: assume a linear ground truth $y = Ax_* + w$:

$$\|x_{CS} - x_*\| \sim \|x_{ls} - x_*\| \Rightarrow m = \Theta(n)$$

- We expect the optimal method satisfies $m \approx O(p)$ **Think about this part more carefully?**

Hessian Sketch

- Only sketch A , but not y :

$$x_{hs} := \arg \min_{x \in C} \frac{1}{2} \|SAx\|_2^2 - \langle A^\top y, x \rangle.$$

Hessian Sketch

- Only sketch A , but not y :

$$x_{hs} := \arg \min_{x \in C} \frac{1}{2} \|SAx\|_2^2 - \langle A^\top y, x \rangle.$$

- **Sub-optimal** in the same sense;

- Only sketch A , but not y :

$$x_{hs} := \arg \min_{x \in C} \frac{1}{2} \|SAx\|_2^2 - \langle A^\top y, x \rangle.$$

- **Sub-optimal** in the same sense;
- With $m \sim O(p)$ sample size, we can obtain a weak result:

$$\|x_{hs} - x_{ls}\| \leq \rho \|x_{ls}\|, \quad \text{w.h.p.}$$

where $\rho \in (0, \frac{1}{2})$.

- Only sketch A , but not y :

$$x_{hs} := \arg \min_{x \in C} \frac{1}{2} \|SAx\|_2^2 - \langle A^\top y, x \rangle.$$

- **Sub-optimal** in the same sense;
- With $m \sim O(p)$ sample size, we can obtain a weak result:

$$\|x_{hs} - x_{ls}\| \leq \rho \|x_{ls}\|, \quad \text{w.h.p.}$$

where $\rho \in (0, \frac{1}{2})$.

- *An iterative idea for improvement:* “ $\|x^{t+1} - x_{ls}\| \leq \rho \|x^t - x_{ls}\|$ ”?

Iterative Hessian Sketch

A detailed idea:

- Given x^t , a modified least square with $x_{ls} - x^t$ as minimizer:

$$\min_u \frac{1}{2} \|A(u + x^t)\|_2^2 - \langle A^\top y, (u + x^t) \rangle$$

Iterative Hessian Sketch

A detailed idea:

- Given x^t , a modified least square with $x_{ls} - x^t$ as minimizer:

$$\min_u \frac{1}{2} \|Au\|_2^2 - \langle A^\top(y - Ax^t), u \rangle$$

Iterative Hessian Sketch

A detailed idea:

- Given x^t , a modified least square with $x_{ls} - x^t$ as minimizer:

$$\min_u \frac{1}{2} \|Au\|_2^2 - \langle A^\top(y - Ax^t), u \rangle$$

- The corresponding Hessian sketch:

$$u^{t+1} = \arg \min_u \frac{1}{2} \|SAu\|_2^2 - \langle A^\top(y - Ax^t), u \rangle$$

Iterative Hessian Sketch

A detailed idea:

- Given x^t , a modified least square with $x_{ls} - x^t$ as minimizer:

$$\min_u \frac{1}{2} \|Au\|_2^2 - \langle A^\top(y - Ax^t), u \rangle$$

- The corresponding Hessian sketch:

$$u^{t+1} = \arg \min_u \frac{1}{2} \|SAu\|_2^2 - \langle A^\top(y - Ax^t), u \rangle$$

- Property of Hessian sketch: $\|u^{t+1} - (x_{ls} - x^t)\| \leq \rho \|x_{ls} - x^t\|;$

Iterative Hessian Sketch

A detailed idea:

- Given x^t , a modified least square with $x_{ls} - x^t$ as minimizer:

$$\min_u \frac{1}{2} \|Au\|_2^2 - \langle A^\top(y - Ax^t), u \rangle$$

- The corresponding Hessian sketch:

$$u^{t+1} = \arg \min_u \frac{1}{2} \|SAu\|_2^2 - \langle A^\top(y - Ax^t), u \rangle$$

- Property of Hessian sketch: $\|u^{t+1} - (x_{ls} - x^t)\| \leq \rho \|x_{ls} - x^t\|$;
- Define $x^{t+1} = x^t + u^{t+1}$, then:

$$\|x^{t+1} - x_{ls}\| \leq \rho \|x^t - x_{ls}\|, \quad \text{w.h.p.}$$

Algorithm

- 1 Initialize $x^0 = 0$.
- 2 For $t = 1, \dots, N$, generate independent sketches $S^t \in \mathbb{R}^{m \times n}$ and

$$x^t = \arg \min_{x \in C} \frac{1}{2} \|S^t A(x - x^{t-1})\|_2^2 - \langle A^T(y - Ax^{t-1}), x - x^{t-1} \rangle$$

- 3 Return $\hat{x} = x^N$.

Iterative Hessian Sketch

Properties of IHS:

- $m = O(p)$ to guarantee $\|x^t - x_{ls}\| \leq \rho \|x^{t-1} - x_{ls}\|$ in each iteration;

Iterative Hessian Sketch

Properties of IHS:

- $m = O(p)$ to guarantee $\|x^t - x_{ls}\| \leq \rho \|x^{t-1} - x_{ls}\|$ in each iteration;
- To achieve an accuracy of ϵ , we need $\log(\frac{1}{\epsilon})$ iterations;

Iterative Hessian Sketch

Properties of IHS:

- $m = O(p)$ to guarantee $\|x^t - x_{ls}\| \leq \rho \|x^{t-1} - x_{ls}\|$ in each iteration;
- To achieve an accuracy of ϵ , we need $\log(\frac{1}{\epsilon})$ iterations;
- Optimality:
 - To achieve the same bound as $\|x_{ls} - x_*\| \approx O(\frac{1}{\sqrt{n}})$, we need $N = \log(n)$ iterations;

Iterative Hessian Sketch

Properties of IHS:

- $m = O(p)$ to guarantee $\|x^t - x_{ls}\| \leq \rho \|x^{t-1} - x_{ls}\|$ in each iteration;
- To achieve an accuracy of ϵ , we need $\log(\frac{1}{\epsilon})$ iterations;
- Optimality:
 - To achieve the same bound as $\|x_{ls} - x_*\| \approx O(\frac{1}{\sqrt{n}})$, we need $N = \log(n)$ iterations;
 - Union bound: $\|x^N - x_{ls}\| \leq \rho^N \|x_{ls}\|$, *w.h.p.*

Simulations in the paper




Figure : Left: classical sketch vs. iterative hessian sketch; Right: different choices of $m = \gamma p$.

Simulations - different sketch matrices




Figure : Using different sketch matrices, under Gaussian design. “expon” means Laplace design.

Simulations - model mis-specifications




Figure : Left: exponential design; Right: Laplace design.

Simulations - model mis-specifications cont.




Figure : Left: $y = \sin(Ax) + w$; Right: $y = (Ax)^3 + w$. Both under Gaussian design. Large noise w behaves similarly.

Thank you!

Evaluation for Sketch Performance

Cost Approximation

In terms of f -cost, the approximated \tilde{x} is said to be ϵ -optimal if

$$f(x^{LS}) \leq f(\tilde{x}) \leq (1 + \epsilon)^2 f(x^{LS}).$$

Solution Approximation

In terms of f -cost, the prediction norm defined as

$$\|\tilde{x} - x^{LS}\|_A := \frac{1}{\sqrt{n}} \|A(\tilde{x} - x^{LS})\|_2.$$