

A319-115, 空调开, 防冰关, 构型FULL, DISA+25° C

WEIGHT	Pressure Altitude (ft)									
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000	15000
42000	33.0	32.8	30.5	28.4	26.3	24.0	21.7	19.4	17.2	16.0
44000	30.7	30.5	28.3	26.4	24.4	22.2	20.0	17.9	15.8	14.6
46000	28.5	28.4	26.3	24.4	22.6	20.5	18.4	16.4	14.4	13.3
48000	26.5	26.3	24.4	22.6	20.9	18.9	17.0	15.0	13.1	12.1
50000	24.6	24.4	22.6	21.0	19.3	17.5	15.6	13.8	12.0	11.0
52000	22.9	22.7	21.0	19.4	17.9	16.1	14.4	12.7	10.9	10.0
54000	21.3	21.2	19.6	18.1	16.6	15.0	13.3	11.6	10.0	9.1
56000	20.0	19.8	18.3	16.8	15.5	13.9	12.3	10.7	9.1	8.3
58000	18.7	18.5	17.1	15.7	14.4	12.9	11.4	9.8	8.3	7.5
60000	17.5	17.4	16.0	14.7	13.4	12.0	10.5	9.0	7.6	6.8
62000	16.4	16.3	15.0	13.7	12.5	11.1	9.7	8.3	6.9	6.2
62500	16.1	16.0	14.7	13.5	12.3	10.9	9.5	8.1	6.7	6.0

A319-115W, 空调开, 防冰关, 构型FULL, DISA+25° C

WEIGHT	Pressure Altitude (ft)									
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000	15000
42000	33.3	33.1	30.8	28.7	26.6	24.3	22.0	19.7	17.5	16.3
44000	31.0	30.8	28.6	26.6	24.7	22.5	20.3	18.1	16.0	14.9
46000	28.8	28.6	26.6	24.7	22.9	20.8	18.7	16.7	14.7	13.6
48000	26.7	26.6	24.7	22.9	21.2	19.2	17.3	15.3	13.4	12.4
50000	24.9	24.7	22.9	21.3	19.6	17.8	15.9	14.1	12.3	11.3
52000	23.2	23.0	21.3	19.7	18.2	16.4	14.7	13.0	11.2	10.3
54000	21.6	21.5	19.9	18.4	16.9	15.3	13.6	11.9	10.3	9.4
56000	20.3	20.1	18.6	17.2	15.8	14.2	12.6	11.0	9.4	8.6
58000	19.0	18.8	17.4	16.0	14.7	13.2	11.7	10.2	8.6	7.8
60000	17.8	17.7	16.3	15.0	13.7	12.3	10.8	9.4	7.9	7.1
62000	16.7	16.6	15.3	14.0	12.8	11.4	10.0	8.6	7.2	6.5
62500	16.4	16.3	15.0	13.8	12.6	11.2	9.8	8.4	7.0	6.3

A319-132W, 空调开, 防冰关, 构型FULL, DISA+25° C										
WEIGHT	Pressure Altitude (ft)									
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000	15000
42000	27.2	27.0	25.7	24.5	23.0	21.3	19.7	17.9	15.9	14.8
44000	25.2	25.0	23.8	22.7	21.2	19.7	18.1	16.5	14.5	13.5
46000	23.4	23.2	22.0	21.0	19.6	18.1	16.6	15.1	13.2	12.2
48000	21.6	21.5	20.3	19.3	18.1	16.7	15.3	13.8	12.0	11.1
50000	20.0	19.9	18.8	17.9	16.7	15.3	14.0	12.6	10.9	10.0
52000	18.6	18.4	17.4	16.6	15.4	14.1	12.9	11.5	9.9	9.1
54000	17.3	17.2	16.2	15.4	14.3	13.0	11.8	10.5	9.0	8.2
56000	16.1	16.0	15.1	14.3	13.2	12.1	10.9	9.6	8.2	7.4
58000	15.0	14.9	14.0	13.3	12.2	11.1	10.0	8.8	7.4	6.7
60000	14.0	13.9	13.1	12.3	11.3	10.3	9.2	8.1	6.7	6.0
62000	13.1	12.9	12.2	11.4	10.5	9.5	8.5	7.4	6.1	5.4
62500	12.9	12.7	11.9	11.2	10.3	9.3	8.3	7.2	5.9	5.2

A319-133W, 空调开, 防冰关, 构型FULL, DISA+25° C

WEIGHT	Pressure Altitude (ft)									
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000	15000
42000	27.1	27.0	25.6	24.5	23.3	22.2	20.3	18.2	15.9	14.7
44000	25.2	25.0	23.7	22.6	21.5	20.5	18.7	16.7	14.6	13.4
46000	23.4	23.2	22.0	21.0	19.9	18.9	17.2	15.4	13.3	12.2
48000	21.6	21.5	20.3	19.3	18.4	17.5	15.8	14.1	12.1	11.1
50000	20.0	19.9	18.8	17.9	17.0	16.2	14.5	12.9	11.0	10.0
52000	18.6	18.4	17.4	16.6	15.7	14.9	13.4	11.8	10.0	9.1
54000	17.3	17.2	16.2	15.4	14.5	13.8	12.3	10.8	9.1	8.2
56000	16.1	16.0	15.1	14.3	13.5	12.8	11.3	9.9	8.3	7.4
58000	15.0	14.9	14.0	13.3	12.5	11.8	10.5	9.1	7.5	6.7
60000	14.0	13.9	13.1	12.3	11.6	10.9	9.6	8.3	6.8	6.0
62000	13.1	12.9	12.2	11.4	10.8	10.1	8.9	7.6	6.1	5.4
62500	12.9	12.7	11.9	11.2	10.6	9.9	8.7	7.4	6.0	5.2

A320-214, 空调开, 防冰关, 构型FULL, DISA+25° C

WEIGHT	Pressure Altitude (ft)								
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000
44000	36.7	36.2	33.6	32.3	29.9	26.7	22.2	19.5	16.9
46000	34.2	33.7	31.3	30.0	27.8	24.7	20.5	18.0	15.5
48000	31.8	31.4	29.1	27.9	25.8	23.0	18.9	16.6	14.2
50000	29.7	29.2	27.1	26.0	24.0	21.3	17.5	15.3	13.1
52000	27.7	27.3	25.3	24.2	22.4	19.9	16.2	14.1	12.0
54000	25.9	25.5	23.7	22.6	21.0	18.5	15.0	13.0	11.0
56000	24.3	23.9	22.2	21.2	19.6	17.3	14.0	12.1	10.1
58000	22.9	22.5	20.8	19.9	18.4	16.1	13.0	11.1	9.3
60000	21.5	21.1	19.6	18.6	17.2	15.1	12.0	10.3	8.5
62000	20.2	19.9	18.4	17.5	16.2	14.1	11.2	9.5	7.8
64000	19.0	18.7	17.3	16.5	15.2	13.2	10.4	8.8	7.1
66000	18.0	17.6	16.3	15.5	14.3	12.3	9.6	8.1	6.5
67400	17.2	16.9	15.6	14.8	13.7	11.8	9.1	7.6	6.1

A320-214W, 空调开, 防冰关, 构型FULL, DISA+25° C

WEIGHT	Pressure Altitude (ft)								
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000
44000	37.0	36.5	33.9	32.5	30.2	26.9	22.4	19.8	17.2
46000	34.5	34.0	31.6	30.3	28.1	25.0	20.8	18.3	15.8
48000	32.1	31.6	29.4	28.2	26.1	23.3	19.2	16.9	14.5
50000	30.0	29.5	27.4	26.3	24.3	21.6	17.8	15.6	13.4
52000	28.0	27.6	25.6	24.5	22.7	20.2	16.5	14.4	12.3
54000	26.2	25.8	24.0	22.9	21.3	18.8	15.4	13.4	11.3
56000	24.6	24.2	22.5	21.5	19.9	17.6	14.3	12.4	10.4
58000	23.2	22.8	21.1	20.2	18.7	16.4	13.3	11.4	9.6
60000	21.8	21.4	19.9	18.9	17.5	15.4	12.3	10.6	8.8
62000	20.5	20.2	18.7	17.8	16.5	14.4	11.5	9.8	8.1
64000	19.4	19.0	17.6	16.8	15.5	13.5	10.7	9.1	7.4
66000	18.3	18.0	16.6	15.8	14.6	12.6	9.9	8.4	6.8
67400	17.6	17.3	16.0	15.1	14.0	12.1	9.4	7.9	6.4

A320-232, 空调开, 防冰关, 构型FULL, DISA+25° C

WEIGHT	Pressure Altitude (ft)								
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000
44000	28.4	28.2	27.3	25.2	23.1	21.2	18.8	16.6	14.5
46000	26.3	26.1	25.3	23.3	21.3	19.5	17.3	15.2	13.2
48000	24.4	24.2	23.4	21.6	19.7	18.0	15.9	13.9	12.0
50000	22.7	22.5	21.8	20.0	18.2	16.6	14.6	12.7	10.9
52000	21.1	21.0	20.2	18.6	16.9	15.3	13.4	11.6	9.9
54000	19.6	19.5	18.8	17.3	15.7	14.2	12.4	10.6	9.0
56000	18.3	18.2	17.6	16.1	14.5	13.1	11.4	9.7	8.2
58000	17.1	17.0	16.4	15.0	13.5	12.1	10.5	8.9	7.4
60000	16.0	15.9	15.3	13.9	12.5	11.2	9.6	8.1	6.7
62000	14.9	14.8	14.3	13.0	11.6	10.4	8.9	7.4	6.0
64000	13.9	13.9	13.4	12.1	10.8	9.6	8.1	6.7	5.4
66000	13.0	13.0	12.5	11.3	10.0	8.8	7.5	6.1	4.8
67400	12.4	12.4	11.9	10.7	9.5	8.4	7.0	5.7	4.4

A320-232W, 空调开, 防冰关, 构型FULL, DISA+25° C

WEIGHT	Pressure Altitude (ft)								
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000
44000	28.7	28.5	27.6	25.5	23.4	21.4	19.1	16.9	14.8
46000	26.6	26.4	25.6	23.6	21.6	19.8	17.6	15.5	13.5
48000	24.7	24.5	23.7	21.9	20.0	18.3	16.2	14.2	12.3
50000	23.0	22.8	22.1	20.3	18.5	16.9	14.9	13.0	11.2
52000	21.4	21.3	20.5	18.9	17.2	15.6	13.7	11.9	10.2
54000	19.9	19.8	19.1	17.6	16.0	14.5	12.7	11.0	9.3
56000	18.6	18.5	17.9	16.4	14.8	13.4	11.7	10.0	8.5
58000	17.4	17.3	16.7	15.3	13.8	12.4	10.8	9.2	7.7
60000	16.3	16.2	15.6	14.2	12.8	11.5	9.9	8.4	7.0
62000	15.2	15.2	14.6	13.3	11.9	10.7	9.2	7.7	6.3
64000	14.3	14.2	13.7	12.4	11.1	9.9	8.4	7.0	5.7
66000	13.4	13.3	12.8	11.6	10.3	9.2	7.8	6.4	5.1
67400	12.8	12.7	12.2	11.0	9.8	8.7	7.3	6.0	4.8

A320-251W, 空调开, 防冰关, 构型FULL, DISA+25° C

WEIGHT	Pressure Altitude (ft)								
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000
44000	29.8	29.4	28.9	28.1	25.2	22.4	20.5	18.7	16.6
46000	27.9	27.5	27.1	26.3	23.6	20.9	19.0	17.4	15.4
48000	26.2	25.8	25.4	24.6	22.1	19.5	17.7	16.1	14.3
50000	24.5	24.2	23.8	23.1	20.6	18.2	16.5	14.9	13.1
52000	23.0	22.6	22.3	21.6	19.2	16.9	15.3	13.8	12.1
54000	21.4	21.1	20.8	20.1	17.9	15.7	14.1	12.7	11.1
56000	20.0	19.7	19.4	18.8	16.7	14.5	13.1	11.7	10.1
58000	18.7	18.4	18.1	17.5	15.5	13.5	12.1	10.8	9.3
60000	17.5	17.3	16.9	16.4	14.5	12.5	11.1	9.9	8.5
62000	16.4	16.1	15.8	15.3	13.5	11.6	10.3	9.1	7.7
64000	15.4	15.1	14.8	14.4	12.6	10.8	9.5	8.3	7.0
66000	14.4	14.2	13.9	13.4	11.8	10.0	8.8	7.6	6.4
67400	13.8	13.5	13.3	12.8	11.2	9.5	8.3	7.2	5.9

A321-211, 空调开, 防冰关, 构型FULL, DISA+25° C									
WEIGHT	Pressure Altitude (ft)								
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000
50000	34.8	34.5	31.2	28.5	25.2	21.8	18.8	16.0	13.4
52000	32.6	32.3	29.2	26.6	23.6	20.3	17.4	14.7	12.3
54000	30.5	30.3	27.3	24.9	22.0	18.9	16.2	13.6	11.2
56000	28.6	28.4	25.6	23.3	20.6	17.7	15.0	12.5	10.3
58000	26.9	26.7	24.0	21.9	19.3	16.5	13.9	11.6	9.4
60000	25.4	25.1	22.6	20.5	18.1	15.4	12.9	10.7	8.6
62000	23.9	23.7	21.2	19.3	17.0	14.4	12.0	9.8	7.8
64000	22.6	22.3	20.0	18.2	15.9	13.5	11.2	9.1	7.1
66000	21.3	21.0	18.9	17.1	15.0	12.6	10.4	8.3	6.5
68000	20.1	19.8	17.8	16.1	14.1	11.8	9.6	7.6	5.8
70000	19.0	18.7	16.8	15.2	13.2	11.0	8.9	7.0	5.3
72000	17.9	17.7	15.9	14.4	12.4	10.3	8.3	6.4	4.7
74000	17.0	16.7	15.0	13.6	11.7	9.6	7.7	5.9	4.3
76000	16.1	15.9	14.2	12.8	11.0	9.0	7.1	5.4	3.8
77800	15.3	15.1	13.5	12.2	10.4	8.5	6.6	5.0	3.4

A321-211W, 空调开, 防冰关, 构型FULL, DISA+25° C									
WEIGHT	Pressure Altitude (ft)								
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000
50000	34.9	34.7	31.3	28.6	25.4	22.0	19.0	16.2	13.6
52000	32.8	32.5	29.4	26.8	23.8	20.6	17.7	15.0	12.5
54000	30.7	30.5	27.5	25.1	22.2	19.2	16.4	13.8	11.5
56000	28.9	28.6	25.8	23.5	20.8	17.9	15.2	12.8	10.5
58000	27.1	26.9	24.3	22.1	19.5	16.7	14.2	11.8	9.6
60000	25.6	25.3	22.8	20.8	18.3	15.7	13.2	10.9	8.8
62000	24.1	23.9	21.5	19.6	17.2	14.7	12.3	10.1	8.1
64000	22.8	22.5	20.2	18.4	16.2	13.7	11.4	9.3	7.4
66000	21.5	21.2	19.1	17.4	15.2	12.8	10.6	8.6	6.7
68000	20.3	20.0	18.0	16.4	14.3	12.0	9.9	7.9	6.1
70000	19.2	18.9	17.0	15.5	13.5	11.3	9.2	7.3	5.5
72000	18.2	17.9	16.1	14.6	12.7	10.5	8.5	6.7	5.0
74000	17.2	17.0	15.3	13.8	12.0	9.9	7.9	6.2	4.5
76000	16.3	16.1	14.5	13.1	11.3	9.3	7.4	5.7	4.1
77800	15.6	15.3	13.8	12.4	10.7	8.7	6.9	5.2	3.7

A321-231, 空调开, 防冰关, 构型FULL, DISA+25° C									
WEIGHT	Pressure Altitude (ft)								
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000
50000	29.7	28.3	26.2	24.1	22.0	19.8	17.1	14.7	12.4
52000	27.8	26.4	24.4	22.5	20.5	18.4	15.8	13.5	11.4
54000	26.0	24.7	22.8	21.0	19.1	17.1	14.6	12.5	10.4
56000	24.4	23.2	21.4	19.7	17.8	15.9	13.6	11.5	9.5
58000	22.9	21.8	20.0	18.4	16.7	14.8	12.6	10.6	8.7
60000	21.5	20.4	18.8	17.2	15.6	13.8	11.7	9.7	8.0
62000	20.3	19.2	17.6	16.1	14.6	12.9	10.8	9.0	7.2
64000	19.1	18.1	16.6	15.1	13.6	12.0	10.0	8.2	6.6
66000	18.0	17.0	15.6	14.2	12.7	11.2	9.3	7.6	6.0
68000	17.0	16.1	14.6	13.3	11.9	10.4	8.6	6.9	5.4
70000	16.0	15.1	13.8	12.5	11.2	9.7	7.9	6.3	4.9
72000	15.1	14.3	13.0	11.8	10.4	9.0	7.3	5.8	4.4
74000	14.3	13.5	12.2	11.1	9.8	8.4	6.8	5.3	3.9
76000	13.6	12.8	11.5	10.4	9.2	7.9	6.3	4.8	3.5
77800	12.9	12.1	11.0	9.8	8.7	7.4	5.8	4.4	3.1

A321-231W, 空调开, 防冰关, 构型FULL, DISA+25° C

WEIGHT	Pressure Altitude (ft)								
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000
50000	30.2	28.5	26.4	24.4	22.2	20.0	17.3	14.9	12.7
52000	28.2	26.6	24.6	22.7	20.7	18.6	16.0	13.8	11.6
54000	26.4	24.9	23.0	21.2	19.3	17.3	14.9	12.7	10.7
56000	24.8	23.4	21.6	19.9	18.1	16.1	13.8	11.7	9.8
58000	23.3	22.0	20.2	18.6	16.9	15.1	12.8	10.8	9.0
60000	22.0	20.7	19.0	17.5	15.8	14.0	11.9	10.0	8.2
62000	20.7	19.5	17.9	16.4	14.8	13.1	11.1	9.2	7.5
64000	19.5	18.3	16.8	15.4	13.9	12.2	10.3	8.5	6.8
66000	18.4	17.3	15.8	14.5	13.0	11.4	9.5	7.8	6.2
68000	17.4	16.3	14.9	13.6	12.2	10.7	8.8	7.2	5.6
70000	16.4	15.4	14.0	12.8	11.4	10.0	8.2	6.6	5.1
72000	15.5	14.5	13.2	12.0	10.7	9.3	7.6	6.0	4.6
74000	14.7	13.8	12.5	11.3	10.0	8.7	7.0	5.5	4.1
76000	14.0	13.0	11.8	10.7	9.4	8.1	6.5	5.1	3.7
77800	13.3	12.4	11.2	10.1	8.9	7.6	6.1	4.7	3.4

A332 772C, 空调开, 防冰关, 构型FULL, DISA+25° C

WEIGHT	Pressure Altitude (ft)								
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000
118000	33.9	33.8	31.5	29.4	27.1	24.5	21.3	18.6	16.1
122000	32.2	32.2	30.0	28.0	25.7	23.3	20.2	17.6	15.2
126000	30.7	30.7	28.6	26.7	24.5	22.1	19.2	16.7	14.4
130000	29.3	29.2	27.3	25.4	23.3	21.1	18.2	15.8	13.6
134000	28.0	27.9	26.0	24.3	22.3	20.1	17.3	15.0	12.8
138000	26.7	26.7	24.8	23.1	21.2	19.1	16.4	14.2	12.1
142000	25.5	25.5	23.7	22.0	20.2	18.1	15.6	13.4	11.4
146000	24.4	24.3	22.6	21.0	19.2	17.2	14.8	12.7	10.7
150000	23.3	23.3	21.6	20.1	18.3	16.4	14.0	12.0	10.1
154000	22.4	22.3	20.7	19.2	17.4	15.6	13.3	11.3	9.5
158000	21.4	21.4	19.8	18.3	16.6	14.8	12.6	10.7	9.0
162000	20.5	20.5	19.0	17.5	15.8	14.1	12.0	10.1	8.4
166000	19.7	19.6	18.2	16.7	15.1	13.5	11.4	9.6	7.9
170000	18.9	18.9	17.4	16.0	14.4	12.8	10.8	9.1	7.5
174000	18.2	18.1	16.7	15.3	13.8	12.2	10.3	8.6	7.0
178000	17.5	17.4	16.0	14.6	13.2	11.7	9.8	8.1	6.6
182000	16.8	16.7	15.3	14.0	12.6	11.1	9.3	7.7	6.2
186000	16.1	16.0	14.7	13.4	12.0	10.6	8.8	7.2	5.8
187000	16.0	15.8	14.5	13.3	11.9	10.5	8.7	7.1	5.7

A332 772B, 空调开, 防冰关, 构型FULL, DISA+25° C

WEIGHT	Pressure Altitude (ft)								
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000
118000	33.9	33.8	31.5	29.4	27.1	24.5	20.6	17.9	15.5
122000	32.2	32.2	30.0	28.0	25.7	23.3	19.5	16.9	14.6
126000	30.7	30.7	28.6	26.7	24.5	22.1	18.5	16.0	13.8
130000	29.3	29.2	27.3	25.4	23.3	21.1	17.6	15.2	13.0
134000	28.0	27.9	26.0	24.3	22.3	20.1	16.7	14.4	12.3
138000	26.7	26.7	24.8	23.1	21.2	19.1	15.8	13.6	11.6
142000	25.5	25.5	23.7	22.0	20.2	18.1	15.0	12.8	10.9
146000	24.4	24.3	22.6	21.0	19.2	17.2	14.2	12.1	10.2
150000	23.3	23.3	21.6	20.1	18.3	16.4	13.5	11.5	9.6
154000	22.4	22.3	20.7	19.2	17.4	15.6	12.8	10.8	9.1
158000	21.4	21.4	19.8	18.3	16.6	14.8	12.1	10.2	8.5
162000	20.5	20.5	19.0	17.5	15.8	14.1	11.5	9.7	8.0
166000	19.7	19.6	18.2	16.7	15.1	13.5	10.9	9.1	7.5
170000	18.9	18.9	17.4	16.0	14.4	12.8	10.3	8.6	7.1
174000	18.2	18.1	16.7	15.3	13.8	12.2	9.8	8.1	6.6
178000	17.5	17.4	16.0	14.6	13.2	11.7	9.3	7.7	6.2
182000	16.8	16.7	15.3	14.0	12.6	11.1	8.8	7.2	5.8
186000	16.1	16.0	14.7	13.4	12.0	10.6	8.4	6.8	5.4
187000	16.0	15.8	14.5	13.3	11.9	10.5	8.2	6.7	5.4

A333 772C, 空调开, 防冰关, 构型FULL, DISA+25° C

WEIGHT	Pressure Altitude (ft)								
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000
118000	33.2	33.1	30.9	28.7	26.3	23.8	20.7	18.1	15.7
122000	31.7	31.6	29.5	27.4	25.1	22.7	19.7	17.2	14.8
126000	30.3	30.2	28.2	26.2	24.0	21.6	18.8	16.3	14.1
130000	28.9	28.9	26.9	25.0	22.9	20.6	17.9	15.5	13.3
134000	27.7	27.6	25.7	23.9	21.8	19.7	17.0	14.7	12.6
138000	26.5	26.4	24.6	22.8	20.8	18.8	16.2	13.9	11.9
142000	25.4	25.3	23.5	21.8	19.9	17.9	15.4	13.2	11.3
146000	24.3	24.2	22.5	20.9	19.0	17.1	14.7	12.6	10.7
150000	23.3	23.2	21.6	20.0	18.2	16.3	14.0	12.0	10.1
154000	22.3	22.3	20.7	19.1	17.4	15.6	13.3	11.3	9.5
158000	21.4	21.4	19.8	18.3	16.6	14.9	12.7	10.7	9.0
162000	20.6	20.5	19.0	17.5	15.9	14.2	12.0	10.2	8.5
166000	19.7	19.7	18.2	16.7	15.2	13.5	11.4	9.6	8.0
170000	18.9	18.9	17.4	16.0	14.5	12.9	10.8	9.1	7.5
174000	18.2	18.1	16.7	15.3	13.8	12.3	10.3	8.6	7.0
178000	17.5	17.4	16.0	14.7	13.2	11.7	9.8	8.1	6.6
182000	16.8	16.7	15.3	14.0	12.6	11.1	9.3	7.7	6.2
186000	16.1	16.0	14.7	13.4	12.1	10.6	8.8	7.3	5.8
187000	16.0	15.9	14.5	13.3	11.9	10.5	8.7	7.2	5.7

A333 772B, 空调开, 防冰关, 构型FULL, DISA+25° C

WEIGHT	Pressure Altitude (ft)								
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000
118000	33.2	33.1	30.9	28.7	26.3	23.8	20.0	17.4	15.0
122000	31.7	31.6	29.5	27.4	25.1	22.7	19.0	16.5	14.2
126000	30.3	30.2	28.2	26.2	24.0	21.6	18.1	15.7	13.5
130000	28.9	28.9	26.9	25.0	22.9	20.6	17.2	14.9	12.7
134000	27.7	27.6	25.7	23.9	21.8	19.7	16.4	14.1	12.1
138000	26.5	26.4	24.6	22.8	20.8	18.8	15.5	13.4	11.4
142000	25.4	25.3	23.5	21.8	19.9	17.9	14.8	12.7	10.8
146000	24.3	24.2	22.5	20.9	19.0	17.1	14.1	12.1	10.2
150000	23.3	23.2	21.6	20.0	18.2	16.3	13.4	11.4	9.6
154000	22.3	22.3	20.7	19.1	17.4	15.6	12.8	10.8	9.1
158000	21.4	21.4	19.8	18.3	16.6	14.9	12.1	10.2	8.5
162000	20.6	20.5	19.0	17.5	15.9	14.2	11.5	9.7	8.0
166000	19.7	19.7	18.2	16.7	15.2	13.5	10.9	9.1	7.5
170000	18.9	18.9	17.4	16.0	14.5	12.9	10.4	8.6	7.1
174000	18.2	18.1	16.7	15.3	13.8	12.3	9.8	8.2	6.6
178000	17.5	17.4	16.0	14.7	13.2	11.7	9.3	7.7	6.2
182000	16.8	16.7	15.3	14.0	12.6	11.1	8.8	7.3	5.8
186000	16.1	16.0	14.7	13.4	12.1	10.6	8.4	6.8	5.5
187000	16.0	15.9	14.5	13.3	11.9	10.5	8.3	6.7	5.4

A350, 空调开, 防冰关, 构型FULL, DISA+25° C

WEIGHT	Pressure Altitude (ft)								
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000
142000	25.0	25.0	25.2	25.5	23.6	21.9	19.3	16.6	14.3
146000	23.9	24.0	24.2	24.4	22.6	20.9	18.4	15.8	13.6
150000	22.9	22.9	23.1	23.4	21.6	20.0	17.6	15.1	12.9
154000	21.9	22.0	22.1	22.4	20.7	19.1	16.8	14.3	12.2
158000	21.0	21.1	21.2	21.5	19.8	18.3	16.0	13.6	11.6
162000	20.1	20.3	20.5	20.7	18.9	17.4	15.2	12.9	10.9
166000	19.4	19.6	19.8	20.0	18.1	16.6	14.5	12.2	10.3
170000	18.7	19.0	19.1	19.2	17.3	15.9	13.8	11.6	9.8
174000	18.1	18.4	18.4	18.4	16.5	15.1	13.1	11.0	9.2
178000	17.5	17.8	17.8	17.6	15.8	14.5	12.5	10.4	8.7
182000	16.9	17.2	17.1	16.9	15.1	13.8	11.9	9.9	8.2
186000	16.3	16.7	16.4	16.2	14.5	13.2	11.3	9.4	7.7
190000	15.8	16.2	15.8	15.5	13.9	12.6	10.8	8.9	7.3
194000	15.3	15.6	15.2	14.9	13.3	12.1	10.3	8.4	6.9
198000	14.8	15.1	14.7	14.3	12.7	11.5	9.8	8.0	6.5
202000	14.4	14.6	14.1	13.7	12.2	11.0	9.3	7.6	6.1
206000	14.0	14.1	13.6	13.1	11.7	10.5	8.9	7.2	5.7
207000	13.9	13.9	13.5	13.0	11.6	10.4	8.8	7.1	5.6

B737-700 22K, 空调开, 防冰关, 襟翼40, DISA+25° C

WEIGHT	Pressure Altitude (ft)									
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000	16000
40000	24.7	24.4	23.2	21.8	19.9	17.6	16.1	14.5	13.0	10.1
42000	22.5	22.3	21.1	19.8	18.1	15.9	14.5	13.0	11.6	8.8
44000	20.6	20.4	19.3	18.1	16.4	14.4	13.0	11.6	10.3	7.6
46000	18.9	18.6	17.6	16.5	14.9	13.0	11.7	10.3	9.1	6.6
48000	17.3	17.1	16.1	15.0	13.5	11.7	10.5	9.2	8.0	5.6
50000	15.9	15.6	14.7	13.7	12.3	10.6	9.4	8.2	7.0	4.7
52000	14.5	14.3	13.4	12.5	11.1	9.5	8.4	7.2	6.1	3.9
54000	13.4	13.1	12.3	11.4	10.1	8.5	7.5	6.3	5.3	3.2
56000	12.2	12.0	11.2	10.4	9.1	7.6	6.6	5.5	4.5	2.5
58000	11.2	11.0	10.2	9.4	8.3	6.8	5.8	4.8	3.8	1.9
58604	10.9	10.7	10.0	9.1	8.0	6.6	5.6	4.6	3.6	1.7

B737-700 24K, 空调开, 防冰关, 襟翼40, DISA+25° C										
WEIGHT	Pressure Altitude (ft)									
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000	16000
40000	28.0	27.6	25.6	23.8	21.9	20.1	18.4	16.7	14.8	11.2
42000	25.6	25.3	23.4	21.7	19.9	18.2	16.6	15.0	13.2	9.9
44000	23.5	23.1	21.4	19.8	18.1	16.5	15.0	13.5	11.8	8.7
46000	21.6	21.2	19.6	18.1	16.5	15.0	13.6	12.2	10.6	7.6
48000	19.9	19.5	18.0	16.6	15.1	13.7	12.3	11.0	9.4	6.6
50000	18.3	18.0	16.5	15.2	13.8	12.4	11.1	9.9	8.4	5.7
52000	16.9	16.6	15.2	13.9	12.6	11.3	10.0	8.8	7.4	4.8
54000	15.6	15.3	14.0	12.7	11.5	10.2	9.0	7.9	6.6	4.1
56000	14.4	14.1	12.8	11.7	10.5	9.3	8.1	7.0	5.7	3.4
58000	13.3	13.0	11.8	10.7	9.5	8.4	7.3	6.2	5.0	2.7
58604	12.9	12.7	11.5	10.4	9.2	8.1	7.0	6.0	4.8	2.5

B737-700W 24K, 空调开, 防冰关, 襟翼40, DISA+25° C

WEIGHT	Pressure Altitude (ft)									
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000	16000
40000	28.5	28.1	26.1	24.3	22.4	20.5	18.8	17.1	15.2	11.7
42000	26.1	25.7	23.9	22.2	20.4	18.7	17.1	15.5	13.7	10.3
44000	24.0	23.6	21.9	20.3	18.6	17.0	15.5	14.0	12.3	9.1
46000	22.1	21.7	20.1	18.6	17.0	15.5	14.1	12.6	11.0	8.0
48000	20.3	20.0	18.5	17.0	15.6	14.1	12.8	11.4	9.9	7.0
50000	18.8	18.4	17.0	15.6	14.2	12.9	11.6	10.3	8.8	6.1
52000	17.3	17.0	15.6	14.4	13.0	11.7	10.5	9.3	7.9	5.3
54000	16.0	15.7	14.4	13.2	11.9	10.7	9.5	8.3	7.0	4.5
56000	14.8	14.5	13.3	12.1	10.9	9.7	8.6	7.4	6.2	3.8
58000	13.7	13.4	12.2	11.1	10.0	8.8	7.7	6.6	5.4	3.1
58604	13.4	13.1	11.9	10.8	9.7	8.5	7.5	6.4	5.2	2.9

B737-700W 24A, 空调开, 防冰关, 襟翼40, DISA+25° C

WEIGHT	Pressure Altitude (ft)									
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000	16000
40000	33.7	33.2	31.3	29.5	26.8	23.9	21.9	19.2	16.6	11.7
42000	31.0	30.5	28.7	27.0	24.5	21.8	20.0	17.4	15.0	10.3
44000	28.5	28.1	26.4	24.8	22.5	19.9	18.2	15.8	13.5	9.1
46000	26.3	25.9	24.3	22.9	20.7	18.3	16.7	14.4	12.2	8.0
48000	24.3	23.9	22.5	21.1	19.0	16.8	15.3	13.1	11.0	7.0
50000	22.6	22.2	20.8	19.5	17.5	15.4	14.0	11.9	9.9	6.1
52000	21.0	20.6	19.3	18.0	16.2	14.1	12.8	10.8	8.9	5.3
54000	19.5	19.1	17.9	16.7	14.9	13.0	11.7	9.8	8.0	4.5
56000	18.1	17.8	16.6	15.5	13.8	11.9	10.7	8.8	7.1	3.8
58000	16.9	16.5	15.4	14.3	12.7	10.9	9.7	8.0	6.3	3.1
58604	16.5	16.2	15.1	14.0	12.4	10.6	9.5	7.7	6.1	2.9

B737-800 26K, 空调开, 防冰关, 襟翼40, DISA+25° C

WEIGHT	Pressure Altitude (ft)								
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000
42000	30.3	29.9	28.0	26.3	23.8	21.1	18.6	16.2	13.9
44000	27.9	27.4	25.7	24.1	21.8	19.3	16.9	14.6	12.4
46000	25.7	25.2	23.7	22.1	20.0	17.6	15.4	13.2	11.2
48000	23.7	23.3	21.8	20.4	18.3	16.1	14.0	11.9	10.0
50000	21.9	21.5	20.1	18.7	16.8	14.7	12.7	10.8	8.9
52000	20.3	19.9	18.6	17.3	15.5	13.5	11.5	9.7	7.9
54000	18.8	18.4	17.2	15.9	14.2	12.3	10.5	8.7	7.0
56000	17.4	17.1	15.9	14.7	13.1	11.3	9.5	7.8	6.2
58000	16.2	15.8	14.7	13.6	12.0	10.3	8.6	7.0	5.4
60000	15.0	14.7	13.6	12.5	11.0	9.4	7.7	6.2	4.7
62000	13.9	13.6	12.6	11.5	10.1	8.5	7.0	5.5	4.0
64000	12.9	12.6	11.6	10.6	9.3	7.7	6.2	4.8	3.4
65317	12.3	12.0	11.0	10.1	8.7	7.2	5.8	4.4	3.0

B737-800W 24K, 空调开, 防冰关, 襟翼40, DISA+25° C

WEIGHT	Pressure Altitude (ft)								
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000
42000	25.9	25.6	23.7	22.0	20.2	18.5	16.9	15.3	13.5
44000	23.8	23.4	21.7	20.1	18.4	16.8	15.3	13.8	12.2
46000	21.9	21.5	19.9	18.4	16.8	15.3	13.9	12.5	10.9
48000	20.1	19.8	18.3	16.8	15.4	13.9	12.6	11.3	9.8
50000	18.6	18.2	16.8	15.4	14.0	12.7	11.4	10.1	8.7
52000	17.1	16.8	15.4	14.1	12.8	11.5	10.3	9.1	7.7
54000	15.8	15.5	14.2	13.0	11.7	10.5	9.3	8.2	6.9
56000	14.6	14.3	13.0	11.9	10.7	9.5	8.4	7.3	6.1
58000	13.5	13.2	12.0	10.9	9.7	8.6	7.5	6.5	5.3
60000	12.4	12.1	11.0	9.9	8.9	7.8	6.7	5.7	4.6
62000	11.5	11.2	10.1	9.1	8.0	7.0	6.0	5.0	4.0
64000	10.6	10.3	9.3	8.3	7.3	6.3	5.3	4.4	3.4
65317	10.0	9.7	8.7	7.8	6.8	5.8	4.9	4.0	3.0

B737-800W 26K, 空调开, 防冰关, 襟翼40, DISA+25° C

WEIGHT	Pressure Altitude (ft)								
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000
42000	30.8	30.3	28.5	26.7	24.3	21.6	19.0	16.6	14.3
44000	28.3	27.9	26.2	24.5	22.2	19.7	17.3	15.1	12.9
46000	26.1	25.7	24.1	22.6	20.4	18.1	15.8	13.7	11.6
48000	24.2	23.7	22.2	20.8	18.8	16.6	14.4	12.4	10.4
50000	22.4	22.0	20.5	19.2	17.3	15.2	13.1	11.2	9.3
52000	20.7	20.3	19.0	17.7	15.9	13.9	12.0	10.1	8.3
54000	19.2	18.9	17.6	16.4	14.7	12.8	10.9	9.1	7.4
56000	17.9	17.5	16.3	15.1	13.5	11.7	9.9	8.2	6.6
58000	16.6	16.3	15.1	14.0	12.4	10.7	9.0	7.4	5.8
60000	15.4	15.1	14.0	12.9	11.5	9.8	8.2	6.6	5.1
62000	14.4	14.0	13.0	12.0	10.5	8.9	7.4	5.9	4.4
64000	13.3	13.0	12.0	11.0	9.7	8.1	6.6	5.2	3.8
65317	12.7	12.4	11.4	10.5	9.1	7.7	6.2	4.8	3.4

B737-800WSFP 26K, 空调开, 防冰关, 襟翼40, DISA+25° C

WEIGHT	Pressure Altitude (ft)								
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000
42000	31.0	30.5	28.6	26.9	24.4	21.7	19.1	16.7	14.4
44000	28.5	28.0	26.3	24.7	22.4	19.9	17.4	15.2	13.0
46000	26.3	25.8	24.2	22.7	20.5	18.2	15.9	13.8	11.7
48000	24.3	23.9	22.4	20.9	18.9	16.7	14.5	12.5	10.5
50000	22.5	22.1	20.7	19.3	17.4	15.3	13.2	11.3	9.4
52000	20.9	20.5	19.1	17.8	16.0	14.0	12.1	10.2	8.4
54000	19.4	19.0	17.7	16.5	14.8	12.9	11.0	9.2	7.5
56000	18.0	17.6	16.4	15.3	13.6	11.8	10.0	8.3	6.7
58000	16.7	16.4	15.2	14.1	12.6	10.8	9.1	7.5	5.9
60000	15.6	15.2	14.1	13.1	11.6	9.9	8.3	6.7	5.2
62000	14.5	14.2	13.1	12.1	10.6	9.0	7.5	6.0	4.5
64000	13.5	13.2	12.2	11.2	9.8	8.3	6.7	5.3	3.9
65317	12.8	12.5	11.6	10.6	9.3	7.8	6.3	4.9	3.5

737-8_LEAP-1B27, 空调开, 防冰关, 襟翼40, DISA+25° C

WEIGHT	Pressure Altitude (ft)								
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000
46000	27.5	27.0	25.1	23.1	21.2	17.0	14.9	12.3	10.0
48000	25.4	25.0	23.1	21.3	19.5	15.5	13.5	11.1	8.9
50000	23.5	23.1	21.4	19.6	17.9	14.2	12.3	9.9	7.9
52000	21.8	21.4	19.8	18.1	16.5	12.9	11.1	8.9	6.9
54000	20.3	19.9	18.3	16.7	15.2	11.8	10.1	7.9	6.0
56000	18.8	18.5	17.0	15.5	14.0	10.8	9.1	7.1	5.2
58000	17.5	17.2	15.7	14.3	12.9	9.8	8.2	6.2	4.5
60000	16.3	15.9	14.6	13.2	11.9	8.9	7.4	5.5	3.8
62000	15.2	14.8	13.5	12.2	10.9	8.0	6.6	4.8	3.2
64000	14.1	13.8	12.5	11.3	10.0	7.3	5.9	4.1	2.6
66000	13.1	12.8	11.6	10.4	9.2	6.6	5.2	3.5	2.0
68000	12.2	11.9	10.8	9.6	8.5	5.9	4.6	3.0	1.5
69308	11.7	11.4	10.3	9.2	8.0	5.5	4.2	2.7	1.3

787-9_GENX-1B74-75, 防冰关, 襟翼30, DISA+25° C

WEIGHT	Pressure Altitude (ft)									
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000	16000
128000	32.0	31.6	29.4	27.2	24.9	22.5	19.2	16.5	14.1	10.5
132000	30.5	30.1	28.0	25.9	23.6	21.4	18.2	15.6	13.2	9.8
136000	29.1	28.7	26.7	24.7	22.5	20.3	17.2	14.8	12.5	9.2
140000	27.7	27.3	25.4	23.5	21.4	19.2	16.3	13.9	11.7	8.5
144000	26.4	26.0	24.2	22.3	20.3	18.3	15.4	13.1	11.0	7.9
148000	25.2	24.8	23.1	21.3	19.3	17.3	14.6	12.4	10.4	7.4
152000	24.0	23.7	22.0	20.3	18.4	16.5	13.8	11.7	9.8	6.9
156000	23.0	22.7	21.0	19.3	17.5	15.7	13.1	11.1	9.2	6.4
160000	22.0	21.7	20.1	18.5	16.7	14.9	12.4	10.5	8.6	5.9
164000	21.0	20.7	19.2	17.6	15.9	14.2	11.8	9.9	8.1	5.4
168000	20.1	19.9	18.4	16.8	15.2	13.5	11.2	9.3	7.6	5.0
172000	19.3	19.0	17.6	16.1	14.5	12.9	10.6	8.8	7.1	4.6
176000	18.5	18.2	16.8	15.4	13.8	12.2	10.1	8.3	6.7	4.2
180000	17.7	17.5	16.1	14.7	13.2	11.7	9.6	7.9	6.2	3.9
184000	17.0	16.8	15.4	14.1	12.6	11.1	9.1	7.4	5.8	3.6
188000	16.3	16.1	14.8	13.4	12.0	10.6	8.6	7.0	5.4	3.3
192000	15.7	15.4	14.2	12.9	11.5	10.1	8.2	6.6	5.1	3.0
193000	15.5	15.3	14.0	12.7	11.3	10.0	8.1	6.5	5.0	2.9

777-300ER_GE90-115BL, 防冰关, 襟翼30, DISA+25° C

WEIGHT	Pressure Altitude (ft)								
KG	-2000	0	2000	4000	6000	8000	10000	12000	14000
171000	35.2	34.7	32.2	29.4	26.3	22.8	19.7	17.0	14.6
175000	33.8	33.3	31.0	28.3	25.2	21.9	18.8	16.2	13.9
179000	32.5	32.0	29.8	27.2	24.2	21.0	18.0	15.5	13.2
183000	31.3	30.8	28.6	26.1	23.3	20.1	17.2	14.8	12.5
187000	30.2	29.7	27.6	25.2	22.4	19.3	16.5	14.1	11.9
191000	29.1	28.6	26.6	24.2	21.5	18.5	15.7	13.4	11.3
195000	28.0	27.6	25.6	23.3	20.7	17.7	15.1	12.8	10.8
199000	27.0	26.6	24.7	22.5	19.9	17.0	14.4	12.2	10.2
203000	26.1	25.7	23.8	21.7	19.2	16.3	13.8	11.7	9.7
207000	25.2	24.8	23.0	20.9	18.5	15.7	13.2	11.1	9.2
211000	24.4	24.0	22.3	20.2	17.8	15.1	12.7	10.6	8.8
215000	23.6	23.2	21.5	19.5	17.2	14.5	12.1	10.2	8.3
219000	22.8	22.4	20.8	18.8	16.5	13.9	11.6	9.7	7.9
223000	22.1	21.7	20.1	18.2	16.0	13.4	11.1	9.2	7.5
227000	21.4	21.0	19.4	17.6	15.4	12.9	10.7	8.8	7.1
231000	20.7	20.3	18.8	17.0	14.8	12.4	10.2	8.4	6.7
235000	20.0	19.7	18.2	16.4	14.3	11.9	9.8	8.0	6.3
239000	19.4	19.0	17.6	15.8	13.8	11.4	9.4	7.6	6.0
243000	18.8	18.4	17.0	15.3	13.3	11.0	9.0	7.2	5.7
247000	18.2	17.9	16.5	14.8	12.8	10.6	8.6	6.9	5.3
251000	17.6	17.3	16.0	14.3	12.4	10.2	8.2	6.5	5.0
251290	17.6	17.3	15.9	14.3	12.3	10.1	8.2	6.5	5.0