

# Dry Type Transformer

English Product Datasheet | Southeast Asia Project Selection



|          |                                    |
|----------|------------------------------------|
| Document | WZE-DS-DTT-EN-R0                   |
| Revision | R0   14 July 2026                  |
| Language | English                            |
| Status   | Preliminary product selection data |

## Product Overview

Wenze cast-resin dry-type transformers use solid insulation and air cooling for indoor substations, commercial buildings, data centers, hospitals and industrial distribution rooms. Cooling, enclosure, environmental class and monitoring are selected against the approved installation conditions.

## Typical Selection Range

|                     |                                                |
|---------------------|------------------------------------------------|
| Rated capacity      | 125-2500 kVA                                   |
| Primary voltage     | 6-35 kV                                        |
| Secondary voltage   | 0.4 / 0.415 kV or project-specific             |
| Frequency           | 50 Hz / 60 Hz                                  |
| Phase               | Three-phase                                    |
| Cooling             | AN / AF                                        |
| Vector group        | Dyn11 / Yyn0 or project-specific               |
| Insulation medium   | Cast resin                                     |
| Applicable standard | IEC 60076-11 or approved project standard      |
| Standard altitude   | Up to 1000 m; higher altitude by design review |

Important: This document supports preliminary product selection. It does not replace the project-specific approved datasheet, drawings, technical agreement or routine test report.



## Southeast Asia Project Selection

Common regional configurations are shown for inquiry preparation. The destination utility, local regulations and site conditions remain the governing requirements.

| Parameter                           | Typical Project Selection                                      | Confirmation Basis                                                                 |
|-------------------------------------|----------------------------------------------------------------|------------------------------------------------------------------------------------|
| <b>Common voltage ratios</b>        | 10/0.4 kV, 11/0.415 kV, 20/0.4 kV, 22/0.415 kV and 33/0.415 kV | Final ratio follows the destination utility specification.                         |
| <b>Frequency</b>                    | 50 Hz / 60 Hz according to the destination-country utility     | Frequency and voltage ratio are confirmed against the local utility specification. |
| <b>Enclosure protection</b>         | IP00 open indoor; IP20 or IP23 enclosure options               | Final IP level depends on ventilation and site requirements.                       |
| <b>Environmental classification</b> | Climatic, environmental and fire-behaviour classes             | Classes are confirmed under IEC 60076-11 for the approved design.                  |
| <b>Temperature monitoring</b>       | Winding sensors, controller and optional cooling fans          | Alarm and trip contacts are configured to the project interface.                   |
| <b>Testing</b>                      | IEC 60076-11 routine tests                                     | Type and special tests are available when included in the agreed scope.            |

### Key Product Features

- No insulating oil and reduced fire risk for indoor applications
- Cast-resin windings designed for humid and demanding environments
- AN natural-air cooling with AF forced-air option
- Temperature monitoring and enclosure options configured to order

### Guaranteed Data Confirmed After Design Review

- No-load loss and load loss at the stated reference temperature
- Short-circuit impedance and no-load current
- Insulation system, temperature rise and environmental classes
- Sound level, enclosure, overall dimensions and total weight
- Monitoring accessories, terminal arrangement and general arrangement drawing

### Typical Applications

- Commercial buildings and shopping centers
- Data centers and communication facilities
- Hospitals and public buildings
- Indoor industrial distribution rooms
- Rail, metro and infrastructure projects

### Information Required for Quotation

- Transformer or substation type
- Rated capacity and quantity
- Primary and secondary voltage
- Frequency, phase and vector group
- Destination country and utility specification
- Indoor/outdoor service, ambient temperature and altitude
- Required accessories, protection and metering
- Delivery schedule and applicable standard

Important: Final guaranteed performance, dimensions, weight, accessories and document scope are stated only in the approved project documents issued for the applicable order.