

Dry Type Transformer

English Product Datasheet | Preliminary Project Reference



Document	WZE-DS-DTT-EN-R2
Revision	R2 30 September 2026
Language	English
Status	Preliminary project reference data

Product Overview

Wenze cast-resin dry-type transformers use solid insulation and air cooling for indoor substations, commercial buildings, data centers, hospitals and industrial distribution rooms. Cooling, enclosure, environmental class and monitoring are selected against the approved installation conditions.

Typical Selection Range

Rated capacity	125-2500 kVA
Primary voltage	6-35 kV
Secondary voltage	0.4 / 0.415 kV or project-specific
Frequency	50 Hz / 60 Hz
Phase	Three-phase
Cooling	AN / AF
Vector group	Dyn11 / Yyn0 or project-specific
Insulation medium	Cast resin
Applicable standard	IEC 60076-11 or approved project standard
Standard altitude	Up to 1000 m; higher altitude by design review

Important: This document supports preliminary product selection. It does not replace the project-specific approved datasheet, drawings, technical agreement or routine test report.



Project Selection Reference

Typical configurations are shown for inquiry preparation. The destination utility specification, applicable local requirements and site conditions govern final selection.

Parameter	Typical Project Selection	Confirmation Basis
Common voltage ratios	10/0.4 kV, 11/0.415 kV, 20/0.4 kV, 22/0.415 kV and 33/0.415 kV	Final ratio follows the destination utility specification.
Frequency	50 Hz / 60 Hz according to the destination-country utility	Frequency and voltage ratio are confirmed against the local utility specification.
Enclosure protection	IP00 open indoor; IP20 or IP23 enclosure options	Final IP level depends on ventilation and site requirements.
Environmental classification	Climatic, environmental and fire-behaviour classes	Classes are confirmed under IEC 60076-11 for the approved design.
Temperature monitoring	Winding sensors, controller and optional cooling fans	Alarm and trip contacts are configured to the project interface.
Testing	IEC 60076-11 routine tests	Type and special tests are available when included in the agreed scope.

Key Product Features

- No insulating oil and reduced fire risk for indoor applications
- Environmental class and humidity suitability confirmed for the project
- AN natural-air cooling with AF forced-air option
- Temperature monitoring and enclosure options configured to order

Guaranteed Data Confirmed After Design Review

- No-load loss and load loss at the stated reference temperature
- Short-circuit impedance and no-load current
- Insulation system, temperature rise and environmental classes
- Sound level, enclosure, overall dimensions and total weight
- Monitoring accessories, terminal arrangement and general arrangement drawing

Typical Applications

- Commercial buildings and shopping centers
- Data centers and communication facilities
- Hospitals and public buildings
- Indoor industrial distribution rooms
- Rail, metro and infrastructure projects

Information Required for Quotation

- Transformer or substation type
- Rated capacity and quantity
- Primary and secondary voltage
- Frequency, phase and vector group
- Destination country and utility specification
- Indoor/outdoor service, ambient temperature and altitude
- Required accessories, protection and metering
- Delivery schedule and applicable standard

Important: Final guaranteed performance, dimensions, weight, accessories and document scope are stated only in the approved project documents issued for the applicable order.