

rocr::Addr::V2::Gfx10Lib
::HwlGetPreferredSurfaceSetting

rocr::Addr::V2::Gfx11Lib
::HwlGetPreferredSurfaceSetting

rocr::Addr::V2::Gfx9Lib
::HwlGetPreferredSurfaceSetting

rocr::Addr::V2::Lib
::IsBlockTypeAvaiable

```
graph LR; A[rocr::Addr::V2::Gfx10Lib::HwlGetPreferredSurfaceSetting] --> D[rocr::Addr::V2::Lib::IsBlockTypeAvaiable]; B[rocr::Addr::V2::Gfx11Lib::HwlGetPreferredSurfaceSetting] --> D; C[rocr::Addr::V2::Gfx9Lib::HwlGetPreferredSurfaceSetting] --> D;
```

The diagram illustrates a mapping from three specific GPU library functions to a common target function. On the left, three white rectangular boxes are stacked vertically. Each box contains the name of a function: the top box is for Gfx10Lib, the middle for Gfx11Lib, and the bottom for Gfx9Lib. All three functions are named ::HwlGetPreferredSurfaceSetting. Blue arrows originate from the right side of each of these three boxes and point towards a single gray rectangular box on the right. This gray box contains the name of the target function: ::IsBlockTypeAvaiable, which is part of the rocr::Addr::V2::Lib namespace.