

Lecture 13

Image Blending

Dr. Xiran Cai

Email: caixr@shanghaitech.edu.cn

Office: 3-438 SIST

Tel: 20684431

ShanghaiTech University



Long history of fake images



Long history of fake images

1950



Long history of fake images




Hard edge composition vs Pyramid Blending


Apple



Orange



Direct Connection



Pyramid Blending




Hard compositing

❑ Hard compositing:





$$I(x, y) = M(x, y)S(x, y) + (1 - M(x, y))T(x, y)$$

$$= \begin{cases} S(x, y) & M(x, y) = 1 \\ T(x, y) & M(x, y) = 0 \end{cases}$$




❑ Generally bad: seam/matte line is visible




Weighted transition region



Weighted transition region



Good window size



Pyramid blending

❑ Better idea: Multi-resolution blending with a Laplacian pyramid.

- Idea: wide transition regions for low-frequency component, narrow transition regions for high-frequency component (edges).
- Gaussian pyramid:

G = 5x5 Gaussian filter

I_0 = original image (full resolution)

$$\bullet I_i = (G * I_{i-1}) \downarrow 2$$

↑
Convolution

← Down-sample
by 2 in both directions

- Get a series of smaller and blurry images.



What does blurring take away?



What does blurring take away?



What does blurring take away?




Pyramid blending

□ Difference of Gaussian at each scale:

High-pass image at scale i $\longrightarrow L_i = I_i - \boxed{(G * I_i) \downarrow 2}$ \longleftarrow Blurred version of level i

\uparrow
Gaussian pyramid image at scale i




$\{L_i\}$ = the set of L_i form. A Laplacian pyramid $L_1, L_2, L_3, \dots, L_n$

Pyramid blending


□ We can recover the original as:

$$I = \sum_{i=0}^N (L_i) \uparrow$$




$\{L_i\}$ = the set of L_i form. A Laplacian pyramid $L_1, L_2, L_3, \dots, L_n$


Pyramid blending



Left pyramid





blend



Right pyramid

Pyramid blending



Season blending




Season blending



Target image




Target image with editing region



Source image



Result of pyramid blending




Poisson image editing

- ❑ A better idea: to reduce the color mismatch between source and target, create composite in gradient domain.
- ❑ We want the gradient of the composite inside Ω to look as close as possible to the source image gradient. The composite must match target image on the boundary $\partial\Omega$.

$$\min_{I(x,y) \in \Omega} \|\nabla I(x,y) - \nabla S(x,y)\|^2 dx dy$$

$$s.t. I(x,y) = T(x,y) \text{ on } \partial\Omega$$



Poisson image editing

□ Solution for this Pb:


$$\nabla^2 I(x, y) = \nabla^2 S(x, y) \text{ in } \Omega$$

$$I(x, y) = T(x, y) \text{ on } \partial\Omega$$

➤ Poisson equation

➤ Discretizing and solving the problem:

➤ 1) For a pixel A inside Ω ,



$$\nabla^2 I(x, y) = \nabla^2 S(x, y)$$

	1	
1	-4	1
	1	

$$\begin{array}{ccc}
 & \uparrow & \uparrow \\
 I(x+1, y) + I(x, y+1) + & S(x+1, y) + S(x, y+1) + \\
 I(x-1, y) + I(x, y-1) - & S(x-1, y) + S(x, y-1) - \\
 4 * I(x, y) & 4 * S(x, y)
 \end{array}$$


Poisson image editing

- For a pixel B not inside Ω (whose neighbor is Ω).

$$\nabla^2 I(x, y) = \nabla^2 S(x, y)$$

$$\begin{array}{c} \uparrow \\ I(x+1, y) + I(x, y+1) + \\ T(x-1, y) + T(x, y-1) - \\ 4 * I(x, y) \end{array}$$

$$\begin{array}{c} \uparrow \\ S(x+1, y) + S(x, y+1) + \\ S(x-1, y) + S(x, y-1) - \\ 4 * S(x, y) \end{array}$$



- Big linear system : so in all there will be N unknowns and N


equations that can be divided into 3 different groups

<p>5 non-zeros values in a row</p> <hr style="border-top: 1px dashed blue;"/> <p>3 non-zeros values in a row</p> <hr style="border-top: 1px dashed red;"/> <p>1 non-zeros value in a row</p>	$\begin{bmatrix} -4 & 1 & 0 & \dots & 0 & 1 & 0 & \dots & 0 \\ 1 & -4 & 1 & 0 & \dots & 0 & 1 & \dots & 0 \\ \dots & 1 & -4 & 1 & 0 & \dots & 0 & 0 & 0 \\ 0 & 0 & \dots & 1 & 0 & 0 & 0 & 0 & 0 \end{bmatrix}$	$\begin{bmatrix} I_1 \\ I_2 \\ \vdots \\ I_N \end{bmatrix}$	$= \begin{bmatrix} \nabla^2 S_1 \\ \nabla^2 S_2 \\ \vdots \\ \nabla^2 S_n - \sum T_n \\ T_N \end{bmatrix}$	<p>Group 1: $A \in \Omega$</p> <hr style="border-top: 1px dashed blue;"/> <p>Group 2: $B \in \partial\Omega \cap \Omega$</p> <hr style="border-top: 1px dashed red;"/> <p>Group 3: $C \in \partial\Omega$</p>
--	---	---	--	--

Source image



Target image



Poisson image editing result



Take home message

- ❑ Pyramid image blending is able to merge two images with similar background, but it is not robust for color mismatch.
- ❑ Poisson image edit is more powerful on image blending Pbs with variations on background color.