

Table1 The original class Database in ApacheHSQLDB

Original Class Database	
Attributes	Methods
sqlEnforceStrictSize	checkColumnIsInView(String, String)
urlProperties	classLoader
userManager	clearStructures()
CLOSEMODE_COMPACT	close(int)
CLOSEMODE_IMMEDIATELY	connect(String, String)
CLOSEMODE_NORMAL	dropIndex(Session, String, String, boolean)
CLOSEMODE_SCRIPT	dropTrigger(Session, String)
DATABASE_CLOSING	finalize()
DATABASE_ONLINE	findUserTableForIndex(Session, String)
DATABASE_OPENING	firstIdentity
DATABASE_SHUTDOWN	getAliasMap()
bIgnoreCase	getJavaName(String)
bReferentialIntegrity	getPath()
databaseID	getProperties()
databaseProperties	getSessionManager()
databaseReadOnly	getState()
dbState	getStateString()
filesInJar	getTable(Session, String)
filesReadOnly	getTableIndex(Table)
compiledStatementManager	getType()
hAlias	getURI()
logger	getUserManager()
sName	getUserTable(Session, String)
sPath	getViewsWithSequence(NumberSequence)
sType	getViewsWithTable(String, String)
sessionManager	getViewsWithView(View)
	isFilesInJar()
	isFilesReadOnly()
	isIgnoreCase()
	isReferentialIntegrity()
	isShutdown()
	linkTable(Table)
	nameManager
	open()
	recompileViews(String)
	removeExportedKeys(Table)
	reopen()
	setFilesReadOnly()
	setIgnoreCase(boolean)
	setMetaDirty(boolean)
	setReadOnly()

	setReferentialIntegrity(boolean) setState(int)
--	---

Table2 The new classes extracted by developers

Class Extracted by the Developers - 1	
Attributes	Methods
firstIdentity bIgnoreCase bReferentialIntegrity databaseProperties hAlias userManager nameManager sessionManager compiledStatementManager DATABASE_ONLINE DATABASE_OPENING DATABASE_CLOSING DATABASE_SHUTDOWN CLOSEMODE_IMMEDIATELY CLOSEMODE_NORMAL CLOSEMODE_COMPACT CLOSEMODE_SCRIPT databaseID sType sName urlProperties sPath classLoader dbState logger databaseReadOnly filesReadOnly filesInJar sqlEnforceStrictSize	open() reopen() clearStructures() getType() getPath() getProperties() getSessionManager() isShutdown() connect(String username, String password) setReadOnly() setFilesReadOnly() isFilesReadOnly() isFilesInJar() getUserManager() setReferentialIntegrity(ref) isReferentialIntegrity() getAliasMap() getJavaName(String s) setIgnoreCase(b) isIgnoreCase() finalize() close(closemode) setMetaDirty(resetPrepared) setState(state) getState() getStateString() getURI()
Class Extracted by the Developers - 2	
Attributes	Methods
Variables	getTable(Session, String) getUserTable(Session, String) linkTable(Table t) findUserTableForIndex(Session, String) getTableIndex(Table) dropIndex(Session, String, StringName, boolean) checkColumnIsInView(String, String) getViewsWithView(View)

	getViewsWithTable(String, String) getViewsWithSequence(NumberSequence) recompileViews(String) removeExportedKeys(Table) dropTrigger(Session, String)
--	--

Table3 The new classes extracted by our approach

Class Extracted our approach - 1	
Attributes	Methods
firstIdentity bIgnoreCase bReferentialIntegrity databaseProperties hAlias userManager nameManager sessionManager compiledStatementManager DATABASE_ONLINE DATABASE_OPENING DATABASE_CLOSING DATABASE_SHUTDOWN CLOSEMODE_IMMEDIATELY CLOSEMODE_NORMAL CLOSEMODE_COMPACT CLOSEMODE_SCRIPT databaseID sType sName urlProperties sPath classLoader dbState logger databaseReadOnly filesReadOnly filesInJar sqlEnforceStrictSize	open() reopen() clearStructures() getType() getPath() getProperties() getSessionManager() isShutdown() connect(String username, String password) setReadOnly() setFilesReadOnly() isFilesReadOnly() isFilesInJar() getUserManager() setReferentialIntegrity(ref) isReferentialIntegrity() getAliasMap() getJavaName(String s) setIgnoreCase(b) isIgnoreCase() finalize() close(closemode) setMetaDirty(resetPrepared) setState(state) getState() getStateString() getURI()
Class Extracted our approach - 2	
Attributes	Methods
Variables	getTable(Session, String) getUserTable(Session, String) linkTable(Table t) findUserTableForIndex(Session, String)

	getTableIndex(Table) dropIndex(Session, String, StringName, boolean) checkColumnIsInView(String, String) getViewsWithView(View) getViewsWithTable(String, String) getViewsWithSequence(NumberSequence) recompileViews(String) removeExportedKeys(Table) dropTrigger(Session, String)
--	--

Table 4 The new classes extracted by Bavota's approach[14]

Class Extracted Bavota's approach - 1	
Attributes	Methods
	checkColumnIsInView(String, String) connect(String, String) dropIndex(Session, String, String, boolean) dropTrigger(Session, String) finalize() findUserTableForIndex(Session, String) getAliasMap() getJavaName(String) getPath() getProperties() getSessionManager() getState() getStateString() getTable(Session, String) getTableIndex(Table) getType() getURI() getUserManager() getUserTable(Session, String) isFilesInJar() isFilesReadOnly() isIgnoreCase() isReferentialIntegrity() linkTable(Table) recompileViews(String) removeExportedKeys(Table) setFilesReadOnly() setIgnoreCase(boolean) setMetaDirty(boolean) setReadOnly() setReferentialIntegrity(boolean)

	setState(int) close(int) open()
Class Extracted Bavota's approach - 2	
Attributes	Methods
CLOSEMODE_COMPACT DATABASE_ONLINE DATABASE_CLOSING nameManager hAlias CLOSEMODE_IMMEDIATELY DATABASE_OPENING CLOSEMODE_SCRIPT CLOSEMODE_NORMAL DATABASE_SHUTDOWN databaseID databaseProperties sqlEnforceStrictSize firstIdentity sName sType sPath urlProperties filesInJar classLoader userManager logger sessionManager filesReadOnly databaseReadOnly compiledStatementManager bIgnoreCase bReferentialIntegrity Variables	getViewsWithTable(String, String) getViewsWithSequence(NumberSequence) getViewsWithView(View) clearStructures() reopen() isShutdown()

Table 5 The new classes extracted by Fokaefs' approach

Class Extracted Fokaefs' approach - 1	
Attributes	Methods
CLOSEMODE_COMPACT DATABASE_ONLINE DATABASE_CLOSING hAlias CLOSEMODE_IMMEDIATELY DATABASE_OPENING	getStateString() open() isShutdown() dbState getState() setState(int)

CLOSEMODE_SCRIPT CLOSEMODE_NORMAL DATABASE_SHUTDOWN databaseID databaseProperties sName sType sPath urlProperties filesInJar classLoader userManager logger sessionManager filesReadOnly bIgnoreCase bReferentialIntegrity Variables	finalize() getJavaName(String) getAliasMap() getProperties() sqlEnforceStrictSize firstIdentity getURI() getType() getPath() isFilesInJar() getUserManager() getSessionManager() connect(String, String) close(int) setReadOnly() setFilesReadOnly() isFilesReadOnly() databaseReadOnly compiledStatementManager setMetaDirty(boolean) isIgnoreCase() setIgnoreCase(boolean) setReferentialIntegrity(boolean) isReferentialIntegrity()
Class Extracted Fokaefs' approach - 2	
Attributes	Methods
nameManager	getUserTable(Session, String) dropIndex(Session, String, String, boolean) checkColumnIsInView(String, String) recompileViews(String) dropTrigger(Session, String) findUserTableForIndex(Session, String) reopen() clearStructures() removeExportedKeys(Table) getViewsWithView(View) getViewsWithTable(String, String) getViewsWithSequence(NumberSequence) getTableIndex(Table) getTable(Session, String) linkTable(Table)