

Design Specification - Case T2R1NOCEILING

Best-effort design L (AnPorUp). NEGATIVE RESULT: ED/SEI100/lowT PASS; 4C plating and SEI500 FAIL for every design in the admissible space. Full text: design_spec.md.

Design	Round	ED Wh/kg	SEI100 mS	SEI500 mS	lowT
Baseline Chen2020		400.3	449.1	777.9	0.9943
A ThinCC	R2	456.4	449.1	777.9	0.9943
B HiCond (sigma R2, D x1.7, t+0.4)		404.1	476.8	829.8	0.9945
C SmallNeg (r 3.5um)	R2	407.0	452.9	771.4	0.9944
D LowLoad (x0.72)	R2	355.6	481.0	836.8	0.9940
E ThickNeg (N/P R3)		478.6	494.6	865.6	0.9999
F ThinSep (9 um R0.55)		458.6	455.0	787.9	0.9943
G ThickNeg+ThinSep		480.0	496.2	868.9	0.9999
H ThickNeg2 (N/P R3.77)		452.1	540.0	979.9	1.0000
I Cool (h 100)	R4	454.1	454.1	786.4	0.9919
J CathPartUp (1254um)		376.4	463.3	856.7	0.9999
K TransDown (degenerate)		238.2	68.0	68.0	1.0000
L AnPorUp (SELECTED)		476.7	467.6	811.3	0.9944