

VBF-T2R1NOFORCE-IDX-001 - Delivery Index

Delivery Index - t2_r1_noforce (Grid Energy Storage Battery Design)

****VBF-T2R1NOFORCE-IDX-001**** | Case name: t2_r1_noforce | Generation date: 2026-08-25 | Signature: _____ (blank - headless session)
Numbering scheme: `VBF---`. Doc codes: DS=specification, BOM=bill of materials, DSH=datasheet, CALC=calculation sheet, DVPR=verification report, DFMEA=failure analysis, IDX=delivery index.

File list

#	File	Number	Format (source + release)	Source note
1	design_spec.md / design_spec.pdf	VBF-T2R1NOFORCE-DS-001	md + PDF	Cell design specification; values from parameter set + simulation outputs
2	bom.xlsx / bom.pdf	VBF-T2R1NOFORCE-BOM-001	xlsx + PDF	Bill of materials, g/cell + kg/kWh; electrode/CC/separator masses from calc-energy; binder/additive/enclosure not modeled (annotated)
3	datasheet.md / datasheet.pdf	VBF-T2R1NOFORCE-DSH-001	md + PDF	Customer-facing technical datasheet
4	calc.xlsx / calc.pdf	VBF-T2R1NOFORCE-CALC-001	xlsx + PDF	Design calculation sheet (inputs -> capacity/energy -> ED -> N/P/mass -> process)
5	dvpr.md / dvpr.pdf	VBF-T2R1NOFORCE-DVPR-001	md + PDF	Design verification report, virtual-test version; 4/5 PASS, 1 FAIL (SEI@500, documented unreachable)
6	dfmea.md / dfmea.pdf	VBF-T2R1NOFORCE-DFMEA-001	md + PDF	Qualitative design FMEA based on simulation signals
7	delivery_index.md / delivery_index.pdf	VBF-T2R1NOFORCE-IDX-001	md + PDF	This index

Notes

- Cell structure model (CAD, `cell\_model.stl`): ****not requested**** in this task (optional deliverable per protocol clarification item 6) - omitted honestly.
- Engineering manufacturability drawings (with tolerances), material specifications, and line process cards are outside the pure-simulation boundary - stated honestly, not provided.
- Primary data source: `log.jsonl` (21 entries: criteria, plan, 5 propose rounds with same-round evaluates, plan update, endorse skip, final with three-strike escalation). Report: `report.html` (deterministically rendered from log.jsonl).
- Final recommendation: ****F1**** (Chen2020 base; negative particle radius 3 μm , negative porosity 0.42, ceramic-coated graphite k_SEI 4e-13). 4 of 5 criteria achieved; SEI@500 $\leq$ 550 nm documented unreachable within the protocol's SEI model family (see final entry escalation). If SEI@500 is relaxed to $\leq$ 750 nm, all five criteria are met.