

Bill of Materials

VBF Case t2_r3 | VBF-T2R3-BOM-01 | Virtual simulation calibre | Generated 2026-08-26

Sheet: BOM

Component	Material	Mass (g/cell)	kg/kWh
Positive electrode active material	NMC811	16.1685	0.876
Positive electrode conductive additive	Carbon black	0.3368	0.01825
Positive electrode binder	PVDF	0.3368	0.01825
Negative electrode active material	Graphite	8.3513	0.45247
Negative electrode conductive additive	Carbon black	0.174	0.00943
Negative electrode binder	CMC/SBR	0.174	0.00943
Separator	Polyolefin, 12 µm (porosity 0.47)	0.2593	0.01405
Electrolyte	LiPF6 in EC/EMC carbonate, 1 M-class (electrolyte density 1.2 g/cm3 [E])	8.0163	0.43432
Positive current collector	Al foil 16 µm	4.4366	0.24037
Negative current collector	Cu foil 12 µm	11.0423	0.59827
Enclosure / tabs	—	Not modeled	—
SUMMARY			
Total mass (contract, electrolyte excluded)	41.280 g		41.27959999999999
Total mass incl. electrolyte (estimate)	49.296 g		49.2959
Cell energy (DFN 1C)	18.4572 Wh		
Material usage per unit energy (contract)	0.04128	kg/kWh	