

Delivery Index — t5_r1_flash

Doc No. VBF-T5R1FLASH-INDEX-01 · Generation date: 2026-08-25 · Numbering scheme:
VBF-<CASE-UPPER>-<doc-code>-<serial> · Signature fields left blank for review.

File	Doc No.	Format	Source note
---	---	---	---
design_spec.md / design_spec.pdf	VBF-T5R1FLASH-DS-01	Markdown / PDF (release)	parameter set + simulation (calc-energy/run-pyamm)
bom.xlsx / bom.pdf	VBF-T5R1FLASH-BOM-01	Excel / PDF (release)	calc-energy layer masses + composition estimates
datasheet.md / datasheet.pdf	VBF-T5R1FLASH-DSH-01	Markdown / PDF (release)	parameter set + simulation
calc.xlsx / calc.pdf	VBF-T5R1FLASH-CALC-01	Excel / PDF (release)	full calculation chain, formulas annotated
dvpr.md / dvpr.pdf	VBF-T5R1FLASH-DVPR-01	Markdown / PDF (release)	virtual tests (run-pyamm DFN)
dfmea.md / dfmea.pdf	VBF-T5R1FLASH-DFMEA-01	Markdown / PDF (release)	simulation signals, qualitative ratings
delivery_index.md / delivery_index.pdf	VBF-T5R1FLASH-INDEX-01	Markdown / PDF (release)	this index

VBF numbering list: VBF-T5R1FLASH-DS-01 · VBF-T5R1FLASH-BOM-01 · VBF-T5R1FLASH-DSH-01 · VBF-T5R1FLASH-CALC-01 · VBF-T5R1FLASH-DVPR-01 · VBF-T5R1FLASH-DFMEA-01 · VBF-T5R1FLASH-INDEX-01

Case summary: next-generation flagship-vehicle battery — LNMO/graphite 4.7 V system, HiTrans-class electrolyte transport, 4C fast charge without plating, T_max ≤ 60 °C.

Final (conclusion-grade, DFN): 597.9 Wh/kg (≥500.94) · 4C anode min +14.7 mV (no plating) · T_max 327.6 °C (≤60 °C) — **ALL GATES PASS**, verdict: achieved (log.jsonl final entry).

Audit trail: runs/exp/t5_r1_flash/log.jsonl (plan → propose R1–R9 → funnel → evaluate R1–R9 → endorse (skipped, real_compute=false) → final).

Signatures: _____ (design) · _____ (review) · _____ (approval)