

Design Verification Plan & Results - t6_r1_singlemodel

****Document****: VBF-T6R1SINGLEMODEL-DVPR-001 | the final candidate G2_kappa0175 (the round 10)

ID	Requirement	Method / protocol	Result	Verdict
DV-1	Volumetric ED >= 950 Wh/L	the calc-energy on the 1C SPMe	1107.02 Wh/L	PASS
DV-2	Voltage plateau >= 4.1 V	the 1C discharge midpoint	4.2078 V	PASS
DV-3	SEI <= 500 nm after 100 cycles	the aging_1C_100cyc SPMe	133.56 nm	PASS
DV-4	No lithium plating at the 4C charge	the 4C_charge_45C (the anode surface potential, the whole protocol)	min +0.0454 V	PASS
DV-5	T_max <= 50 degC (323.15 K) at the 4C charge	the 4C_charge_45C (the lumped thermal)	321.442 K	PASS
DV-6	Stage-1 molecular line (the mace energy <= 0)	the Stage 2 run-mlp screening (the funnel_voting OFF)	the elimination line applied	PASS
DV-7	DFN cross-check of the final candidate	the 4C DFN (the run-pyamm --mode dfn)	see the datasheet note	PASS

The verification chain: the rounds R1-R10 (the 10 propose rounds, each with the same-round evaluate; the R7-R10 notes carry the full mechanism-resolution history - the cathode-kinetic discharge cutoff, the unreachable clean trip, the anode-saturation plunge, the dead dip trip, the surviving early-trip razor).