

Delivery Index — VBF-T6R2-IDX-001

Delivery Index — Smartphone Battery Design (VBF-T6R2-IDX-001)

Case: exp/t6_r2 · **Date:** 2026-08-26 · **Verdict:** criteria achieved (DFN-verified)

Doc code	Document	File
DS	Design specification	deliverables/design_spec.md
BOM	Bill of materials	deliverables/bom.xlsx (+ pdf)
DSH	Datasheet	deliverables/datasheet.md (+ pdf)
CALC	Compliance calculation book	deliverables/calc.xlsx (+ pdf)
DVPR	Design verification plan & report	deliverables/dvpr.md (+ pdf)
DFMEA	Design FMEA	deliverables/dfmea.md (+ pdf)
IDX	Delivery index (this file)	deliverables/delivery_index.m

Summary of result (all values tool-sourced, DFN precise model)

- Volumetric energy density: **1096.0 Wh/L** ≥ 950 □ (cell/r12_a_energy_dfn.json)
- Voltage plateau: **4.1301 V** ≥ 4.1 □ (cell/r12_a_energy_dfn.json)
- Max temperature (4C, 45 °C amb.): **322.70 K** ≤ 323.15 □ (cell/r12_a_4c45_dfn.json)
- Lithium plating: **not plated** (min anode potential +0.0382 V) □ (cell/r12_a_4c45_dfn.json)
- SEI after 100 cycles: **415.6 nm** ≤ 500 □ (cell/r12_a_aging.json)

Supporting artifacts

- log.jsonl — full audit chain (entry 0 criteria → plan → propose/evaluate R1–R12 → endorse → final)
- report.html — rendered design report
- design_plan.md — Stage 1 planning document
- cell/ — all simulation outputs (SPMe/DFN), parameter files, batch evaluation inputs (batches relocated to cell/batches/)

True-compute endorsement skipped per pre-registered real_compute=false; endorse entry records the skip and the DFN-only endorsement basis.