

Bill of Materials - VBF-T8R2-BOM-01 (t8_r2, final design V_G)

	g/cell	kg/kWh	Formula/source
L1)	16.1685	0.8870	coating mass x 0.96 (wt fraction literature default; parameter set carries mix density only); coating mass = cell/r3_VG_energy.json:la
	0.3368	0.0185	coating mass x 0.02 (literature default; no parameter key)
	0.3368	0.0185	coating mass x 0.02 (literature default; no parameter key)
ite)	10.4391	0.5727	coating mass x 0.96 (literature default); coating mass = cell/r3_VG_energy.json:layer_kg_m2.negative_electrode x area_m2
	0.2175	0.0119	coating mass x 0.02 (literature default)
	0.2175	0.0119	coating mass x 0.02 (literature default)
	0.2450	0.0134	cell/r3_VG_energy.json:layer_kg_m2.separator x area_m2 (thickness x (1-porosity) x density)
tract mass)	6.4030	0.3513	pore volume x 1200 kg/m3 (literature-default density); parameter set lacks electrolyte density
	2.7951	0.1533	cell/r3_VG_energy.json:layer_kg_m2.positive_cc x area_m2 (thickness x density)
	6.9567	0.3816	cell/r3_VG_energy.json:layer_kg_m2.negative_cc x area_m2 (thickness x density)
	Not modeled	Not modeled	no parameters in set - honest annotation
	37.7131	2.0688	cell/r3_VG_energy.json:mass_kg; energy 0.0182 kWh (cell/r3_VG_energy.json:energy_wh/1000)