

Recommendation Algorithms for User First Booking on Airbnb

Zhao Wang
Northeastern University
Seattle, WA
wang.zhao2@husky.neu.edu

Zerui Ma
Northeastern University
Seattle, WA
zeruima1989@gmail.com

Heng Xu
Northeastern University
Seattle, WA
xu.he@husky.neu.edu

ABSTRACT

Airbnb has become more and more popular under the trend of sharing economy. In order to attract new users to place their first booking on Airbnb and offer a more personalized experience, we aim to build a recommendation system by using collaborative filtering approach, to predict which country these new users will make their first booking. Also the hosting data for various countries will be analyzed to provide better insight around booking area.

Keywords

Learning Algorithms; Recommendation Systems; Collaborative Filtering; Cluster Models

1. INTRODUCTION

Data mining is the process of discovering interesting patterns from massive amounts of data. As a knowledge discovery process, it typically involves data cleaning, data integration, data selection, data transformation, pattern discovery, pattern evaluation, and knowledge presentation[1]. The science of learning plays a key role in the fields of data mining, statistics and artificial intelligence, intersecting with areas of engineering and other disciplines[2]. In a typical scenario, a quantitative or categorical outcome measurement is predicted based on a set of features.

Recommendation algorithms are a kind of learning algorithms which are widely used on e-commerce web sites. they use input about a customer's interests to generate a list of recommended items. Most recommendation algorithms are designed for finding similar customers, where they aggregate items from the similar customers, eliminates items the user has already purchased or rated, and recommends the remaining items to the user. The popular versions of these algorithms are collaborative filtering and cluster models. In the collaborative filtering, the similarity of customers is measured by the cosine of the angle between the two vectors which represent users' interests[3]. Using this algorithm to generate recommendations is computationally ex-

pensive, but it can be released by dimensionally reduction techniques[4]. To find the similar customers to the user, cluster models divide the customer base into many segments and treat the task as a classification problem[5]. Some algorithms classify users into multiple segments and describe the strength of each relationship[6]. Besides grouping the user to the similar customers, other algorithms such as search-based methods and item-to-item collaborative filtering focus on finding similar items[7]. Search- or content-based methods treat the recommendations problem as a search for related items[8].

User experience is now a critical factor to keep users and attract new users among web applications. That is the reason Airbnb wants to provide personalized and unique experience for its new users, thus Airbnb need an effective recommendation system to recommend a country for first-time booking.

However, the main challenge here is that Airbnb doesn't have the travel history or other type of the traveling data of new users, the only data available here is basic feature such as age, gender, session log etc., basically like a white paper to a recommendation system. While a typical recommendation system might make recommendation based on a few strongly related features, the system designed here need to focus on correctly classify similar users first, then trying to make recommendation with some relatively strong features. And that is why we choose collaborative filtering as our first-step approach.

2. DATASET DESCRIPTION

In this section, the data sets which are applied for the recommendation are introduced. The data is consisted of two parts: the first one is the list of users' first booking destinations as well as their demographics and web session records; the other is the aggregated public host information dataset which is sourced from publicly available information from the Airbnb site. By analyzing the statistics of the source data, we can have an overview of the entire data and help to decide how to apply for the recommendation algorithms.

2.1 User data set

In the list of user first booking, each user is specified by a unique string id and each instance contains multiple types of properties for that user, which should be date, numerical, categorical, etc. There exists missing values in each fields, which should be handled before building recommendation model. The users whose destination countries are unavailable (indicated as NDF) are also need to be filtered out. The

details of user properties are described as Table.1.

Table 1: User Data Statistics

field	type	description
id	string	unique for each user
date_account_created	date	
timestamp_first_active	timestamp	
date_first_booking	date	
gender	categorical	FEMALE, MALE, OTHER, unknown
age	numerical	1 to 150
signup_method	categorical	basic, facebook, google
signup_flow	numerical	0 to 25
language	categorical	en, zh, fr, es, ko, de, etc.
affiliate_channel	categorical	api, content, direct, etc
affiliate_provider	categorical	bing, facebook, google, etc
first_affiliate_tracked	categorical	linked, local ops, product, etc.
signup_app	categorical	Android, iOS, Moweb, Web
first_device_type	categorical	Android Phone, iPad, iPhone, Mac Desktop, etc.
first_browser	categorical	Chrome, Safari, Firefox, etc.

Since most records in the dataset have no first booking destination, we only focus on the instances with available destination. After filtering the records without specific destinations, the numbers of the users for each country are as Table.2 described. The most number of remaining users is for other destinations, which is less useful for the recommendation. The instances with specific destinations are the data we can use to build the predication model for new users.

Table 2: Users First Booking Destination

Destination Country	Population
AU	537
CA	1425
DE	1059
ES	2243
FR	5013
GB	2318
IT	2827
NL	757
PT	217
other	10075




Figure 1: Age Distribution for Users on Airbnb

2.2 Hosts data set

The other data set is about detailed information of host listings among 16 countries available on Airbnb, although it covers almost all the countries in new user data set, but PT(Portugal) listing data is missing here.

This listing data set contains most of the public information available on Airbnb, and lots of features such as listing price, listing rating score, host registration information and neighbourhood etc., may help recommendation system identify better listings among target country for new users. However, due to the limitation of new user data, the recommendation on this part is most likely to be based on features weighted by common sense: highest rated, best available price etc..

Since listing price is showed in dollar, so the average listing price distribution is influenced by currency exchange rate in some extent, but besides that fact, the average listing price definitely reflects the popularity of these destination countries. BM(Bermuda) is a typical high-end vacation hot spot, but it's surprised to see UY(Uruguay) has such a high average price, maybe because the retrived UY listings is very limited. Other than these two countries, AU and US are the most expensive countries to go on Airbnb. It's interesting to see AU has higher average listing price over US, a possible explanation for this could be the number of listings in US is much greater than AU's, thus competetion over the host has lowered the average listing price in US.




Figure 2: Average price distribution among countries




Figure 3: Average rating score distribution among countries

When comes to average review scores, most of countries get over score of 90. BM, UY and VU receives average score of 100, but since the number of listing of these 3 countries in this data set is very limited, it probably has large bias here. Besides these 3 countries, US and NL is probably best reviewed place to go on Airbnb, IT and ES is the worst reviewed, but still has average score of over 89.

3. PROPOSED ALGORITHMIC APPROACH

Using collaborative filtering to aggregate the similar users based on their first booking on Airbnb. The similarity between users is measured by cosine of the angle between the two vectors which indicate users' properties. Dimensionality reduction should be applied to reduce computational complexity and speed up the algorithm.

3.1 Data preprocess

Table 3: Data Preprocess

Processed Attribute	Description
Time between Account Created & First Booking	
Time between First Active & First Booking	
Age	
Others	Original value

3.2 Basic and Ensemble Classifiers

3.3 Collaborative Filtering

Table 4: Clustering Parameters

Percentage Change of WGSS	Cluster Num	WGSS	Error Rate
< 0.3%	10	114013	0.3036
< 0.1%	17	106895	0.2978
< 0.03%	67	84909	0.2700
< 0.003%	163	73112	0.2330
< 0.001%	424	55412	0.2137

4. CONCLUSION




Figure 4: Error Rates for Basic Classifier




Figure 5: Error Rates for Ensemble Classifier




Figure 6: WGSS based on Clusters

5. REFERENCES

- [1] Han, J., Kamber, M., and Pei, J. , "Data Mining: Concepts and Techniques", 3rd Edition, 2011.
- [2] Hastie T., Tibshirani R., and Friedman, J. , "The Elements of Statistical Learning: Data Mining, Inference, and Prediction", 2nd Edition, 2009.
- [3] B.M. Sarwarm et al., "Analysis of Recommendation Algorithms for E-Commerce", ACM Conf. Electronic Commerce, ACM Press, 2000, pp.158-167.
- [4] K. Goldberg et al., "Eigentaste: A Constant Time Collaborative Filtering Algorithm", Information Retrieval J., vol. 4, no. 2, July 2001, pp. 133-151.
- [5] P.S. Bradley, U.M. Fayyad, and C. Reina, "Scaling Clustering Algorithms to Large Databases", Knowledge Discovery and Data Mining, Kluwer Academic, 1998, pp. 9-15.
- [6] L. Ungar and D. Foster, "Clustering Methods for Collaborative Filtering", Proc. Workshop on Recommendation Systems, AAAI Press, 1998.
- [7] G. Linden, B. Smith, and J. York, "Amazon.com recommendations: item-to-item collaborative filtering", Internet Computing 7:1, 2003, pp. 76-80.
- [8] Leskovec, J., Rajaraman, A., and Ullman, "Mining of Massive Datasets", 2nd Edition, 2004, pp. 307-341.