FOSTEX

Features

- 300mm (12in) cone type woofer
- ø76mm/1.1kg larger alnico manget
- Fine-ceramics multi-coated cone
- fo to 3kHz frequency response

Specifications

Thiele/Small Parameters


Size	:	300	mm	/	12 in			
Voice Coil Diameter								
	:	80	mm	/	3 in			
Cast / Stamped	:	Ca	st					
Impedance	:	8	Ω					
Reproduction Frequency Response								
	:f	s - 3.0	kHz	Z				
Sound Pressure Level								
bound i ressure L	CVC	1						
Sound I ressure E	:	93	dB/	W(m	1)			
Rated Input	: :	93	dB/	W(m	1)			
	: : :	93 50		W(m	n)			
Rated Input	: : :	93 50 150	W	W(m	n)			
Rated Input Music Power	:	93 50 150	W	W(m	n)			
Rated Input Music Power Magnet Material	:	93 50 150	W OW nico	W(m				
Rated Input Music Power Magnet Material Magnet Weight	: : : :	93 50 150 Ali	W OW nico					

a:	131 mm
D :	262 mm
Sd:	0.0539 m^2
Zn:	8 Ω
Fs:	25 Hz
Re:	7.0 Ω
Le:	0.1 mH
Qms:	9.17
Qes:	0.29
Qts:	0.28
Mms:	92.7 g
BL:	18.75 Telsa/m
Vas:	227.01 L
Xmax:	6.5 mm
Eff/η0:	1.20 %
Cms:	0.056 mm/N
EBP:	86


W300AII



Frequency Response / Impedance



Dimensions & Mounting Information



Overall Diameter	:	317	mm /	12 in
Baffle Hole Diame	eter			
	:	278	mm /	11 in
Depth	:	180	mm /	in