

MB8G200

MID-BASS

DESCRIPTION

The MB8G200 is a professioanl mid-bass woofer featuring very high output and dynamics.

The equipment, used a 22 coil, fiberglass former and copper inside / outside winding, has enable a very good transient peak response and has allowed good extension on mid-high frequencies. A specially designed M-roll surround guarantee a very low midrange distortion and perfect damping of the spurius resonances. Inverted dust cap for minimum cone break-up.



FEATURES

- 2-inch, fiberglass former, copper voice coil
- 400W continuous program power handling
- 94 dB Sensitivity
- 60 Hz 4 kHz Frequency range
- M-roll damped surround

General specifications



8 inch / 203 mm

TECHNICAL SPECIFICATIONS

	Rated Impedance:	8 ohm
	Program Power (watt):	400 W
	Power handling capacity:	200 W
	Sensitivity:	94 dB
	Frequency range:	60 - 4000 Hz
	Effective piston diameter:	165 mm / 6.5 inch
	Max. Excursion Before Damage:	30 mm / 1.18 inch
	Minimum Impedance (ohm):	6 ohm
	Voice Coil Diameter:	2.0 inch / 51 mm
	Voice Coil Material:	Copper
	Voice Coil Winding Material:	16 mm / 0.63 inch
	Number of layers:	2
	Kind of layers:	outside
	Top Plate Thickness:	8 mm / 0.31 inch
	Cone Design:	Curved
	Surround Material:	Polycotton
	Surround Design:	M-roll
	Magnets:	Ceramic
	Spider:	Single
Thiele - small parameters	Resonance frequency (Fs):	76 Hz
	DC resistance (Re) (ohm):	4.80 ohm

Nominal Diameter:

Thiele - small parameters	Resonance frequency (Fs):	76 Hz
	DC resistance (Re) (ohm):	4.80 ohm
	Mechanical factor:	3.70 Qms
	Electrical factor:	0.37 Qes
	Total factor:	0.33 Qts
	BI factor (BI) (T x m):	12.50 T x m
	Effective moving mass (Mms):	25 gr

Equivalent Cas air loaded (Vas): 11 liters
Effettive piston area (Sd): 0.02 m2
Max. linear excursion (Xmax): 6 mm
Voice coil inductance @ 1kHz (Le1k): 1.40 mH
Half-space efficency (Eff): 1.26%

Mounting informations Overall diameter: 239 mm / 9.41 inches

Bolt circle diameter: 221 mm / 8.7 inch
Bolt hole diameter: 7 mm / 0.28 inch
Front mount baffle cut-out: 184 mm / 7.24 inch
Rear mount baffle cut-out: 184 mm / 7.24 inch
Volume occupied by the driver: 0.8 liters / 0.03 ft3

Standard compliance CE marking: Yes

DATASHEET



 Size
 Height:
 99 mm / 3.9 inches

 Diameter:
 208 mm / 8.19 inches

 Weight:
 3.54 kg / 7.8 lbs

Shipping informations Package Height: 160 mm / 6.3 inches

Package Width: 245 mm / 9.65 inches
Package Depth: 230 mm / 9.06 inches
Package Weight: 4.03 kg / 8.88 lbs

PART NUMBER

• 11100018

MB8G200