



SP-30

Order No.: 10.1530

Price upon request

PRODUCTINFOS

Universal speaker, 5 W, 4 Ω

- Dual cone
- Wide frequency response
- For general applications from car speakers to column speakers

TECHNICAL SPECIFICATIONS

SP-30

Impedance (Z)	4 Ω
Frequency range	f3-15,000 Hz
Resonant frequency (fs)	150 Hz
Power rating	5 W
Peak music power output	10 W
Sensitivity	88 dB/W/m

SP-30

Suspension compl. (Cms)	0.52 mm/N
Moving mass (Mms)	1.7 g
Mech. Q factor (Qms)	2.5
Electr. Q factor (Qes)	1.04
Total Q factor (Qts)	0.73
Equivalent volume (Vas)	0.7 l
DC resistance (Re)	3.5 Ω
Force factor (BxL)	2.33 Tm
Voice coil induct. (Le)	0.18 mH
Voice coil diameter	20 mm
Voice coil former	aluminium
Linear excursion (X_{MAX})	± 1.5 mm
Eff. cone area (Sd)	31 cm ²
Magnet weight	150 g
Magnet diameter	\varnothing 60 mm
Mounting cutout	\varnothing 73 mm
Mounting depth	37.5 mm
Dimensions	78 x 78 x 40 mm
Width	78 mm
Height	78 mm
Depth	40 mm
Admiss. ambient temp.	0-40 °C
Weight	0.3 kg