



## SP-30/200PA

Order No.: 10.3350

**Price upon request**

### PRODUCTINFOS

**PA bass-midrange speaker, 200 W, 8  $\Omega$**

- For a deep low limit frequency
- For bass-midrange applications and monitoring in bass-reflex cabinets of medium size

### TECHNICAL SPECIFICATIONS

#### SP-30/200PA

Impedance (Z)	8 $\Omega$
Frequency range	f3-4,500 Hz
Resonant frequency (fs)	44 Hz
Power rating	200 W
Peak music power output	400 W
Sensitivity	97 dB/W/m
Suspension compl. (Cms)	0.29 mm/N

**SP-30/200PA**

Moving mass (Mms)	44 g
Mech. Q factor (Qms)	6.71
Electr. Q factor (Qes)	0.41
Total Q factor (Qts)	0.39
Equivalent volume (Vas)	120 l
DC resistance (Re)	6.5 $\Omega$
Force factor (BxL)	13.9 Tm
Voice coil induct. (Le)	0.9 mH
Voice coil diameter	Ø 51 mm
Voice coil former	Kapton
Linear excursion ( $X_{MAX}$ )	$\pm 2.5$ mm
Eff. cone area (Sd)	540 cm <sup>2</sup>
Magnet weight	1.3 kg
Magnet diameter	Ø 156 mm
Mounting cutout	Ø 279 mm
Mounting depth	132 mm
Dimensions	Ø 310 mm x 138 mm
Outside diameter	Ø 310 mm
Width	Ø 310 mm
Depth	138 mm
Admiss. ambient temp.	0-40 °C
Weight	4.32 kg
Packing unit	1
Type of speaker	12"