



SPH-60X

Order No.: 10.0920

Price upon request

PRODUCTINFOS

Full range speaker, 30 W, 8 Ω

- Drilled pole core
- Very good frequency response linearity also in the high frequency range
- For general applications
- Speaker from the successful building concepts CT193 and CT194 of the magazine Klang+Ton

TECHNICAL SPECIFICATIONS

SPH-60X

Impedance (Z)	8 Ω
Frequency range	f3-20,000 Hz
Resonant frequency (fs)	60 Hz
Power rating	30 W
Peak music power output	60 W
Sensitivity	89 dB/W/m

SPH-60X

Suspension compl. (Cms)	1.19 mm/N
Moving mass (Mms)	5.9 g
Mech. Q factor (Qms)	2.17
Electr. Q factor (Qes)	0.53
Total Q factor (Qts)	0.42
Equivalent volume (Vas)	9 l
DC resistance (Re)	6.2 Ω
Force factor (BxL)	5.1 Tm
Voice coil induct. (Le)	0.4 mH
Voice coil diameter	Ø 25.5 mm
Voice coil former	aluminium
Linear excursion (X_{MAX})	± 1.3 mm
Eff. cone area (Sd)	80 cm ²
Magnet weight	370 g
Magnet diameter	Ø 100 mm
Mounting cutout	Ø 122 mm
Mounting depth	70 mm
Dimensions	130 x 130 x 71 mm
Width	130 mm
Height	130 mm
Depth	71 mm
Admiss. ambient temp.	0-40 °C
Weight	1.1 kg
Packing unit	1
Type of speaker	5"