



SPP-110/4

Order No.: 10.1050

Price upon request

PRODUCTINFOS

Hi-fi bass-midrange speakers, 30 W, 4 Ω

- Carbonised plastic cone
- Drilled pole core
- Linear wide frequency response in very small cabinets

HOBBY HiFi 03/2016

"Ideally suited for the combination with ribbon tweeters and magnetostatic tweeters."

TECHNICAL SPECIFICATIONS

SPP-110/4

Impedance (Z) 4Ω

Frequency range f3-8,000 Hz



SPP-110/4

Resonant frequency (fs) 53 Hz
Power rating 30 W
Peak music power output 60 W

Sensitivity 90 dB/W/m Suspension compl. (Cms) 1.95 mm/N

Moving mass (Mms) 4.3 g Mech. Q factor (Qms) 2.01 Electr. Q factor (Qes) 0.46 Total Q factor (Qts) 0.37 8 I Equivalent volume (Vas) DC resistance (Re) 3.3 Ω Force factor (BxL) 3.3 Tm 0.3 mH Voice coil induct. (Le)

Voice coil diameter25.5 mmVoice coil formeraluminiumLinear excursion (X_{MAX}) $\pm 2 \text{ mm}$

Eff. cone area (Sd) 55 cm²

Magnet weight 280 g

Magnet diameter Ø 80 mm

Mounting cutout Ø 100 mm

Mounting depth 59 mm

Mounting hole diameter Ø 120 mm

Hole spacing X-axis 84.5 mm

Hole spacing Y-axis 84.5 mm

Dimensions 110 x 110 x 60 mm

Outside diameter Ø 135 mm

Width 110 mm

Height 110 mm

Depth 60 mm

Admiss. ambient temp. 0-40 °C

Weight 0.809 kg

Packing unit 1
Type of speaker 4"