



SPP-200

Order No.: 10.1080

Price upon request

PRODUCTINFOS

Bass-midrange speaker, 30 W, 8 Ω

For general applications.

This series of speakers with polypropylene cone is very well-suited for replacing defective 8 Ω speakers in hi-fi speaker systems.

TECHNICAL SPECIFICATIONS

SPP-200

Impedance (Z)	8 Ω
Frequency range	f3-3,500 Hz
Resonant frequency (fs)	45 Hz
Power rating	30 W
Peak music power output	60 W
Sensitivity	92 dB/W/m

SPP-200

Suspension compl. (Cms)	0.75 mm/N
Moving mass (Mms)	16.7 g
Mech. Q factor (Qms)	3.96
Electr. Q factor (Qes)	1.35
Total Q factor (Qts)	1.00
Equivalent volume (Vas)	48 l
DC resistance (Re)	6.5 Ω
Force factor (BxL)	4.8 Tm
Voice coil induct. (Le)	0.6 mH
Voice coil diameter	Ø 25.5 mm
Voice coil former	aluminium
Linear excursion (X_{MAX})	± 1 mm
Eff. cone area (Sd)	214 cm ²
Magnet weight	280 g
Magnet diameter	Ø 80 mm
Mounting cutout	Ø 184 mm
Mounting depth	81 mm
Mounting hole diameter	Ø 192 mm
Hole spacing X-axis	135 mm
Hole spacing Y-axis	135 mm
Dimensions	Ø 205 mm x 90 mm
Outside diameter	Ø 205 mm
Width	Ø 205 mm
Depth	90 mm
Admiss. ambient temp.	0-40 °C
Weight	0.96 kg
Packing unit	1
Type of speaker	8"