

QXE6D2

Dual Voice Coil Subwoofer 16,5 cm

Power Handling 250 Watts RMS / 500 Watts Max.

Technical Specifications

Impedance Voice Coil Diameter Voice Coil Winding Height	Zn Ø	2 x 2 Ohms 50 mm 30 mm
Max. Linear Excursion Max. Mechanical Excursion Cone Area Moving Mass	Xmax Xmax (Peak) Sd Mms	+/- 10 mm +/- 15 mm 120 cm ² 91,5 g
DC Resistance	Re	2 x 1,9 Ohms
Resonance Frequency	Fs	50,4 Hz
Mechanical Q-Factor	Qms	5,21
Electrical Q-Factor	Qes	0,47
Total Q-Factor	Qts	0,43
Equivalent Air Volume	VAS	3,2 L
VC Inductance	Le	1,93 mH
Flux Density	B/L	15,3 N/A
Efficiency 1W/1m	SPL	81,3 dB
Max.In-Car Sound Pressure	SPL	135 dB

Recommended Enclosure

Ported Box
Vented Volume: 12 L
Port Diameter: 66 mm
Port Area: 34 cm²
Port Length: 41 cm
Tuning Freq. (Fb): 48 Hz
-3 dB Rolloff (F3): 40 Hz

Mechanical Components

- Diecast Aluminium Basket
- Non-pressed Paper Cone
- Foam Surround
- Injected PP Dustcap
- Dual Nomex Spider
- Dual Magnet 2 x 40 oz (2.268 g)
- Magnet Size: Ø134 x 40 mm
- Aluminium Voice Coil Former

Dimensions & Weight

External Diameter: 179 mm
Mounting Diameter: 150 mm
Mounting Depth: 117 mm
Shipping Weight: 5,6 kg







