



# **SPM-205/4**

Order No.: 10.5380

## **Price upon request**

### **PRODUCTINFOS**

Hi-fi bass-midrange speakers, 70 W, 8  $\Omega$  (/8) and 4  $\Omega$  (/4)

- Excellent replacement speakers of the same quality as from the original equipment manufacturer
- Coated low-resonance paper cone
- Long-term stable rubber surround
- To be used preferably in closed or transmission line cabinets

### **TECHNICAL SPECIFICATIONS**

#### SPM-205/4

Impedance (Z)  $4 \Omega$ 

Frequency range f3-5,000 Hz

Resonant frequency (fs) 37 Hz

Power rating 70 W

Peak music power output 150 W

Sensitivity 89 dB/W/m



#### SPM-205/4

Mounting depth

Mounting hole diameter

0.98 mm/H Suspension compl. (Cms) Moving mass (Mms) 18 g Mech. Q factor (Qms) 2.71 Electr. Q factor (Qes) 0.68 0.55 Total Q factor (Qts) Equivalent volume (Vas) 72 I DC resistance (Re) 3.6 Ω 4.75 Tm Force factor (BxL) Voice coil induct. (Le) 0.65 mH Voice coil diameter Ø 25.5 mm Voice coil former aluminium Linear excursion  $(X_{MAX})$ ± 3 mm Eff. cone area (Sd) 210 cm<sup>2</sup> Magnet weight 380 g Magnet diameter Ø 80 mm Mounting cutout Ø 183 mm

Dimensions Ø 200 mm x 88 mm

80 mm

Ø 216 mm

Outside diameter Ø 200 mm

Width Ø 200 mm

Depth 88 mm

Admiss. ambient temp. 0-40 °C

Weight 1.062 kg

Packing unit 1

Type of speaker 8"