



KL3015CX-8

High power coaxial woofer design with 3" fiberglass I/O voice coil for lower distortion and power compression. Great for vented or sealed satellite, monitor, or bass guitar enclosures. Accepts 1" exit HF driver with 1 3/8" male thread. This allows the user to select their preference in HF driver and makes the KL series much more affordable and versatile.

15" | **800 W**
8 Ω



- | | | | |
|-----------------------------------|--|---|--|
| <input type="checkbox"/> Midrange | <input checked="" type="checkbox"/> Woofer | <input checked="" type="checkbox"/> Sealed Box | <input type="checkbox"/> Scoop Loading |
| <input type="checkbox"/> Midbass | <input type="checkbox"/> Subwoofer | <input checked="" type="checkbox"/> Bass Guitar | <input checked="" type="checkbox"/> Vented Box |
| | | | <input type="checkbox"/> Horn Loading |

SPECIFICATION

THIELE SMALL PARAMETERS*			MOUNTING INFORMATION	
Nominal Basket Diameter	15.0", 381 mm	Fs	38 Hz	Recommended Enclosure Volume
Nominal Impedance*	8 Ω	Re	5.71 Ω	Sealed 22.65-84.95 liters, 0.80-3.00 cu.ft.
Power Rating**		Le	0.63 mH	Vented 53.80-178.40 liters, 1.90-6.30 cu.ft.
Watts	400 W	Qms	6.48	
Music Program	800 W	Qes	0.47	
Resonance	38 Hz	Qts	0.44	Driver Volume Displaced 0.090 cu.ft., 2.54 liters
Usable Frequency Range	40 Hz - 4.0 kHz	Vas	0.27 cu.ft., 7.76 liters	Overall Diameter 15.32 ", 389.1 mm
Sensitivity***	96.7 dB	Vd	771.3 cc	Baffle Hole Diameter 14.00 ", 355.6 mm
Magnet Weight	11 oz.	Cms	0.20 mm/N	Front Sealing Gasket Yes
Gap Height	0.365 ", 9.3 mm	BL	16.08 T-M	Rear Sealing Gasket Yes
Voice Coil Diameter	3.0 ", 76 mm	Mms	89 grams	Mounting Holes Diameter 0.28 ", 7.1 mm
		EBP	81	Mounting Holes B.C.D. 14.56 ", 369.8 mm
		Xmax	8.67 mm	Depth 6.72 ", 170.7 mm
		Sd	889.6 cm ²	Net Weight 7.70 lbs., 3.49 kg
		Xlim	17.8 mm	Shipping Weight 9.90 lbs., 4.49 kg

MATERIALS OF CONSTRUCTION

Copper voice coil	Die-cast aluminum basket
Fiberglass former	Treated paper cone
Neodymium magnet	Sealed cloth edge
Tapered coax	Zurette dust cap

