





Introduction to Lemur Admin Pro

Limited External Use

Lemur Pro is an Esri-based GIS application that provides world-class offline-capable GIS capabilities and a streamlined user experience. Lemur Admin Pro allows developers to add, modify, or remove Lemur Pro data such as environments, bundles, or geocaches. This document will show you how to access Lemur Admin Pro and provide a detailed walkthrough of the software.



Contents

Introduction to Lemur Admin Pro	
Purpose of this Document	3
Environments	3
Business Data Files	4
Bundle JSON	6
Client Credentials	7
Geocache Dashboard	9
Extents	10
Configs	12
Config Extents	14
Locked	16
Service Credentials	17
Logs	19
Settings	21
Files	22
Hub Connector Dashboard	24
Hub Connectors	25
Tasks List	26
Custom Headers	27
Custom URLs	28
Reported Problems	30
Replica Management	31
Edit Modules	33
Replica File Queue	35
Tools	38
Zoom to Location Scheme Builder	38
Zoom to Objects Scheme Builder	39
Load Business Objects	42
Audio Resources	44
Glossary	46



Purpose of this Document

The purpose of this document is to provide a general overview of the Lemur Admin Pro application.

Environments

The **Environments** page displays 4 categories: environment, company, application, and bundle.

You may click on the **Application** drop-down menu to view the list of applications available.




Figure 1: Application

You may also click on the **Bundle** drop-down menu to view the list of available bundles for the selected application.



Business Data Files

The **Business Data Files** page displays JSON files that can contain sample business data. Sample data is typically only used in Development or Testing workflows.

You can view, edit, or remove a data file by clicking on the ellipsis next to the corresponding data file.




Figure 2: Business Data Files Options



You can add new business data files by clicking **New** near the top of the page.




Figure 3: New Data File



Bundle JSON

The Bundle JSON page allows the user to add, modify, or remove data that exists in the bundle being viewed.

Figure 4: Bundle JSON



Client Credentials

The **Client Credentials** page displays credentials defined in the selected bundle.

You can view, edit, or remove a credential by clicking on the ellipsis next to the corresponding credential.




Figure 5: Credential Options



You can create a new client credential by clicking New in the **toolbar** above.



Figure 6: New Credential

To create a new client credential, you will need:

- Label
- Service Uri
- Token service Uri
- Username
- Password



Geocache Dashboard

The **Geocache Dashboard** displays an overview of the activity regarding geocache generation, including the following:

- Cache processes in progress
- Active caches
- · Cache file sizes
- Cache run logs




Figure 7: Geocache Dashboard



Extents

The **Extents** page displays the defined extents for the selected application.




Figure 8: Extents

You can view, edit, or remove an extent by clicking on the ellipsis next to the corresponding extent.




Figure 9: Extent Options



You may also create a new extent or import/export an extent from the toolbar at the top of the page.



Figure 10: Extents Toolbar



Configs

The **Configs** page displays a list of map configurations, i.e., base maps or feature services, which are defined for the selected application.




Figure 11: Configs



You can view, edit, or remove a configuration by clicking on the ellipsis next to its corresponding configuration.




Figure 12: Config Options

You may also create a new configuration or import/export a configuration from the toolbar at the top of the page.



Figure 13: Configs Toolbar



Config Extents

The **Config Extents** page allows you to view the health of a config extent and modify its configuration as needed. Extents with a health status of "frowny face" have one or more issues that need to be addressed. Extents with a health status of "smiley face" are healthy and require no changes.




Figure 14: Config Extents



Clicking on the ellipsis next to a config extent allows you to perform one of the following actions:

- Copy ID
- View
- Edit
- Delete
- Upload
- Generate
- Generate New Prime (only available if the config is defined to have deltas)




Figure 15: Config Extent Options



Locked

The **Locked** page displays a list of config extents that are no longer queued and need attention as they are no longer being automatically generated. Config extents become locked when they have failed to successfully generate cache repeatedly.



Figure 16: Locked

You can click on a checkbox beside one of the caches and click **Generate Selected** to mark the cache "to be generated". This will attempt to regenerate the cache. However, if the error that puts this Cache Extent into a locked state has not been resolved, the cache extent is likely to become locked once again. Therefore, It is best to use this option only once the failure condition that locked this Cache Extent has been resolved.



Figure 17: Generate Selected



Service Credentials

The **Service Credentials** page shows the list of Token Services defined and used by bundles in this Hub. You can view, edit, or remove a credential by clicking on the ellipsis next to its corresponding credential.




Figure 18: Service Credential Options



You can add new service credentials by clicking **New** inside of the toolbar near the top of the page. To create a new credential, you will need:

- Service Uri
- Token service Uri
- Username
- Password



Figure 19: New Service Credential



Logs

The **Logs** page displays a list of caches that have attempted to generate and if the cache was generated successfully or not.



Figure 20: Logs



You can view or remove a log by clicking on the ellipsis next to its corresponding log.




Figure 21: Log Options



Settings

The **Settings** page displays cache and log settings that can be viewed and/or changed.

	:	Key	:	Value :	Description
•	ï	ACCESSLOG_RETENTION_DAYS		30	The number of days to keep the access logs
•		AUDITLOG_RETENTION_DAYS		30	The number of days to keep the audit logs
•		REPLICASERVICE_CREATEERRORRECOVERYDELAYMINUT	ES	60	Time to delay before resetting the error count for replica
•	••	REPLICASERVICE_MAXCREATEERRORRETRIES		2	Maximum number of times that a failed replica creation
•	••	REPLICASERVICE_MAXUPDATEERRORRETRIES		2	Maximum number of times that a failed replica update v

Figure 22: Settings



Files

The **Files** page displays a list of generated cache files that can be viewed or downloaded. These can be filtered using the 'Set Filters' option in the header toolbar.




Figure 23: Files



You can view or download a file by clicking on the ellipsis next to its corresponding file.




Figure 24: File Options



Hub Connector Dashboard

The Hub Connector Dashboard page displays a list of registered Lemur Hub connectors as well as asummary of the work it has performed.



Figure 25: Hub Connector Dashboard

You can view recent tasks and recent errors by clicking on the ellipsis next to a hub connector.




Figure 26: Hub Connector Options



Hub Connectors

The Hub Connectors page allows you to view the configuration details of each hub connector for yourcompany.

Note that a new Hub Connector can only be edited when logged in as a system administrator user, and not as a company administrator.



Figure 27: Hub Connectors



Tasks List

The Task List page displays a list of tasks that took place inside of a hub connector. You can apply the following filters to these tasks:

- Hub connector
- Date
- Status

Once the filter options are set as desired, click the Load button to load the tasks




Figure 28: Tasks List



Custom Headers

The Custom Headers page is used to define headers that are passed to ArcGIS when generating cache.



Figure 29: Custom Headers Home Page

To create a new custom header, click **New** at the top of the page.



Figure 30: Create Custom Header

Enter the name and value of your custom header, then click OK (save).



Figure 31: Custom Header Name and Value



Custom URLs

The Custom URLs page is used to send custom headers for a given URL.



Figure 32: Custom URLs Home Page

To create a new custom URL, click **New** at the top of the page.



Figure 33: Create Custom URL

Enter the name and URL, then click OK (save). You may assign a header to your custom URL if necessary.



Figure 34: Custom URL Values



You can view a task by clicking on the ellipsis next to a task.




Figure 35: Task Options



Reported Problems

The Reported Problems page shows a list of reported issues. Reported Problems may be user-submitted or automatically generated if the Lemur Pro application detected a crash in the previous session. You can apply the following filters to this list:

- Status (open/closed)
- Status Date

Clicking on the "eye" icon allows you to view additional details about the report.




Figure 36: Reported Problems



Replica Management

The **Replica Management** page displays a current list of templates along with additional information, such as:

- Last modified date
- Is the template active?
- Can you download the template?
- Can you upload the template?

You may click on the pencil icon to edit a template. Note: editing a replica template is only for advanced users and should not be attempted without contacting a member of the Lemur Success Team.




Figure 37: Replica Management

Specific template details you can modify include:

- Toggle template active/inactive
- · Add/remove login credentials
- Toggle hub connectors active/inactive
- Editing errors, throttling and recovery settings



You may also add a new template after providing the following information:

- Template name
- Feature service URL
- Login credentials



Figure 38: Add Template



Edit Modules

The **Edit Modules** page displays a list of known modules. You may click on the ellipsis to deactivate or manage a module.




Figure 39: Edit Modules



In the Manage Module Settings window, you can add a unique key and value to the module.




Figure 40: Manage Module Settings



Replica File Queue

The Replica File Queue page displays a list of replica file creation/update tasks.




Figure 41: Replica File Queue



You can apply the filters below to your search.




Figure 42: Replica File Filters



Clicking on the ellipsis next to the corresponding item allows you to perform the following tasks:




Figure 43: Replica File Options



Tools

This section consists of several tools that are useful for testing functionality in Lemur Pro, including deep links.

Zoom to Location Scheme Builder

The **Zoom to Location Scheme Builder** allows you to set up individual "zoom to location" configurations. To create your own configuration, paste your geometry data in JSON format, then set your zoom precedence and user-defined zoom level scale.




Figure 44: Zoom to Location Scheme Builder

You can import a premade "zoom to location scheme" by clicking **Import** and pasting the scheme's URL into the box. The Invoke feature allows you to send the configured deep link to Lemur Pro.





Figure 45: Zoom to Location Scheme Builder Toolbar

Zoom to Objects Scheme Builder

The Zoom to Objects Scheme builder allows you to set up individual "zoom to object" configurations. To set up your own configuration, click **Add** in the **Set Business Objects** box.



Figure 46: Setting up an Individual Zoom to Object Configuration

Enter a collection name and any associated business IDs, then click Save.



Figure 47: Entering a Collection Name and ID

Across from Set Feature Objects, click on Edit.



Figure 48: Edit



Enter a feature service label and any associated feature unique IDs, then click **Save**.



Figure 49: Entering a Feature Service Label and Unique ID



Toggle Select Objects (if necessary), then set the zoom precedence and user-defined zoom level scale.




Figure 50: Set Zoom Precedence and Zoom Level Scale

You can import a premade "zoom to objects scheme" by clicking **Import** and pasting the scheme's URL into the box. The Invoke feature allows you to send the configured deep link to Lemur Pro.



Figure 51: Import/Invoke



Load Business Objects

The **Load Business Objects** feature allows you to set up a deep link to add/update/remove a business object, and/or set a pinned object and set a zoom precedence for that object.

To add a new business object, enter the name and unique ID of the business object, then set the zoom precedence and user-defined zoom level scale.




Figure 52: Adding a New Business Object

You can also execute an action on the selected object by pasting the ID of the action you want to use.



Figure 53: Action to Execute



You can import a premade "load business objects scheme" by clicking **Import** and pasting the scheme's URL into the box. The Invoke feature allows you to send the configured deep link to Lemur Pro.



Figure 54: Import/Invoke



Audio Resources

The Audio Resource page allows you to use custom sounds in Lemur Pro for Geofence alerts. Lemur Pro supports only MP3 format for audio playback, as it is a common compressed audio format.

If you wish to use your own sound file for an event notification, go to the **Audio Resources** tab under the Tools section. Click Import, then select your MP3 audio file.



Figure 55: Import Audio File

Click **Play to Test** to ensure that Lemur Pro will be able to play your file properly.



Figure 56: Play Audio File

Click Copy To Clipboard to copy the encoded audio to your clipboard.



Figure 57: Copy Encoded Audio to Clipboard



To insert your audio resource into your LPC, go to **Bundle JSON**, then go to the ResourceDictionaries property.

If null, you'll need to add a new property for your language. For example:

```
"ResourceDictionaries": {
    "EN-US": {
     }
}
```

Inside the appropriate language culture code, add a new resource key for your sound and the value previously copied to your clipboard. For example:

```
"ResourceDictionaries" : {
     "EN-US": {
          "MyEventSound" : "SUQzBAAAAAAZ1RJVDIAAAAZAAADUmV0cm8sIF......"
     }
}
```

Note: Be sure to set the AudioResourceKey value in your event to the name of your resource key you added.



Glossary

- 1. Bundle A large file that contains up to 16,384 geographical tiles.
- 2. Hub Connector Connects the user to Lemur Hub, which takes a snapshot of business data that can be used for offline use.
- 3. Geocache Client-specific business data taken from Lemur Hub for offline use.
- 4. Replica Describes what data has been replicated and contains the information needed to synchronize changes.
- 5. Esri An American multinational geographic information system (GIS) software company. It is best known for its ArcGIS products
- 6. GIS Geographic information system, a system for storing and manipulating geographical information on computer.
- 7. Business Object The GIS object represents the GIS you are working with, be it Lemur Pro or ArcGIS.
- 8. Cache Data stored in a cache memory
- 9. Access Token An access token is generated by the logon service when a user logs on to the system and the credentials provided by the user are authenticated against the authentication database.
- 10. Uri A Uniform Resource Identifier (URI) is a unique sequence of characters that identifies a logical or physical resource used by web technologies.

Introduction to Lemur Admin Pro



This page is purposely left blank.