

ECE 587 Midterm Review

Miao Liu

Department of Electrical and Computer Engineering
Duke University, Durham NC 27708

October 3, 2012

Concepts related to Entropy

The Asymptotic Equipartition Property (AEP)

Entropy Rates of a Stochastic Process

Data Compression




Figure: Venn diagram for entropy and mutual information

Entropy

- ▶ If the inequality is true prove it, otherwise, give a counter example
 - ▶ $H(X|Y) \leq H(X)$
 - ▶ $H(X, Y|Z) \geq H(X|Z)$
 - ▶ $H(X|Z) \leq H(Z)$
 - ▶ $H(X, Y, Z) - H(X, Y) \geq H(X, Z) - H(X)$
 - ▶ $H(X|Z) \geq H(Z)$
- ▶ Relative entropy $D(p||q)$
 - ▶ show that $D(p||q) \geq 0$
 - ▶ Is relative entropy symmetric, i.e $D(p||q) = D(q||p)$?

Law of large numbers (LLN) for product of random variables

- ▶ Since $X_i = \exp\{\ln X_i\}$
- ▶ we have $\sqrt[n]{\prod_{i=1}^n X_i} = \exp\{\frac{1}{n} \sum_{i=1}^n \ln X_i\}$.
- ▶ Hence

$$\sqrt[n]{\prod_{i=1}^n X_i} = \exp\left\{\frac{1}{n} \sum_{i=1}^n \ln X_i\right\} \quad (1)$$

$$\rightarrow \exp\{\mathbb{E} \ln X\} \quad (\text{LLN}) \quad (2)$$

$$\leq \exp\{\ln \mathbb{E} X\} = \mathbb{E} X \quad (\text{Jensen's Inequality}) \quad (3)$$

The Asymptotic Equipartition Property (AEP)

- ▶ AEP. Let X_i be *iid* $\sim p(x)$, $x \in \{1, 2, \dots, m\}$. Let $\mu = \mathbb{E}X$ and $H = -\sum p(x)\log(x)$. Let
 $A^n = \{x^n \in \mathcal{X}^n : |-\frac{1}{n} \log p(x^n) - H| \leq \epsilon\}$. Let
 $B^n = \{x^n \in \mathcal{X}^n : |-\frac{1}{n} \sum_{i=1}^n X_i - \mu| \leq \epsilon\}$
 - ▶ $Pr\{X^n \in A^n\} \rightarrow 1$?
 - ▶ Does $Pr\{X^n \in A^n \cap B^n\} \rightarrow 1$?
 - ▶ Show that $|A^n \cap B^n| \leq 2^{n(H+\epsilon)}$ for all n .
 - ▶ Show that $|A^n \cap B^n| \leq (\frac{1}{2})2^{n(H-\epsilon)}$ for n sufficiently large.

Entropy rate of random walk on a weighted graphs

- ▶ The nodes of graphs are random variables, with state distribution π_t at time t and transition probability matrix T .
- ▶ T is determined by the weights over the edges.
- ▶ Stationary distribution is a distribution p_i over states, such that $\pi_t = \pi_{t+1}$ (shift invariant).
- ▶ The stationary distribution $\pi(i), i = 1, \dots, |\mathcal{X}|$ satisfies

$$\pi = T\pi. \tag{4}$$

Entropy Rates of a Stochastic Process

- ▶ Monotonicity of entropy per element. For a stationary stochastic process X_1, X_2, \dots, X_n , show that



$$\frac{H(X_1, X_2, \dots, X_n)}{n} \leq \frac{H(X_1, X_2, \dots, X_{n-1})}{n-1} \quad (5)$$



$$\frac{H(X_1, X_2, \dots, X_n)}{n} \geq H(X_n | X_{n-1}, \dots, X_1). \quad (6)$$

- ▶ Entropy rates of Markov Chains
 - ▶ What is the stationary distribution π
 - ▶ Find the entropy rate the two-state Markov Chain with transition matrix

$$\begin{pmatrix} 1-p & p \\ q & 1-q \end{pmatrix}$$

Data compression

- ▶ Huffman Coding Consider the random variable

$$X = \begin{pmatrix} x_1 & x_2 & x_3 & x_4 & x_5 & x_6 & x_7 \\ 0.49 & 0.26 & 0.12 & 0.04 & 0.04 & 0.03 & 0.02 \end{pmatrix}$$

- ▶ Find the binary Huffman code for X.
- ▶ Find the expected code length for this encoding.
- ▶ Find a ternary Huffman code for X.

Summary

Good Luck!