



Universität des Saarlandes
Max-Planck-Institut für Informatik



Thesis Tytple

Masterarbeit im Fach Informatik
Master's Thesis in Computer Science

von / by

Author Name

angefertigt unter der Leitung von / supervised by

betreut von / advised by

begutachtet von / reviewers

Saarbrücken, August 2015

Eidesstattliche Erklärung

Ich erkläre hiermit an Eides Statt, dass ich die vorliegende Arbeit selbstständig verfasst und keine anderen als die angegebenen Quellen und Hilfsmittel verwendet habe.

Statement in Lieu of an Oath

I hereby confirm that I have written this thesis on my own and that I have not used any other media or materials than the ones referred to in this thesis.

Einverständniserklärung

Ich bin damit einverstanden, dass meine (bestandene) Arbeit in beiden Versionen in die Bibliothek der Informatik aufgenommen und damit veröffentlicht wird.

Declaration of Consent

I agree to make both versions of my thesis (with a passing grade) accessible to the public by having them added to the library of the Computer Science Department.

Saarbrücken, August 2015

Mohamed Gad-Elrab

Abstract

Stereoscopic and automultiscopic displays suffer from crosstalk. An effect which greatly reduces image quality, viewer comfort and distort the perception of depth. Previously, only a limited work has been done on understanding the relation between crosstalk and the perceived depth with respect to the nature of the stimuli. Moreover most of the previous work is carried on simple monochromatic scenes. Since the human visual system uses numerous other cues than disparity to estimate the depth of an object in a stereo scene, monochromatic scenes are poor choice for understanding the above mentioned relation. Moreover, the model for depth resolution via disparity as provided by the current literature fails to justify why and how the perceived depth is affected by the crosstalk. In this work, we improved and performed more generalized experimentation to see how the depth perception is affected by the crosstalk for different kinds of stimuli. Based on the result of these experiments, we derived a model for human visual system's resolution of depth from disparity that accurately measures the depth of a stimulus as perceived by the human in presence of cross-talk. Finally some improved algorithms for removal/compensation of crosstalk in automultiscopic are developed.

Acknowledgements

Contents

Abstract	v
Acknowledgements	vii
Contents	xi
List of Figures	xv
List of Tables	xvii
1 Introduction	1
1.1 Preliminaries	1
1.2 Contributions of this Thesis	1
1.3 Structure	1
1.4 List of Commonly used abbreviations	1
2 Relevant Background	3
2.1 Depth Perception	3
2.2 Stereopsis in HVS	3
2.3 Crosstalk	5
2.4 Stereoscopic/Automultiscopic Screens and its cross-talk	6
2.4.1 CRT Screens	6
2.4.2 LCD Screens	6
2.4.3 Anaglyph Stereo	6
2.4.4 Active/Time Sequential Stereo	6
2.4.5 Passive/ Space Multiplexed Stereo	6
2.4.6 Automultiscopic Screens	6
2.5 Crosstalk Quality Metrics	6
2.6 Lightfields	6

3	Related Work	7
3.1	Effects of Crosstalk on Perceived Depth	8
3.1.1	Thirsins's work	8
3.1.2	Systematic Distortion	8
3.1.3	Visibility Threshold and Fusion Limit	8
3.2	Migation/Compensation of Cross-talk	8
3.2.1	Stereoscopic Screens	8
3.2.1.1	Subtractive Approaches	8
3.2.1.2	Perceptual Optimization	8
3.2.1.3	Temporal Approach	8
3.2.2	Automultiscopic Screens	8
3.2.2.1	Inverse Filtering	8
3.2.2.2	Subtractive Reduction	8
3.2.2.3	Sub-pixel Optimization	8
3.2.2.4	Low Pass Filtering	8
4	Contribution	9
4.1	Crosstalk Experiments	10
4.1.1	Apparatus setup	10
4.1.2	Experimentation Procedure	10
4.1.3	Stereoscopic Experimentations	10
4.1.3.1	Initial Hypothesis	10
4.1.3.2	stimuli	10
4.1.3.3	Simulation of Cross-talk	10
4.1.3.4	Experimentation procedure	10
4.1.3.5	Results	10
4.1.4	Automultiscopic Experimentations	10
4.1.4.1	Initial Hypothesis	10
4.1.4.2	stimuli	10
4.1.4.3	Simulation of Cross-talk	10
4.1.4.4	Experimentation procedure	10
4.1.4.5	Results	10
4.1.5	Conclusion and Discussion	10

4.2	HVS depth from disparity Model	10
4.2.1	Different Hypothesis and their Outcome	10
4.2.2	Future Work	10
4.3	Cross-talk Mitigation	10
4.3.1	Proposed Optimizations	10
4.3.2	Unsharp Masking in View Domain	10
4.3.3	Iterative Subtraction	10
5	Applications	11
5.1	Depth Adjustment for Depth Critical viewing Applications	11
5.2	Efficient Preprocessing for Crosstalkfree Images	11
6	Conclusion	13
6.1	Summary	13
6.2	Future Work	13
6.3	Open Questions	13
	Bibliography	15
	Index	16

List of Figures

2.1	HVS Depth Cues	4
2.2	Representation of theoretical (T) and empirical (E) horopter	5

List of Tables

Chapter 1

Introduction

1.1 Preliminaries

Discuss General idea behind crosstalk and why is it so bad. How it affects the depth and what current literature think about it.

1.2 Contributions of this Thesis

Experimentation, mitigation, HVS model.

test

1.3 Structure

1.4 List of Commonly used abbreviations

Chapter 2

Relevant Background

2.1 Depth Perception

Depth perception is the ability of the Human Visual System to visualize the three dimensional world as well as measuring the distance of an object based on two dimensional images obtained from the eyes. Depth perception is imperative for performing basic everyday tasks such as avoiding obstacles without bumping into them or interacting with the world with relative ease. In animals (specially predators), it is critical to estimate the distance of a prey for an efficient attack. Depth sensation is the term used for animals as it is not known whether they sense the depth in the same way as humans do or not[3].

Human visual system uses several monocular and binocular cues to determine the depth of objects in the view. These cues can be categorized into two categories i.e. cues extracted from a single image (Monocular Cues) and cues extracted from two images (Binocular cues)[2][3]. Figure 2.1 gives an outlook of the depth cues used by the HVS. These cues are then dynamically weighted according to their robustness by the HVS in order to estimate a depth value for each object in the view [1](Write details of those cues in Appendix).

2.2 Stereopsis in HVS

Among all the depth cues discussed in the section above, Stereopsis is the most influential of them all. Since the human eyes are located at different lateral positions




FIGURE 2.1: HVS Depth Cues




FIGURE 2.2: Representation of theoretical (T) and empirical (E) horopter

on the head, the images formed on the retinas of these two eyes are slightly different. The difference is mainly the horizontal positions of the objects[5]. The process of obtaining a fused (Binocular fusion) image (Cyclopean image) and obtaining a depth map based on the horizontal disparities of the objects in these two images is known as stereopsis.

When the eyes verge in order to focus some object (or point) in space, that object is projected at identical corresponding points in the retinas. This means that the difference between their horizontal positions is zero. The locus of all the points in space that is projected on identical retinal points is called the horopter[4]. Theoretically, via geometrical principles, the horopter is a circular segment in the plane of fixation. However, Wheatstone in 1938 observed that the actual/emperical horopter is much larger than that. Figure ?? shows both the theoretical and empirical horopter.

2.3 Crosstalk

Definitions and Factors contributing to Crosstalk Effects on viewers 70% thing etc.

2.4 Stereoscopic/Automultiscopic Screens and its cross-talk

2.4.1 CRT Screens

2.4.2 LCD Screens

2.4.3 Anaglyph Stereo

2.4.4 Active/Time Sequential Stereo

2.4.5 Passive/ Space Multiplexed Stereo

2.4.6 Automultiscopic Screens

2.5 Crosstalk Quality Metrics

2.6 Lightfields

Chapter 3

Related Work

3.1 Effects of Crosstalk on Perceived Depth

3.1.1 Thirsins's work

3.1.2 Systematic Distortion

3.1.3 Visibility Threshold and Fusion Limit

3.2 Migigation/Compensation of Cross-talk

3.2.1 Stereoscopic Screens

3.2.1.1 Subtractive Approaches

3.2.1.2 Perceptual Optimization

3.2.1.3 Temporal Approach

3.2.2 Automultiscopic Screens

3.2.2.1 Inverse Filtering

3.2.2.2 Subtractive Reduction

3.2.2.3 Sub-pixel Optimization

3.2.2.4 Low Pass Filtering

Chapter 4

Contribution

4.1 Crosstalk Experiments

4.1.1 Apparatus setup

4.1.2 Experimentation Procedure

4.1.3 Stereoscopic Experimentations

4.1.3.1 Initial Hypothesis

4.1.3.2 stimuli

4.1.3.3 Simulation of Cross-talk

4.1.3.4 Experimentation procedure

4.1.3.5 Results

4.1.4 Automultiscopic Experimentations

4.1.4.1 Initial Hypothesis

4.1.4.2 stimuli

4.1.4.3 Simulation of Cross-talk

4.1.4.4 Experimentation procedure

Chapter 5

Applications

5.1 Depth Adjustment for Depth Critical viewing Applications

5.2 Efficient Preprocessing for Crosstalkfree Images

Chapter 6

Conclusion

6.1 Summary

6.2 Future Work

6.3 Open Questions

Bibliography

- [1] LANDY, M. S., MALONEY, L. T., JOHNSTON, E. B., AND YOUNG, M. Measurement and modeling of depth cue combination: In defense of weak fusion. *Vision research* 35, 3 (1995), 389–412.
- [2] REICHELT, S., HÄUSSLER, R., FÜTTERER, G., AND LEISTER, N. Depth cues in human visual perception and their realization in 3d displays. In *SPIE Defense, Security, and Sensing* (2010), International Society for Optics and Photonics, pp. 76900B–76900B.
- [3] WIKIPEDIA. Depth perception — wikipedia, the free encyclopedia, 2015. [Online; accessed 20-August-2015].
- [4] WIKIPEDIA. Horopter — wikipedia, the free encyclopedia, 2015. [Online; accessed 21-August-2015].
- [5] WIKIPEDIA. Stereopsis — wikipedia, the free encyclopedia. [Online; accessed 21-August-2015].

Index

HVS, [3](#)