Design AlgoExpert

SystemsExpert design walkthrough

Clarifying questions

- Which parts are in scope: browsing questions, the code editor, running code, user progress, payments?
- How many languages must code execution support?
- Global audience or one region? Latency targets for 'Run Code'?
- Is static content (prompts, video) mostly read-only and edited by a small team?

Functional requirements

- List questions with per-user completion status
- View a question (prompt, hints, video walkthrough)
- Write code in the browser, autosave it per language
- Run code against test cases and see results
- Track progress across devices


Non-functional requirements

- ~99.9% availability for browsing; code execution can degrade gracefully
- Run-code p95 under ~3 s
- No loss of saved user code
- Strong isolation of untrusted code

Capacity estimates

- ~1M users, ~10k concurrent at peak; ~200 questions
- Static content ~ few hundred MB excl. video → CDN
- Autosave every few seconds while typing: ~10k writes/s peak → debounce client-side to ~1/10s → ~1k writes/s
- Code runs: ~1-2k/min peak; each needs ~1-2 s of sandbox CPU → ~50 concurrent sandboxes, provision headroom x3

High-level architecture



Data model

- Questions(id, name, difficulty, category, prompt_md, tests_json, version)
- Users(id, email, plan, created_at)
- User_code(user_id, question_id, language, code, updated_at) PK(user_id, question_id, language)
- Completions(user_id, question_id, completed_at)

API

```
GET  /questions                          -> [{id, name, difficulty, category, completed}]
GET  /questions/{id}                     -> prompt, hints, starter code
PUT  /questions/{id}/code/{language}     body {code}
POST /questions/{id}/run                 body {language, code} -> {runId}
GET  /runs/{runId}                       -> {status, results[]}
```

Code execution

- Untrusted code runs in per-language container pools (gVisor/Firecracker style isolation), no network, CPU/memory/time limits.
- Keep warm containers to avoid cold starts; route by language via the queue.
- Results are pushed back (websocket) or polled.

Autosave

- Client debounces and sends deltas; server does last-write-wins keyed by (user, question, language) with updated_at.
- Local storage keeps a copy for offline edits.

Global latency

- Static assets on a CDN; API in 2-3 regions with a primary DB and read replicas; sandbox fleets in each region so run latency stays low.

Trade-offs & alternatives

- Polling vs websockets for run results: polling is simpler and fine at this scale
- Single relational DB is enough at this size; shard by user_id later if needed
- Pre-warmed sandboxes cost money but are what keeps p95 low

Recap

- Clarify scope, then functional + non-functional needs
- Estimate load to size storage and fan-out
- Core pieces: Browser, CDN, Load balancer, API servers - stateless, Postgres
- Know your trade-offs and failure modes