Blackjack Probability

AlgoExpert · Medium · Recursion

The problem

- The dealer draws cards valued 1-10 uniformly while below target-4; busts if above target.
- Starting from a hand value, probability of busting (rounded to 3 decimals).
- Memoised recursion.

Intuition

- The chance of busting from hand total t is the average over the ten next cards, which we memoise.

Approach

- 1. If the total exceeds the target, it's a bust
- 2. If it reaches target minus four, stop
- 3. Otherwise average the ten draws
- 4. Memoise by total

Java solution

```java
public class BlackjackProbability {
    public static float blackjackProbability(int target, int startingHand) {
        double p = bust(target, startingHand, new HashMap<>());
        return Math.round(p * 1000) / 1000f;
    }

    private static double bust(int target, int hand, Map<Integer, Double> memo) {
        if (hand > target) return 1;
        if (hand + 4 >= target) return 0;
        Double m = memo.get(hand);
        if (m != null) return m;
        double p = 0;
        for (int c = 1; c <= 10; c++) p += 0.1 * bust(target, hand + c, memo);
        memo.put(hand, p);
        return p;
    }
}
```

Complexity

- Time: O(t)
- Space: O(t)

Recap

- The chance of busting from hand total t is the average over the ten next cards, which we memoise.
- Complexity: O(t)