Knuth Morris Pratt Algorithm

AlgoExpert · Very Hard · Famous Algorithms

The problem

- Does `sub` occur in `str`?
- Prefix-function (failure table) matching.

Intuition

- A failure table tells us how far to fall back on a mismatch, so we never rescan the text.

Approach

- 1. Build the prefix function of the pattern
- 2. Walk the text
- 3. On mismatch, fall back via the table
- 4. Match when the pattern is complete

Java solution

```java
public class KnuthMorrisPrattAlgorithm {
    public static boolean knuthMorrisPrattAlgorithm(String str, String sub) {
        if (sub.isEmpty()) return true;
        int[] fail = new int[sub.length()];
        for (int i = 1, k = 0; i < sub.length(); i++) {
            while (k > 0 && sub.charAt(i) != sub.charAt(k)) k = fail[k - 1];
            if (sub.charAt(i) == sub.charAt(k)) k++;
            fail[i] = k;
        }
        for (int i = 0, k = 0; i < str.length(); i++) {
            while (k > 0 && str.charAt(i) != sub.charAt(k)) k = fail[k - 1];
            if (str.charAt(i) == sub.charAt(k)) k++;
            if (k == sub.length()) return true;
        }
        return false;
    }
}
```

Complexity

- Time: O(n + m)
- Space: O(m)

Recap

- A failure table tells us how far to fall back on a mismatch, so we never rescan the text.
- Complexity: O(n + m)