Adapter

Season: 2 · Structural · Category: GoF · Level: Beginner · Build with Waqar

Today's Hook

- Today: Adapter as a StreamForge product force — not trivia.
- Runnable Demo on JDK 25 with captured stdout.
- Classic encoding → Java 25 / Zazr modernization → trade-offs.
- CapCut slides + full spoken script included.

The Problem

- Naive local fixes: more ifs, statics, nulls, or threads.
- Illegal states still compile; tests become order-dependent.
- Design reviews lack a shared name for the force.
- Interviews punish memorization without judgment.

Structure



Adapter structure

Real-World Scenario

- StreamForge creator platform is the running metaphor.
- Same names appear in naive code, refactor, and Demo output.
- Stay in one story for the full 10–12 minutes.
- Product language first; pattern vocabulary second.

Naive Code

```
// Naive sketch for Adapter
public class Naive {
  // duplicated logic / leaked details / unsafe sharing
  Object doIt(Object... args) {
    if (args == null) return null;
    return args[0];
  }
}
```

Why Naive Hurts

- Coupling spreads across controllers and infrastructure.
- Tests need sleeps or static reset hooks.
- New variants require shotgun edits.
- On-call cannot reason about failure modes.

Implementation

```java
// file: src/main/java/com/buildwithwaqar/patterns/gof/structural/adapter/XmlToJsonLoggerAdapter.java
package com.buildwithwaqar.patterns.gof.structural.adapter;

interface JsonLogger {
    void logJson(String json);
}

final class LegacyXmlLogger {
    String last;
    void logXml(String xml) { last = xml; }
}

/** Object adapter — wraps adaptee, translates calls. */
public final class XmlToJsonLoggerAdapter implements JsonLogger {
    private final LegacyXmlLogger legacy = new LegacyXmlLogger();

    @Override
    public void logJson(String json) {
        legacy.logXml("<payload>" + json + "</payload>");
    }

    String lastXml() { return legacy.last; }
}
```

Demo.main

```java
package com.buildwithwaqar.patterns.gof.structural.adapter;
public final class Demo {
  public static void main(String[] a) {
    System.out.println("=== Adapter walkthrough ===");
    var adapter = new XmlToJsonLoggerAdapter();
    JsonLogger logger = adapter;
    logger.logJson("{\"ok\":true,\"ep\":\"adapter\"}");
    System.out.println("lastXml=" + adapter.lastXml());
  }
}
```

Walkthrough Output

```
=== Adapter walkthrough ===
lastXml=<payload>{"ok":true,"ep":"adapter"}</payload>
```

Step-by-Step Trace

- Each stdout line maps to a refactor stage.
- Re-run Demo locally on JDK 25 to verify.
- Differences usually mean a dirty tree — pull main.
- Pause the video and predict the next line before revealing.

Modern Java 25 / Zazr

```
// Java 25 / Zazr direction for Adapter
// records + sealed + switch
// Option/Either/Validation instead of null
// virtual threads for blocking fan-out
// inject interfaces at the edge
```

Trade-offs

- Clarity vs ceremony — do not spawn five types for two lines.
- Closed sealed worlds vs open SPI plugins.
- Teaching demos omit production idempotency/metrics.
- Prefer simpler language features when they erase the force.

Related Patterns

- Contrast with the neighbor pattern (force difference).
- Name the roles from memory in sixty seconds.
- Point to the season map for what comes next.
- Link the GitHub episode folder in the description.

Recap

- Force → naive pain → Adapter → Demo stdout.
- Modernize with Java 25 / Zazr when it shrinks code.
- Teach when NOT to use it.
- Practice: break a test, fix it, re-run Demo.