Cake Pattern

eason: 7 · Advanced FP · Category: Functional · Level: Advanced · Build with Waq


Today's Hook

- Today: Cake Pattern as a StreamForge product force — not trivia.
- Runnable Demo on JDK 25 with captured stdout.
- Classic encoding → Java 25 / Zazr modernization → trade-offs.
- CapCut slides + full spoken script included.

The Problem

- Naive local fixes: more ifs, statics, nulls, or threads.
- Illegal states still compile; tests become order-dependent.
- Design reviews lack a shared name for the force.
- Interviews punish memorization without judgment.

Structure



Cake Pattern structure

Real-World Scenario

- StreamForge creator platform is the running metaphor.
- Same names appear in naive code, refactor, and Demo output.
- Stay in one story for the full 10–12 minutes.
- Product language first; pattern vocabulary second.

Naive Code

```
// Naive sketch for Cake Pattern
public class Naive {
  // duplicated logic / leaked details / unsafe sharing
  Object doIt(Object... args) {
    if (args == null) return null;
    return args[0];
  }
}
```

Why Naive Hurts

- Coupling spreads across controllers and infrastructure.
- Tests need sleeps or static reset hooks.
- New variants require shotgun edits.
- On-call cannot reason about failure modes.

Implementation

```java
// file: src/main/java/com/buildwithwaqar/patterns/functional/cake/CakePattern.java
package com.buildwithwaqar.patterns.functional.cake;

/**
 * Cake pattern (Scala) emulated with Java interfaces + default methods.
 * Self-type: a component declares what it needs via abstract getters;
 * the "cake" assembles mixins into one object.
 */
public final class CakePattern {
    private CakePattern() {}

    public interface UserRepoComponent {
        UserRepo userRepo();
    }

    public interface UserRepo {
        String findEmail(String id);
    }

    public interface EmailServiceComponent {
        EmailService emailService();
    }
```

Implementation (2)

```
public interface EmailService {
    String send(String to, String body);
}

public interface UserServiceComponent extends UserRepoComponent, EmailServiceComponent {
    default UserService userService() {
        return id -> {
            var email = userRepo().findEmail(id);
            return emailService().send(email, "welcome " + id);
        };
    }
}

public interface UserService {
    String welcome(String id);
}

/** The cake — wires live implementations. */
public static final class App implements UserServiceComponent {
    public UserRepo userRepo() { return id -> id + "@example.com"; }
    public EmailService emailService() { return (to, body) -> "sent:" + to + ":" + body; }
}
```

Implementation (3)

```
}
```

Demo.main

```java
package com.buildwithwaqar.patterns.functional.io;
import java.util.concurrent.atomic.AtomicInteger;
public final class Demo {
  public static void main(String[] a) {
    System.out.println("=== IO walkthrough ===");
    var hits = new AtomicInteger();
    IO<Integer> io = IO.delay(hits::incrementAndGet).map(n -> n + 10);
    System.out.println("hitsBefore=" + hits.get());
    System.out.println("run=" + io.unsafeRun());
    System.out.println("hitsAfter=" + hits.get());
  }
}
```

Walkthrough Output

```
=== Cake Pattern walkthrough ===
sent:42@example.com:welcome 42
```

Step-by-Step Trace

- Each stdout line maps to a refactor stage.
- Re-run Demo locally on JDK 25 to verify.
- Differences usually mean a dirty tree — pull main.
- Pause the video and predict the next line before revealing.

Modern Java 25 / Zazr

```
// Java 25 / Zazr direction for Cake Pattern
// records + sealed + switch
// Option/Either/Validation instead of null
// virtual threads for blocking fan-out
// inject interfaces at the edge
```

Trade-offs

- Clarity vs ceremony — do not spawn five types for two lines.
- Closed sealed worlds vs open SPI plugins.
- Teaching demos omit production idempotency/metrics.
- Prefer simpler language features when they erase the force.

Related Patterns

- Contrast with the neighbor pattern (force difference).
- Name the roles from memory in sixty seconds.
- Point to the season map for what comes next.
- Link the GitHub episode folder in the description.

Recap

- Force → naive pain → Cake Pattern → Demo stdout.
- Modernize with Java 25 / Zazr when it shrinks code.
- Teach when NOT to use it.
- Practice: break a test, fix it, re-run Demo.