PDFTOHTML(1) PDFTOHTML(1)

NAME

pdftohtml - program to convert PDF files into HTML, XML and PNG images

SYNOPSIS

pdftohtml [options] <PDF-file> [<HTML-file> <XML-file>]

DESCRIPTION

This manual page documents briefly the **pdftohtml** command. This manual page was written for the Debian GNU/Linux distribution because the original program does not have a manual page.

pdftohtml is a program that converts PDF documents into HTML. It generates its output in the current working directory.

OPTIONS

A summary of options are included below.

-h, -help

Show summary of options.

-f <int>

first page to print

-l <int>

last page to print

- -q do not print any messages or errors
- -v print copyright and version info
- -p exchange .pdf links with .html
- **-c** generate complex output
- -s generate single HTML that includes all pages

-dataurls

use data URLs instead of external images in HTML. No available in all platforms

-i ignore images

-noframes

generate no frames. Not supported in complex output mode.

-stdout

use standard output

-zoom < fp >

zoom the PDF document (default 1.5)

-xml output for XML post-processing

-noRoundedCoordinates

do not round coordinates (with XML output only)

-enc <string>

output text encoding name

-opw <string>

owner password (for encrypted files)

-upw <string>

user password (for encrypted files)

-hidden

force hidden text extraction

-fmt image file format for Splash output (png or jpg). If complex is selected, but -fmt is not specified, -fmt png will be assumed

PDFTOHTML(1) PDFTOHTML(1)

-nomerge

do not merge paragraphs

-nodrm

override document DRM settings

-wbt < fp >

adjust the word break threshold percent. Default is 10. Word break occurs when distance between two adjacent characters is greater than this percent of character height.

-fontfullname

outputs the font name without any substitutions.

AUTHOR

Pdftohtml was developed by Gueorgui Ovtcharov and Rainer Dorsch. It is based and benefits a lot from Derek Noonburg's xpdf package.

This manual page was written by S\oren Boll Overgaard <boll@debian.org>, for the Debian GNU/Linux system (but may be used by others).

SEE ALSO

 $\label{eq:pdfdetach} \begin{aligned} &\textbf{pdffonts}(1), \ \ \textbf{pdfimages}(1), \ \ \textbf{pdfinfo}(1), \ \ \textbf{pdftocairo}(1), \ \ \textbf{pdftoppm}(1), \$