Rebuilding and checking PDF documentation

Markdown is the source of truth. For user-facing project documents outside `docs/reports/`, the adjacent PDF is a generated deliverable; never edit it independently. Task reports and addenda are Markdown only. This process builds documentation only. It does not install or configure lab infrastructure.

1. Toolchain

The build uses free Python libraries pinned in `requirements-docs.txt`: ReportLab for PDF layout/vector drawing, Mistune for Markdown parsing, Pygments for code highlighting, and pypdf for structural/text/link validation. Pillow and charset-normalizer are pinned ReportLab dependencies. No paid application, office suite, browser automation, or remote rendering service is required.

The task environment provides Python 3.12.14, ReportLab 4.4.9, pypdf 6.10.0, and Poppler 26.07.0. Mistune 3.4.0 and Pygments 2.21.0 were added only to an ignored local dependency directory. A normal Windows checkout can use its own documentation virtual environment instead of depending on Codex paths.

2. Windows setup and one-command rebuild

Run from the repository root with an existing Python 3.11 or later installation. Create a local documentation environment and install the pinned free dependencies when needed:

```
python -m venv .venv-docs
.\.venv-docs\Scripts\python.exe -m pip install -r requirements-docs.txt
```

Rebuild all PDF editions with one command:

```
.\.venv-docs\Scripts\python.exe scripts/build_docs.py
```

With the environment activated, the equivalent is `python scripts/build_docs.py`. The build works on Windows and Linux. Installation is limited to documentation dependencies in the chosen environment; it has no Proxmox, VM, firewall, network, directory, or production operation.

3. Generated files and consistency

Every maintained user-facing Markdown document outside `docs/reports/` has a PDF beside it. The approved source set includes root guides, purpose-specific documents, folder instructions, and public evidence guidance/records. The entire `docs/reports/` directory is excluded, including indexes, nested files, task reports and addenda. Discovery and direct rendering also reject the legacy root report path. Compatibility navigation aliases are excluded as duplicate navigation pages. Unknown source/PDF pairs fail validation.

The five archived PDFs were published in the root report folder at T3 commit `d1b575761c090c35dac535ec331a1e32f9bd5fe6`. T4 moves them to `docs/reports/` with the six existing Markdown files, preserving all eleven byte for byte. They are excluded from the generated manifest and all rebuilds. Validation pins the complete migration's SHA-256 hashes, rejects missing/changed historical files, duplicate old locations and new report PDFs, and compares finalized history across both paths. No current Markdown/PDF pairing is required for an archive. Their old instructions are historical; the current report index defines Markdown-only reporting. No historical Markdown or Git record is rewritten.

`docs/documentation-manifest.json` records relative source/PDF paths, SHA-256 hashes, page count, source text-token coverage, links/bookmarks, and the toolchain/renderer fingerprint. The document version shown in each PDF is derived from its source hash, not the current date or Git HEAD. Fixed PDF metadata and embedded package fonts make output reproducible. Unchanged inputs skip generation, and byte-identical output is not rewritten.

The build preserves paragraph/list/table content, code, and links. It numbers PDF sections, repeats table headers across pages, wraps long cells/code, creates page numbers and navigation, and gives longer documents a title page and contents. It renders this repository's Mermaid flowchart subset as a vector figure with the same nodes/edges/labels; an unsupported diagram fails rather than disappearing. Syntax highlighting changes presentation, not source commands. Typography converts Unicode dashes and unsupported arrow glyphs to readable ASCII equivalents; Markdown remains unchanged.

The assignment alone uses a compact cover with linked contents, 10-point body text and simpler tables. Its layout rules are selected by its exact source path; other document styles remain unchanged. Report relocation may require rebuilding other documents to update their report links. A renderer-fingerprint change rechecks all sources, but byte-identical outputs are not rewritten.

External URLs are retained. Same-document anchors become PDF navigation. Cross-document links point to the corresponding public PDF edition, except links into `docs/reports/`, which open the Markdown source and its normal heading anchor on GitHub. The old decision/risk aliases and additional aliases under `docs/docs/` and `docs/evidence/` preserve relative links in the unchanged relocated files. The manifest alias is a JSON navigation record pointing to the current generated manifest. PDF reader support for external/named destinations varies. Code blocks are reference text, not active commands or executable attachments.

4. Validation and visual review

Run these commands after a rebuild:

```
.\.venv-docs\Scripts\python.exe scripts/build_docs.py --check --rebuild-check
python scripts/validate_docs.py --require-finalized
.\.venv-docs\Scripts\python.exe -m unittest discover -s tests -v
git diff --check
```

The PDF check opens every generated document output outside `docs/reports/`, checks text extraction/searchability, page/footer/navigation/link structure, coverage of source text with layout line-break normalization, and source/PDF hashes. The rebuild check renders fresh PDFs in memory and compares bytes. Documentation validation checks migrated links, Markdown report structure without PDF pairing, archive integrity, requirement/stage structure, publication patterns, and finalized-history preservation. Regression tests verify report exclusion and unchanged-output skipping, links to report Markdown, all eight submission filenames and requirement coverage, unchanged rubric weights and guide stages, byte-preserved relocation, rejection of missing/changed migration files and duplicate locations, and continued document-PDF drift detection. CI installs the pinned libraries, runs these checks, and never connects to the lab.

Text extraction does not establish visual quality. Render representative pages using an available Poppler installation and inspect the result:

```
pdftoppm -f 1 -l 3 -r 110 -png docs/assignments/PROJECT-ASSIGNMENT.pdf tmp/pdfs/assignment
```

Review title/contents pages, long tables, the architecture figure, command blocks, and page transitions of changed document PDFs. Check for clipping, overlap, missing glyphs, unreadable type, broken rows, and incorrect headers/footers. Report Markdown changes do not require PDF rendering. Keep previews under ignored `tmp/pdfs/`; do not publish raw screenshots or local environment details. If Poppler is absent, obtain an approved local renderer before claiming visual review. No renderer is assumed installed by this guide.

5. Troubleshooting and recovery

The eight native Word/Excel files in the deliverable index are editable blank sources and receive no PDFs. `python scripts/validate_office_templates.py` performs an offline, standard-library check of their exact names, XML-only package contents, safe relationships/formulas, table controls, blank result fields and approved requirement/test definitions. The main validator includes this check. Unrelated binaries remain rejected. Native opening/editing/recalculation and visual layout review are separate observations; CI does not run Microsoft Office or validate lab controls. Review filled working records privately before any later publication task.

- Missing library: use the documentation environment and pinned requirements; do not modify global software or install lab products.
- Stale/missing PDF or manifest entry: rebuild from source, then rerun both checks. Do not edit a PDF or hash entry to hide a mismatch.
- Layout failure: fix the renderer or editable source, rebuild, and inspect affected pages again. Keep finalized historical report Markdown unchanged.
- Broken link after a move: update editable references and the source/output map. Retain compatibility navigation when an immutable historical source needs it.
- Unexpected binary change: compare source, renderer, font, and toolchain fingerprints. A no-change rebuild must leave bytes unchanged.
- Failed publication: retain the reviewed branch, inspect actual CI errors, and reconcile through normal Git; never force-push away work or rewrite finalized reports.

The project license remains an owner decision. This toolchain uses existing free dependencies and does not select a software license for the repository.