Task 001 bootstrap verification record

Table 1. Document

Field	Observed value
Evidence ID	EV-T00-20261105-01
Project / scope	HL-CYB-001; documentation, repository/publication checks only
Recorded	2026-11-05 America/Toronto; publication snapshot read back at 2026-11-06 00:47:31 UTC
Requirements / tests	R11, R15, R16; T00 and repository-only T17
Operator	Repository engineering assistant; no separate human reviewer sign-off claimed
Owner UAT	PENDING
Operational/security tests	NOT RUN; no implementation stage started
Initial verified commit	`2640261ad2738f1e6d4497ee68636621ed403ea3`
Repository / branch	waqashamdani-ca/enterprise-zero-trust-security, PUBLIC, `main`
CI	Run 42139263675: completed / success

1. Preflight and content review

The starting workspace was empty, with no Git history or existing content to overwrite. Git 2.47.0.windows.2, GitHub CLI 2.97.0, Python 3.13.0, and Git Credential Manager 2.6.0 were available. No tools were installed. Existing authentication identified `waqashamdani-ca`. The GitHub integration and authenticated CLI found no accessible target repository before creation. After creation, both confirmed public visibility, `main`, and administrator/push permission.

The initial commit contained twenty newly authored public text artifacts, including fifteen Markdown documents. File inventory and full authored-content review found documentation, documentation-check code/tests, ignore/line-ending policy, and the least-privilege workflow only. No preexisting/proprietary source, production export, actual internal address, sensitive identity, secret, raw log/capture, backup, or VM image was included. All staged blobs matched the reviewed worktree bytes and passed the focused staged-content scan. The author email is the verified account's GitHub noreply address.

The completion-record update adds this Markdown evidence file and changes only README/report/change-history documentation. Its final commit SHA and corresponding CI result are read back after publication and reported in the final response; this record does not pretend to contain its own commit hash.

2. Checks and results

Table 2. Checks and results

Check actually performed	Result / limit
`python scripts/validate_docs.py`	PASS on the initial twenty-file set: required files/directories, local Markdown destinations/anchors, table/fence checks, assignment sections, A-L stage fields, R01-R16 coverage, T00-T20 catalog, 100-point rubric, workflow constraints, selected publication patterns
`python -m unittest discover -s tests -v`	PASS: twelve focused tests covering token-value nondisclosure, address/email hygiene, private/binary rejection, tracked ignored files, link/anchor/path/scheme/fence/table cases
Independent document/capacity counts	Sixteen requirements; twelve stages; planned guest totals 36 GiB RAM / 248 GiB virtual disks; calculations only, no allocations created
`git diff --cached --check` and `git diff --check`	PASS; staged content reviewed before initial commit
External reference reachability	Fifty retained reference URLs; thirty-seven HTTP successes, thirteen local-client transport/certificate validation failures; primary-source browsing used as additional research, no TLS bypass
Public artifact review	Focused scanner plus authored-content/staged review; no selected findings; all files reviewed as text, no binary metadata to sanitize
Existing repository preservation	No target repository found before creation; no remote history overwritten, reset, or force-pushed
Authentication/publication	CLI token could create the repo but its workflow-file push was rejected; existing secure Git Credential Manager login pushed the same commit successfully; expected push actor verified
Hosted workflow	Validation, twelve-test suite, and whitespace steps all succeeded on GitHub-hosted Ubuntu; read-only repository token, commit-pinned checkout, no retained checkout credentials, no lab access
License / governance	No license selected; stage approval, task branches/PRs, focused commits, and intentional synchronization documented

Restricted Windows execution could not access Python-created temporary fixture directories. Tests passed with normal filesystem permissions and then also passed on the hosted Linux runner. Workspace test leftovers were removed only from the exact verified test fixture directory. This was a documentation-test environment limitation, not a lab/security test result.

3. Synchronization read-back

The following read-only commands were actually run after the initial successful push:

```
git remote -v
git status --short --branch
git branch -vv
git log -1 --format=fuller
git ls-remote origin
```

Observed: fetch/push origin was the authorized HTTPS repository URL with no embedded credential; local `main` tracked `origin/main`; the worktree/index were clean; local HEAD, tracking ref, remote HEAD, and remote `refs/heads/main` all equaled `2640261ad2738f1e6d4497ee68636621ed403ea3`. GitHub's run record identified the actor as `waqashamdani-ca`. The same checks are repeated for the completion-record commit

before the final response.

4. Verification limits and stop

The custom scan covers selected credential formats, real address/email literals, sensitive filenames/directories, and text-artifact policy. It is not an exhaustive secret detector or proprietary-code classifier. Manual content/history review remains mandatory. External links are not fetched by CI. No physical inventory, firewall effectiveness, domain/PKI function, remote-access policy, logging, recovery, or business UAT outcome is inferred from these checks.

Task 001 technical publication is complete at this snapshot. No infrastructure was installed or changed and no security tests were run. Stop for owner review; the next single task is a separately approved read-only Stage A hardware and isolation readiness assessment. Licensing, repository protection/review enforcement, hardware/storage/backup feasibility, and isolated egress remain owner decisions.