



NATIONAL DEVELOPMENT COMPLEX
Deputy Directorate General of Quality Control
Metrology-3
TEST REPORT

Test Report No: TR (817)/PML/22

Job Card No: JC (920)/PML/22

Date: 14-12-2022

INDENTER'S DATA	
Name: Muhammad Shafiq	Designation: SRA
Group & Site: Winding/ 3-C	Directorate: ADP Dte.
Organization: NDC	Contact No.: Ext. 3641

GENERAL DATA	
Project Name: S1AM	Assembly/Sub Assembly:
Sample/Part Name: Nose Sink Assembly (With Ablative)	
ID No.: M21079714	
Quantity: 01	Lot No/Set No.: Prod# 06
Ambient Temperature (°C): 20°C ±2°C	Sample Receiving Date: 12-12-2022
	Test Date: 13-12-2022

TEST DATA	
Instrument Type:	Faro Arm, CTM, BP & WS.
Standard test Method:	ASME Y14.5-2009.
Qualification Criteria:	Measured as per MDE Criteria marked on drawing No: P1V3-NOSE-01-00, Rev 0; P1V3-NOSE-01-00, Rev 0.
Test Results:	Non-Conformed.
Remarks:	1. These results relates to the samples as received mentioned and tested above. 2. This Test report shall not be reproduced except in full without written approval of laboratory. 3. Measured results attached (02 pages).

Test Performed By:	Mr. Mujeeb Ur Rehman (FM-i): Mr. Nasir Mehmood (CM)	Contact No. 3154
Prepared By:	Mr. Yasir Baig AM (Mech): <i>Yasir</i> 14/12/22	Contact No. 3148

Reviewed By:	HoD (Met-3): <i>Zia</i> 14/12/22 Mr. Zia Ur Rehman
Approved By:	PD (Met): <i>Shahid</i> 14/12/22 Mr. Shahid Haroon

Met/FM/02, Issue 03, 10-11-2013

Deputy Directorate General of Quality Control

Metrology-3

PML, Site # 3-F

Name of Item: Nose Sink Assy. with Ablative (S1AM)

Date: 14-12-2022

No. of Items: 01

Test Report No: TR (817)/PML/22

ID No.: M21079714

Incident Name: Muhammad Shafiq, SRA, Winding, ADP Dte., Site # 3-C.

Measurements:

Sr. #	Description	Design Value (mm)	Measured Value (mm)	Status
Major Parameters:				
01.	Flatness of the front side (Ablative)	0.2	0.1	OK
02.	Perpendicularity of front side	0.2	0.1	OK
03.	Step height front side	5 +0.1,0	5.0	OK
04.	Flatness of the rear flange	0.2	0.1	OK
05.	Step height rear side	5 +0.0,0.1	5.0	OK
06.	Perpendicularity of front side	0.2	0.1	OK
07.	Edge distance b/w 2 Dias at front side	7.8 +0.2,+0.1	≈8.0	OK
08.	Edge distance at front side	6 +0.2,+0.1	≈6.2	OK
09.	Edge distance b/w 2 Dias at rear side	6 0.0,0.1	Fitting check	OK
10.	Edge distance at rear side	7.8 0.0,0.1	with FEC	
11.	Most Inner Dia at front side	Ø124.9 +0.3,+0.1	Not possible due	
12.	Most Dia at rear side	Ø261.9 +0.3,+0.1	to Assembly	
13.	Ablative Thickness at Line A:	Point 1	11.9	OOT
	Point 2	10 +1.0	11.6	OOT
	Point 3		11.6	OOT
	Point 4		12.4	OOT
	Ablative Thickness at Line B:		Point 1	11.7
	Point 2	10 +1.0	11.6	OOT
	Point 3		11.7	OOT
	Point 4		12.3	OOT
	Ablative Thickness at Line C:		Point 1	11.8
	Point 2	10 +1.0	11.6	OOT
	Point 3		11.9	OOT
	Point 4		12.3	OOT
	Ablative Thickness at Line D:		Point 1	11.6
	Point 2	10 +1.0	11.3	OOT
	Point 3		11.8	OOT
	Point 4		12.4	OOT
	Ablative Thickness at Line E:		Point 1	11.6
	Point 2	10 +1.0	11.4	OOT
	Point 3		11.7	OOT
	Point 4		12.4	OOT
	Ablative Thickness at Line F:		Point 1	11.6
	Point 2	10 +1.0	11.4	OOT
	Point 3		11.9	OOT
	Point 4		12.5	OOT
	Ablative Thickness at Line G:		Point 1	11.7
Point 2	10 +1.0	11.4	OOT	
Point 3		11.7	OOT	

		Point 4		12.4	OOT
	Ablative Thickness at Line H:	Point 1		11.7	OOT
		Point 2		11.6	OOT
		Point 3	10	11.8	OOT
		Point 4	+1.0	12.6	OOT
	Minor Parameters:				
	Angle 1 at Flange 2	9.37°	±5	9°22'	OK
2.	Profile of wall	0.2		0.1	OK
3.	Overall length	415	±0.5	415.5	OK
	Other Parameter:				
1.	Mass of nose sink Assembly	66.44Kg		66.44Kg	OK

Remarks:

1. Measured as per MDE Criteria marked on drawing No: P1V3-NOSE-01-00, Rev 0; P1V3-NOSE-01-02, Rev 0.
2. Fitting check of rear flange of nose sink is carried out with FEC having ID # S1AM-B1-B-SKN-06
3. Tolerance on mass is not mentioned in drawing.
4. Ablative thickness includes air gaps/epoxy material (if any).
5. All linear and angular tolerances (unless otherwise specified) are as according to ISO 2768-1 with medium tolerance class.

Tolerances are (unless otherwise specified):
ISO 2768-1

0.5 to 6 = ± 0.1 mm
Over 6 to 30 = ± 0.2 mm
Over 30 to 120 = ± 0.3 mm
Over 120 to 400 = ± 0.5 mm
Over 400 to 1000 = ± 0.8 mm
Over 1000 to 2000 = ± 1.2 mm
Over 2000 to 4000 = ± 2 mm

Angular Tolerances are (unless otherwise specified):
ISO 2768-1

up to 10° = ± 1°
over 10 up to 50° = ± 0°30'
over 50 up to 120° = ± 0°20'
over 120 up to 400° = ± 0°10'
over 400° = ± 0°5'

These are permissible deviations for ranges of length in millimeters of the shorter side of the angle concerned.


QA Rep