



P.METAL CHEM TRADING CO., LTD.

129/157 Soi Bangbon 3 Soi 14 Lanksong Bangkae Bangkok 10160

Tel. 034-496478 , 034-496479 Fax. 034-496477

MATERIAL SAFETY DATA SHEET

Commercial product name : PF – 18

1. Chemical characterization

Alkaline

2. Composition

Component Name	CAS Number	Concentration %
Sodium Hydroxide	1310-73-2	>20%
Deionized Water	7732-18-5	<80%

3. Form

Liquid

Appearance

Clear liquid

PH-Value

approx. 14 of a 1% solution

4. REACTIVITY DATA

Stability	: Stable
Materials to Avoid	: Avoid corrosive materials
Condition to Avoid (Stability)	: None
Hezardous Poly Occur	: None
Hezardous Decomposition	: May form toxic materials, Phosphorous oxides.

5. HAZARDS IDENTIFICATION

- Inhalation

Toxic. Causes irritation to the respiratory tract and systemic poisoning with symptoms paralleling ingestion.

- Skin Contact

Cause irritation, redness and pain. May be absorbed through the skin causing Systemic poisoning; symptoms may parallel ingestion.

- Eye Contact

Cause irritation, redness, and pain.

6. FIRST AID MEASURES

- Inhalation

Remove to fresh air, If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

- Ingestion

Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Get Medical attention.

- Skin Contact

Immediately flush skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention if irritation develops.

- Eye Contact

Immediately flush eyes with plenty of water for at least 15 minutes. Lifting lower and upper eyelids occasionally. Get medical attention immediately.

7.EXPOSURE CONTROLS / PERSONAL PROTECTION

- Skin Protection

Wear impervious protective clothing, including boots, gloves, lab coat to prevent skin contact.

- Eye Protection

Use chemical safety goggles and/or full face shield where dusting or splashing of solutions is possible. Maintain eye wash fountain and quick facilities in work area.

8. STABILITY AND REACTIVITY

- Stability

This material is stable in closed containers at room temperature. Material slowly oxidizes to sodium nitrate when exposed to air. Very hygroscopic.

9. FIRE FIGHTING MEASURES

Flash Point	: Not applicable
Method used	: Not applicable
<i>Flammability Classification</i>	: <i>Not applicable</i>
Upper Flammable Limit (UFL)	: Not applicable
<i>Lower Flammable Limit (LFL)</i>	: <i>Not applicable</i>
Fire & Explosion Hazards	: This material will not burn.
Decomposition Product	: Irritating and toxic gases or fumes may be released during A fire.
Extinguishing Media	: Use any media suitable for the surrounding fires.
Fire-Fighting instructions	: Firefighters should wear full protective clothing including Self contained breathing apparatus.

10. ACCIDENTAL RELEASE MEASURES

Containment Procedures	: Stop the flow of material, if this is without risk , Wear Appropriate protective equipment and Clothing during Clean-up.
------------------------	--

Clean-up Procedures : Sweep up or gather and place in appropriate container
For disposal. Dispose of Collected material according
To regulation.

HEALTH DATA

Precaution : Avoid contact with eyes, skin and clothes,

REACTIVITY DATA

Stability : Stable
Materials to Avoid : Avoid corrosive materials
Condition to Avoid (Stability) : None
Hazardous Poly Occur : None
Hazardous Decomposition : May form toxic materials, Phosphorous
oxides.

FIRST AID

Skin Contact : In case of contact, Immediately flush skin with
plenty of water for 15 minutes.
Eye Contact : In case of contact, immediately flush eyes with
plenty of water for 15 minutes and call a doctor.
Inhalation : Moved to fresh air, give oxygen if necessary,
call a doctor.
Ingestion : do not induce vomiting, dilute by giving water
and milk, call a doctor

ADDITIONAL INFORMATION

Handling / Storage Precautions : Protect from Physical damage, store away from
heat and sun. Addition to water can result in
violent boiling and spattering.

PACKING : 20 KG. net in Blue or Black poly can.