

# API PIAG - Appels CHAT

## 📌 Phase d'expérimentations

L'offre API PIAG est en cours de construction.

## Appels API supportés

### 📌 Note

Remplacer dans les requêtes "sk-xxxxx" par une apiKey valide

- Récupérer des informations sur une "apikey" (max\_budget, spend) - endpoint "apikey/info"

```
curl -X GET https://preprod.api.piag.e2.rie.gouv.fr/apikey/info \
-H "Content-Type: application/json" \
-H "Authorization: Bearer sk-xxxxx"
```

- Conversation avec réponses directes - endpoint "chat/completions"

```
curl -X POST https://preprod.api.piag.e2.rie.gouv.fr/v1/chat/completions \
-H "Content-Type: application/json" \
-H "Authorization: Bearer sk-xxxxx" \
-d '{
  "model": "mte-api-piag-mistral-medium-latest",
  "messages": [
    {
      "role": "user",
      "content": "bonjour"
    }
  ]
}'
```

- Conversation avec réponses en streaming - endpoint "chat/completions" avec paramètre "stream"

```
curl -X POST https://preprod.api.piag.e2.rie.gouv.fr/v1/chat/completions \
-H "Content-Type: application/json" \
-H "Authorization: Bearer sk-xxxxx" \
-d '{
  "model": "mte-api-piag-mistral-medium-latest",
  "messages": [
    {
      "role": "user",
      "content": "bonjour"
    }
  ],
  "stream": true
}'
```

- Complétion de texte - endpoint "completions"

```
curl -X POST https://preprod.api.piag.e2.rie.gouv.fr/v1/completions \
-H "Content-Type: application/json" \
-H "Authorization: Bearer sk-xxxxx" \
-d '{
  "model": "mte-api-piag-mistral-medium-latest",
  "prompt": "Bonjour",
  "max_tokens": 50,
  "temperature": 0.7
}'
```