

Part 4

Classification: Basic Concepts, Decision Trees & Model Evaluation

Part 1

Classification With Decision tree

NGURAH AGUS SANJAYA ER, S.KOM, M.KOM, PH.D
E-mail: agus.sanjaya@cs.unud.ac.id

Classification: Definition




- Given a collection of records (training set)
 - Each record is characterized by a tuple (x,y) , where x is the attribute set and y is the class label
 - x : attribute, predictor, independent variable, input
 - y : class, response, dependent variable, output
- Task:
 - Learn a model that maps each attribute set x to one of the predefined class labels y

Example of Classification Task

Task	Attribute set, x	Class label, y
Categorizing email messages	Features extracted from email message header and content	spam or non-spam
Identifying tumor cells	Features extracted from MRI scans	malignant or benign cells
Cataloging galaxies	Features extracted from telescope images	Elliptical, spiral, or irregular-shaped galaxies

General Approach for Building Classification Model




Classification Techniques

- Classifier → a systematic approach to building classification models from an input data set.
- Examples :
 - Decision tree classifier
 - Rule-based classifier
 - Neural networks
 - Support vector machines
 - Naïve Bayes

Example of Decision Tree

ID	Home Owner	Marital Status	Annual Income	Defaulted Borrower
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes


Training Data



Model: Decision Tree

Another Example of Decision Tree

ID	Home Owner	Marital Status	Annual Income	Defaulted Borrower
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes



There could be more than one tree that fits the same data!


Decision Tree Classification Task

Tid	Attrib1	Attrib2	Attrib3	Class
1	Yes	Large	125K	No
2	No	Medium	100K	No
3	No	Small	70K	No
4	Yes	Medium	120K	No
5	No	Large	95K	Yes
6	No	Medium	60K	No
7	Yes	Large	220K	No
8	No	Small	85K	Yes
9	No	Medium	75K	No
10	No	Small	90K	Yes

Training Set

Tid	Attrib1	Attrib2	Attrib3	Class
11	No	Small	55K	?
12	Yes	Medium	80K	?
13	Yes	Large	110K	?
14	No	Small	95K	?
15	No	Large	67K	?


Test Set



Apply Model to Test Data

Test Data

Home Owner	Marital Status	Annual Income	Defaulted Borrower
No	Married	80K	?



Performance Evaluation

- Performance evaluation → based on the counts of test records correctly and incorrectly predicted by the model.
- These counts are tabulated in a table known as a confusion matrix.
- Each entry f_{ij} in this table denotes the number of records from class i predicted to be of class j .
- For instance, f_{01} is the number of records from class 0 incorrectly predicted as class 1.


Confusion Matrix

		Predicted Class	
		Class = 1	Class = 0
Actual Class	Class = 1	f_{11}	f_{10}
	Class = 0	f_{01}	f_{00}

$$Accuracy = \frac{f_{11} + f_{00}}{f_{11} + f_{10} + f_{01} + f_{00}}$$

$$Error\ rate = \frac{f_{10} + f_{01}}{f_{11} + f_{10} + f_{01} + f_{00}}$$

Decision Tree Classification Task



Decision Tree Induction




- Many Algorithms:
 - Hunt's Algorithm (one of the earliest)
 - CART
 - ID3, C4.5
 - SLIQ, SPRINT

General Structure of Hunt's Algorithm

- Let D_t be the set of training records that reach a node t
- General Procedure:
 - If D_t contains records that belong the same class y_t , then t is a leaf node labeled as y_t
 - If D_t contains records that belong to more than one class, use an attribute test to split the data into smaller subsets. Recursively apply the procedure to each subset.



ID	Home Owner	Marital Status	Annual Income	Defaulted Borrower
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes



Hunt's Algorithm


Defaulted = No

(a)



(b)

ID	Home Owner	Marital Status	Annual Income	Defaulted Borrower
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes



(c)

(d)

Design Issues of Decision Tree Induction


- How should training records be split?
 - Method for specifying test condition
 - Depending on attribute types
 - Measure for evaluating the goodness of a test condition
- How should the splitting procedure stop?
 - Stop splitting if all the records belong to the same class or have identical attribute values
 - Early termination

Methods for Expression Test Conditions


- Depends on attribute types
 - Binary
 - Nominal
 - Ordinal
 - Continuous
- Depends on number of ways to split
 - 2-way split
 - Multi-way split

Test Condition for Nominal Attributes

- Multi-way split:
 - Use as many partitions as distinct values.




- Binary split:
 - Divides values into two subsets
 - Need to find optimal partitioning.




Test Condition for Ordinal Attributes


- Multi-way split:
 - Use as many partitions as distinct values
- Binary split:
 - Divides values into two subsets
 - Need to find optimal partitioning
 - Preserve order property among attribute values



Test Condition for Continuous Attributes



(i) Binary split



(ii) Multi-way split

Splitting Based on Continues Attributes


- Different ways of handling
 - **Discretization** to form an ordinal categorical attribute
 - Static – discretize once at the beginning
 - Dynamic – ranges can be found by equal interval bucketting, equal frequency bucketting (percentiles) or clustering
 - **Binary Decision:** $(A < v)$ or $(A >= v)$
 - Consider all possible splits and finds the best cut
 - Computation can be more intensive

How to Determine the Best Split / 1



Before Splitting: 10 records of class 0,
10 records of class 1

Customer Id	Gender	Car Type	Shirt Size	Class
1	M	Family	Small	C0
2	M	Sports	Medium	C0
3	M	Sports	Medium	C0
4	M	Sports	Large	C0
5	M	Sports	Extra Large	C0
6	M	Sports	Extra Large	C0
7	F	Sports	Small	C0
8	F	Sports	Small	C0
9	F	Sports	Medium	C0
10	F	Luxury	Large	C0
11	M	Family	Large	C1
12	M	Family	Extra Large	C1
13	M	Family	Medium	C1
14	M	Luxury	Extra Large	C1
15	F	Luxury	Small	C1
16	F	Luxury	Small	C1
17	F	Luxury	Medium	C1
18	F	Luxury	Medium	C1
19	F	Luxury	Medium	C1
20	F	Luxury	Large	C1



Which test condition is the best?

How to Determine the Best Split / 2

- Greedy approach:
 - Nodes with **purer** class distribution are preferred
- Need a measure of node impurity:

C0: 5
C1: 5

High degree of impurity

C0: 9
C1: 1

Low degree of impurity

Measures of Node Impurity

- Gini Index

$$GINI(t) = 1 - \sum_j [p(j|t)]^2$$

- Entropy

$$Entropy(t) = -\sum_j p(j|t) \log p(j|t)$$

- Misclassification error

$$Error(t) = 1 - \max_i P(i|t)$$

Finding the Best Split / 1

- Compute impurity measure (P) before splitting
- Compute impurity measure (M) after splitting

- Compute impurity measure of each child node
- Compute the average impurity of the children

$$M = \sum_{j=1}^k \frac{N(v_j)}{N} I(v_j)$$

where :

I = impurity measure of a given node

N = the total number of records at the parent node

k = the number of attribute values

$N(v_j)$ = the number of records associated with the child node, v_j

- Choose the attribute test condition that produces the highest gain

$$\Delta = P - M$$

or equivalently, **lowest impurity measure after splitting**



- If entropy is used as the impurity measure then the difference in entropy is known as the information gain, Δ_{info}

Finding the Best Split / 2

Before Splitting:

C0	N00
C1	N01

→ P



C0	N10
C1	N11

C0	N20
C1	N21

C0	N30
C1	N31

C0	N40
C1	N41

↓
M11

↓
M12

↓
M21

↓
M22

 M1

 M2

$$\text{Gain} = P - M1 \quad \text{vs} \quad P - M2$$

Measure of Impurity: GINI

- Gini Index for a given node t :

$$GINI(t) = 1 - \sum_j [p(j | t)]^2$$

(NOTE: $p(j | t)$ is the relative frequency of class j at node t).

- Maximum ($1 - 1/n_c$) when records are equally distributed among all classes, implying least interesting information
- Minimum (0.0) when all records belong to one class, implying most interesting information

C1	0
C2	6
Gini=0.000	

C1	1
C2	5
Gini=0.278	

C1	2
C2	4
Gini=0.444	

C1	3
C2	3
Gini=0.500	

Computing GINI Index of a Single Node

$$GINI(t) = 1 - \sum_j [p(j | t)]^2$$

C1	0
C2	6

$$P(C1) = 0/6 = 0 \quad P(C2) = 6/6 = 1$$

$$Gini = 1 - P(C1)^2 - P(C2)^2 = 1 - 0 - 1 = 0$$

C1	1
C2	5

$$P(C1) = 1/6 \quad P(C2) = 5/6$$

$$Gini = 1 - (1/6)^2 - (5/6)^2 = 0.278$$

C1	2
C2	4

$$P(C1) = 2/6 \quad P(C2) = 4/6$$

$$Gini = 1 - (2/6)^2 - (4/6)^2 = 0.444$$

Computing GINI Index for a Collection of Nodes

- When a node p is split into k partitions (children)


$$GINI_{split} = \sum_{i=1}^k \frac{n_i}{n} GINI(i)$$

where, n_i = number of records at child i,
 n = number of records at parent node p.

- Choose the attribute that minimizes weighted average Gini index of the children
- Gini index is used in decision tree algorithms such as CART, SLIQ, SPRINT

Binary Attributes: Computing GINI Index

- Splits into two partitions
- Effect of Weighing partitions:
 - Larger and Purer Partitions are sought for.



Gini(N1)

$$\begin{aligned} &= 1 - (5/6)^2 - (1/6)^2 \\ &= 0.278 \end{aligned}$$

Gini(N2)

$$\begin{aligned} &= 1 - (2/6)^2 - (4/6)^2 \\ &= 0.444 \end{aligned}$$

	N1	N2
C1	5	2
C2	1	4
Gini=0.361		

	Parent
C1	6
C2	6
Gini = 0.500	

Gini(Children)

$$\begin{aligned} &= 6/12 * 0.278 + \\ &\quad 6/12 * 0.444 \\ &= 0.361 \end{aligned}$$

Categorical Attributes: Computing GINI Index

- For each distinct value, gather counts for each class in the dataset
- Use the count matrix to make decisions

Multi-way split

CarType			
	Family	Sports	Luxury
C1	1	8	1
C2	3	0	7
Gini	0.163		

Two-way split
(find best partition of values)


CarType		
	{Sports, Luxury}	{Family}
C1	9	1
C2	7	3
Gini	0.468	

CarType		
	{Sports}	{Family, Luxury}
C1	8	2
C2	0	10
Gini	0.167	

Continuous Attributes: Computing GINI Index / 1

- Use Binary Decisions based on one value
- Several Choices for the splitting value
 - Number of possible splitting values = Number of distinct values
- Each splitting value has a count matrix associated with it
 - Class counts in each of the partitions, $A < v$ and $A \geq v$
- Simple method to choose best v
 - For each v , scan the database to gather count matrix and compute its Gini index
 - Computationally Inefficient! Repetition of work.

ID	Home Owner	Marital Status	Annual Income	Defaulted
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes



Continuous Attributes: Computing GINI Index / 2

- For efficient computation: for each attribute,
 - Sort the attribute on values
 - Linearly scan these values, each time updating the count matrix and computing gini index
 - Choose the split position that has the least gini index

Cheat	No	No	No	Yes	Yes	Yes	No	No	No	No										
Annual Income																				
Sorted Values	60	70	75	85	90	95	100	120	125	220										
Split Positions	55	65	72	80	87	92	97	110	122	172	230									
	<=	>	<=	>	<=	>	<=	>	<=	>	<=	>								
Yes	0	3	0	3	0	3	1	2	2	1	3	0	3	0	3	0	3	0		
No	0	7	1	6	2	5	3	4	3	4	3	4	4	3	5	2	6	1	7	0
Gini	0.420	0.400	0.375	0.343	0.417	0.400	0.300	0.343	0.375	0.400	0.420									

Measure of Impurity: Entropy

- Entropy at a given node t:

$$Entropy(t) = -\sum_j p(j|t) \log p(j|t)$$

(NOTE: $p(j|t)$ is the relative frequency of class j at node t).

- ◆ Maximum ($\log n_c$) when records are equally distributed among all classes implying least information
- ◆ Minimum (0.0) when all records belong to one class, implying most information
- Entropy based computations are quite similar to the GINI index computations

Computing Entropy of a Single Node

$$Entropy(t) = -\sum_j p(j|t) \log_2 p(j|t)$$

C1	0
C2	6

$$P(C1) = 0/6 = 0 \quad P(C2) = 6/6 = 1$$

$$\text{Entropy} = -0 \log 0 - 1 \log 1 = -0 - 0 = 0$$

C1	1
C2	5

$$P(C1) = 1/6 \quad P(C2) = 5/6$$

$$\text{Entropy} = -(1/6) \log_2 (1/6) - (5/6) \log_2 (1/6) = 0.65$$

C1	2
C2	4

$$P(C1) = 2/6 \quad P(C2) = 4/6$$

$$\text{Entropy} = -(2/6) \log_2 (2/6) - (4/6) \log_2 (4/6) = 0.92$$

Computing information Gain After Splitting

- Information Gain:


$$GAIN_{split} = Entropy(p) - \left(\sum_{i=1}^k \frac{n_i}{n} Entropy(i) \right)$$

Parent Node, p is split into k partitions;
 n_i is number of records in partition i

- Choose the split that achieves most reduction (maximizes GAIN)
- Used in the ID3 and C4.5 decision tree algorithms

Problems with Information Gain

- Info Gain tends to prefer splits that result in large number of partitions, each being small but pure



- Customer ID has highest information gain because entropy for all the children is zero

Gain Ratio

- Gain Ratio:

$$GainRATIO_{split} = \frac{GAIN_{split}}{SplitINFO}$$

$$SplitINFO = -\sum_{i=1}^k \frac{n_i}{n} \log \frac{n_i}{n}$$

Parent Node, p is split into k partitions

n_i is the number of records in partition i

- Adjusts Information Gain by the entropy of the partitioning (SplitINFO).
 - Higher entropy partitioning (large number of small partitions) is penalized!
- Used in C4.5 algorithm
- Designed to overcome the disadvantage of Information Gain

Measure of Impurity: Classification Error

- Classification error at a node t :

$$Error(t) = 1 - \max_i P(i | t)$$

- Maximum ($1 - 1/n_c$) when records are equally distributed among all classes, implying least interesting information
- Minimum (0) when all records belong to one class, implying most interesting information

Decision Tree Based Classification

- Advantages:
 - Inexpensive to construct
 - Extremely fast at classifying unknown records
 - Easy to interpret or small-sized trees
 - Accuracy is comparable to other classification techniques for many simple data sets