SiTech Servo Controller II — terminal legend (print at 100 %, 5.08 mm pitch)

M.E. = motor encoder S.E. = scope (axis) encoder Cut each strip and tape it just above its block. Transcribed from the panel 2026-11-08.

ALT / DEC INPUTS

+LIMIT	-LIMIT	HOME	PSYNC	AN IN	+5V	GND

10 mm check

ALT / DEC INPUTS

+LIMIT	-LIMIT	HOME	PSYNC	AN IN	+5V	GND

AZM / R.A. INPUTS

+LIMIT	-LIMIT	HOME	PSYNC	AN IN	+5V	GND

10 mm check

AZM / R.A. INPUTS

+LIMIT	-LIMIT	HOME	PSYNC	AN IN	+5V	GND

ALT / DEC MOTORS

M.E. A	M.E. B	S.E. A	S.E. B	+5V	GND	MOT +	MOT -

10 mm check

ALT / DEC MOTORS

M.E. A	M.E. B	S.E. A	S.E. B	+5V	GND	MOT +	MOT -

AZM / R.A. MOTORS

M.E. A	M.E. B	S.E. A	S.E. B	+5V	GND	MOT +	MOT -

10 mm check

AZM / R.A. MOTORS

M.E. A	M.E. B	S.E. A	S.E. B	+5V	GND	MOT +	MOT -

Top-edge jacks, left to right: GUIDE (RJ) · POWER barrel, + centre, 12–28 V (label worn; Servo I spec 11.5–28 V) · USB-B (COMM / DATA LED) · RS232 (RJ) · HAND PAD (RJ

LEDs: SLEW (red) / PAN (yellow) / GUIDE (green) at top left; MOTOR STATUS red LED under each motor block.