

**Service Information System**

Shutdown SIS

[Previous Screen](#)

Product: EXCAVATOR

Model: 320D2 L EXCAVATOR WBF

Configuration: 320D2 & 320D2 L Excavators WBF00001-UP (MACHINE) POWERED BY C7.1 Engine

Operation and Maintenance Manual**320D2 Excavator****Media Number -SEBU9247-07****Publication Date -01/09/2015****Date Updated -19/12/2017**

i06229605

Capacities (Refill)

SMCS - 1000; 7000

Table 1

Approximate Capacities (Refill)			
Component or System	Liters	US gal	Recommended Type
Cooling System	25	7	Refer to Operation and Maintenance Manual, "Lubricant Viscosities".
Fuel Tank	410	108	
Engine Crankcase with Filter	18	4.8	
Hydraulic System ⁽¹⁾	138	37	
Swing Drive	8	2	
Each Final Drive	8	2	
	kg	lbs	
Swing Gear	13.5	30	Refer to Operation and Maintenance Manual, "Lubricant Viscosities".
Refrigerant ⁽²⁾	0.9	2.0	R-134a
	mL	oz	
Refrigerant Oil ⁽²⁾	240	8.2	Polyalkylene Glycol (PAG) Oil

⁽¹⁾ The amount of hydraulic fluid that is needed to refill the hydraulic system after performing Operation and Maintenance Manual, "Hydraulic System Oil - Change"

⁽²⁾ Refer to Service Manual, "Air Conditioning and Heating R-134a for All Caterpillar Machines" for additional information

[Copyright 1993 - 2018 Caterpillar Inc.](#)

Wed Aug 1 12:37:16 UTC+0700 2018

[All Rights Reserved.](#)

[Private Network For SIS Licensees.](#)