

Python Cheatsheet

MATH60033A · Session 09 · Structural equation modelling

Thierry Warin, PhD · HEC Montréal · A2026

Everything you need to type, in one place. The first three sections are the same every week; the last one is every name from sessions 1 to 9.

Starting Python in VS Codium

Open the course folder once — **File > Open Folder**, then pick the repository. Everything below assumes you are inside it.

Open a terminal with **View > Terminal** (Ctrl + ` on Windows and Linux, Cmd + ` on macOS). Create the environment the first time only:

```
python3 -m venv .venv      # macOS
python3 -m venv .venv      # Linux
py -m venv .venv           # Windows (PowerShell)
```

Then activate it — **every time you open a new terminal**:

```
source .venv/bin/activate  # macOS
source .venv/bin/activate  # Linux
.venv\Scripts\activate     # Windows (PowerShell)
```

You will see (.venv) at the start of the prompt. If you do not, nothing below will find pandas. Install the packages once, with the environment active:

```
pip install -r requirements.txt
```

Finally tell the editor which Python to use: Ctrl/Cmd + Shift + P, type **Python: Select Interpreter**, and choose the one inside .venv.

A new file, and running it

File > New File, then save it with a .py ending — session09.py, say. Write your code, save it, and in the terminal:

```
python session09.py      # macOS, Linux and Windows alike, inside .venv
```

Inside the environment the command is **python** on all three platforms. Outside it, macOS and Linux need **python3** and Windows needs **py**, which is one more reason to activate first.

For trying one line at a time, type **python** on its own to get the >>> prompt, and **exit()** to leave. The editor's **Run** triangle does the same thing as the command above.

The four things you always do

```
import pandas as pd
```

```
# 1 - build a DataFrame
df = pd.DataFrame({"country": ["FR", "DE", "IT"],
                  "gdp_pc_eur": [37_000, 46_000, 32_000]})
```

```
# 2 - look at what is in it
df.head()      # the first five rows
df.shape       # (rows, columns)
df.dtypes      # what type each column holds
```

```

df.info()          # types, and how many values are missing
df.describe()      # count, mean, sd and quartiles, per numeric column

# 3 - read a file in
df = pd.read_csv("data.csv")
df = pd.read_excel("data.xlsx")          # needs openpyxl
df = pd.read_parquet("data/spine/core.parquet")

import qmib
df = qmib.load("core")                   # a course dataset, by name

# 4 - write a CSV out
df.to_csv("out.csv", index=False)      # index=False, or you get a stray column

```

What you have learned so far

Sessions 1 to 9, in the order you met them. Every line below has run on the course data.

Session 1 · Syllabus and Europe 2031

The workstation itself — the editor, the environment, and loading a course dataset with one line. That is section 1 above.

Session 2 · Exploratory data analysis

```

# -- Load and shape -----
core = qmib.load("core")          # a course dataset, by name
core = pd.read_parquet("data/spine/core.parquet")
d = core.dropna(subset=["gdp_pc_eur", "productivity_idx"])
# subset= matters: without it a row missing ANY column goes
both = left.merge(right, on=["geo", "time"], how="inner")
n_rows, n_cols = core.shape

# -- Describe -----
gdp.mean(), gdp.median()          # the gap between them is the finding
gdp.std(ddof=1), gdp.var(ddof=1)   # ddof=1 divides by n-1
gdp.quantile([0.25, 0.5, 0.75])    # IQR is the third minus the first
from scipy import stats
stats.trim_mean(gdp, 0.05)         # mean after cutting 5% off each tail

```

Session 3 · Regression diagnostics

```

# -- Fit -----
import statsmodels.formula.api as smf
fit = smf.ols("gdp_pc_eur ~ productivity_idx", data=d).fit()
# read the ~ as "explained by"; the intercept is added for you
fit = model.fit()                  # .fit() does the arithmetic

# -- Read the fit -----
fit.params                         # the coefficients, in units of y
fit.rsquared                       # share of variance explained
fit.resid, fit.fittedvalues        # what is left, and what was predicted
fit.rsquared_adj                   # penalised for each extra predictor
np.sqrt(fit.mse_resid)             # the RSE, in the units of y

# -- Diagnose -----

```

```

influence = fit.get_influence()      # the whole diagnostic bundle
leverage = influence.hat_matrix_diag # sums to p, always
cooks_d = influence.cooks_distance[0] # screen at 4/n
influence.resid_studentized_internal # on a common scale

# -- Choose and validate -----
fit.aic, fit.bic                      # lower is better, and only relatively

# -- Plot -----
import matplotlib.pyplot as plt
plt.scatter(d["productivity_idx"], d["gdp_pc_eur"], s=12, alpha=0.6)
plt.xlabel("Productivity index"); plt.ylabel("GDP per capita (EUR)")
# say the units, every time
plt.axhline(0, color="black", lw=1)
plt.axvline(2 * 2 / len(d), color="red", ls="--") # the 2p/n screen
plt.stem(cooks_d)                                # one spike per observation

```

Session 4 · Logistic regression

```

# -- Load and shape -----
X = pd.get_dummies(d[["grade"]], drop_first=True)

# -- Describe -----
pd.crosstab(d["grade"], d["default"])
d["default"].value_counts(normalize=True) # how unbalanced is it

# -- Fit -----
fit = smf.logit("default ~ fico + dti", data=d).fit()
from statsmodels.miscmodels.ordinal_model import OrderedModel
fit = OrderedModel(y, X, distr="logit").fit(method="bfgs")
import statsmodels.api as sm
fit = sm.MNLogit(y, sm.add_constant(X)).fit()
X = sm.add_constant(X) # the intercept, with no formula

# -- Read the fit -----
p = fit.predict(newdata) # probabilities, not classes
fit.get_prediction(newdata).summary_frame() # with an interval
np.exp(fit.params)       # a log-odds becomes an odds ratio

# -- Choose and validate -----
lr = 2 * (full.llf - reduced.llf) # the likelihood-ratio statistic
stats.chi2.sf(lr, df=2)           # its p-value

# -- Plot -----
fig, axes = plt.subplots(1, 2, figsize=(7.4, 2.9))

```

Session 5 · Regularisation

```

# -- Load and shape -----
from sklearn.preprocessing import StandardScaler
Z = StandardScaler().fit(Xtr).transform(Xtr) # fit on TRAIN only
pipe = make_pipeline(StandardScaler(), Ridge(alpha=1.0))
# so the scaler never sees the held-out fold

# -- Fit -----

```

```

Ridge(alpha=1.0).fit(Ztr, ytr)      # Lasso, ElasticNet take the same shape

# -- Read the fit -----
model.coef_, model.alpha_          # scikit-learn's spelling of .params

# -- Choose and validate -----
LassoCV(cv=5).fit(Ztr, ytr).alpha_  # lambda by cross-validation
alphas, coefs, _ = lasso_path(Z, y) # the whole coefficient path
Xtr, Xte, ytr, yte = train_test_split(X, y, test_size=0.3, random_state=7)
KFold(n_splits=5, shuffle=True, random_state=7)
mean_squared_error(yte, model.predict(Xte)) ** 0.5    # RMSE
alphas = np.logspace(-3, 2, 100)    # a grid even in log-lambda

```

Session 6 · Panel data and interactions

```

# -- Fit -----
from linearmodels.panel import PanelOLS
fit = PanelOLS.from_formula("y ~ x + EntityEffects", data=panel).fit()
RandomEffects.from_formula("y ~ 1 + x", data=panel).fit()
smf.ols("price ~ living_area + I(living_area**2)", data=d).fit()
smf.ols("wage ~ age * female", data=d).fit()
# a * b expands to a + b + a:b

# -- Choose and validate -----
big.compare_f_test(small)          # nested models only
np.linalg.pinv(v_fe - v_re)        # for the Hausman statistic

```

Session 7 · PCA and factor analysis

```

# -- Describe -----
np.linalg.eigvalsh(np.corrcoef(Z, rowvar=False))

# -- Fit -----
from sklearn.decomposition import PCA
p = PCA().fit(Z)                    # on standardised columns
import prince
famd = prince.FAMD(n_components=3).fit(mixed)    # numeric AND categorical
from statsmodels.multivariate.factor import Factor
f = Factor(df.to_numpy(), n_factor=2, method="ml").fit()

# -- Read the fit -----
p.explained_variance_ratio_        # what the scree plot is drawn from
p.components_                      # loadings: variables on components
f.rotate("varimax")                # same fit, readable loadings

```

Session 8 · KNN and bias–variance

```

# -- Fit -----
KNeighborsClassifier(n_neighbors=15).fit(Xtr, ytr)
KNeighborsRegressor(n_neighbors=15).fit(Xtr, ytr)
RandomForestClassifier(n_estimators=500, random_state=7).fit(Xtr, ytr)

# -- Diagnose -----
permutation_importance(model, Xte, yte, n_repeats=10).importances_mean
confusion_matrix(yte, model.predict(Xte))    # the four cells accuracy hides

```

```

print(classification_report(yte, model.predict(Xte)))

# -- Choose and validate -----
gs = GridSearchCV(knn, {"n_neighbors": range(1, 40)}, cv=5).fit(Xtr, ytr)
gs.best_params_, gs.best_score_ # what it chose, and how it scored
cross_val_score(model, X, y, cv=5, scoring="accuracy").mean()

```

Session 9 · Structural equation modelling

```

# -- Describe -----
np.cov(df.to_numpy(), rowvar=False) # the matrix the model reproduces

# -- Fit -----
import semopy
m = semopy.Model(desc); m.fit(df) # desc is the model description string

# -- Read the fit -----
m.inspect() # loadings and paths, estimated

# -- Choose and validate -----
semopy.calc_stats(m) # CFI, TLI, RMSEA - report all three

```