

# PROGRAM facts

U.S. DEPARTMENT OF ENERGY  
OFFICE OF FOSSIL ENERGY  
NATIONAL ENERGY TECHNOLOGY LABORATORY

Strategic Center  
for Natural Gas & Oil

06/2005



## CONTACTS

### Brad Tomer

Director  
Office of Natural Gas  
304-285-4692  
brad.tomer@netl.doe.gov

### James Ammer

Division Director  
Gas Technology Management  
Division  
304-285-4383  
james.ammer@netl.doe.gov

### Gary L. Covatch

Project Manager  
Gas Technology Management  
Division  
304-285-4589  
gary.covatch@netl.doe.gov

## COMPOSITE DRILL PIPE – BRINGING NEW LIFE TO THOUSANDS OF IDLE WELLS

Composite drill pipe (CDP) could bring new life to thousands of idle wells drilled in the early 20th century. In most oil and gas fields throughout the U.S., many zones above or below the targeted formation were bypassed because the reserves were not considered significant when the well was drilled. Using short-radius composite drill pipe to drill a horizontal well into these formations could bring many of these older wells back into production without the environmental disturbance that drilling new wells from the surface would create. Field tests during DOE's project and use of the composite pipe since then have shown that the CDP has better resistance to the extreme bending conditions placed on the drill pipe during drilling operations.

In addition to its application to short-radius drilling, CDP shows promise for enabling the economic development of oil and gas resources in other challenging locations. Because CDP combines light weight (less than ½ the weight of steel) with the performance properties of steel pipe, it is considered one of the technologies needed for resource development in extended reach, ultra deep, and deep directional drilling applications.

## Composite Pipe

Composite materials made of carbon fibers and epoxy resin could offer mechanical properties comparable to steel at less than half the weight. Pipe made from such composite materials offer superior flexibility for drilling the short radius well bores required to extend horizontal laterals at shallow depths. It could also facilitate high-speed data transfer via cables or fiber optic leads embedded within the body of the pipe during construction. As carbon composites are becoming less expensive to manufacture, the opportunity exists to develop a composite drill pipe (CDP) with some or all of these features that is cost competitive with steel. Also, because the mechanical properties of composites are well established and are a function of the types of resins and fibers used and the amount and orientation of fiber, sections of CDP can be optimized for specific applications.



A 30-ft joint of SR-CDP pipe can be easily lifted

## ADDRESS

### **National Energy Technology Laboratory**

626 Cochran's Mill Road  
P.O. Box 10940  
Pittsburgh, PA 15236-0940  
412-386-4687

3610 Collins Ferry Road  
P.O. Box 880  
Morgantown, WV 26507-0880  
304-285-4764

One West Third Street, Suite 1400  
Tulsa, OK 74103-3519  
918-699-2000

P.O. Box 750172  
539 Duckering Bldg./UAF Campus  
Fairbanks, AK 99775-0172  
907-452-2559

## CUSTOMER SERVICE

**1-800-553-7681**

## WEBSITE

**[www.netl.doe.gov](http://www.netl.doe.gov)**

## Successful Field Tests

The first test, conducted by Grand Resources, Inc. of Tulsa, OK, used the pipe to re-enter an existing vertical well that had stopped producing in 1923. Just below 1,200 feet, using 2½-inch diameter short-radius (SR)-CDP, drillers successfully kicked off a new borehole that curved into a horizontal lateral that extended 1,000 feet. SR-CDP was also used by J.B. Drilling in Leflore County, OK to drill a 60-foot radius, 1,000-foot lateral through hard and abrasive sandstone from a new natural gas well drilled to a depth of 1,385 feet. The SR-CDP was used with air-hammer drilling tools to convincingly test its fatigue life and mechanical strength. Five, 30-foot joints of SR-CDP were run for a total of more than 160,000 cycles at an average RPM of 70, air pressure of 300 psi, and torque of 1,000 lb-ft. After a week of drilling, the pipe showed little to no signs of wear.

## Commercial Orders

Torch International has placed an order for 1,000 feet of the short-radius composite drill pipe. Torch also informed ACPT that they would be placing another order for 1,000 feet in about 60 days. ACPT is working closely with Omsco, a unit of ShawCor Ltd., to determine the required extent of pilot plant upgrade and the commercial basis for building a full scale, continuous operation CDP production unit. At a future time, a full scale manufacturing plant will be installed to expand production rates and to allow production of a premium grade of CDP with even higher strength to weight ratios.



*30-ft lathe for performing finish machining with SR-CDP joint in place*