

Contents

| | | | |
|--|----|--|----|
| 1 Basic | 1 | 5.15 Berlekamp Massey | 16 |
| 1.1 vimrc | 1 | 5.16 Gauss Elimination | 16 |
| 1.2 default | 1 | 5.17 Linear Rec | 17 |
| 1.3 optimize | 1 | 5.18 Subset Conv | 17 |
| 1.4 judge | 1 | 5.19 Sqrt Mod | 17 |
| 1.5 Random | 1 | 5.20 Discrete Log | 17 |
| 1.6 Increase stack size | 1 | 5.21 Floor Sum | 17 |
| 2 Matching and Flow | 1 | 5.22 Linear Programming | 17 |
| 2.1 Dinic | 1 | 5.23 Lagrange Interpolation | 18 |
| 2.2 MCMF | 2 | 6 Geometry | 18 |
| 2.3 Hopcroft Karp | 2 | 6.1 Point | 18 |
| 2.4 KM | 2 | 6.2 Line | 18 |
| 2.5 SW | 3 | 6.3 Circle | 18 |
| 2.6 General Matching | 3 | 6.4 Point to Segment Distance | 19 |
| 3 Graph | 3 | 6.5 Point in Polygon | 19 |
| 3.1 2-SAT | 3 | 6.6 Intersection of Lines | 19 |
| 3.2 Tree | 4 | 6.7 Intersection of Circle and Line | 19 |
| 3.3 Functional Graph | 4 | 6.8 Intersection of Circles | 19 |
| 3.4 Manhattan MST | 5 | 6.9 Area of Circle and Polygon | 19 |
| 3.5 Count Cycles | 5 | 6.10 Area of Sector | 19 |
| 3.6 Maximum Clique | 5 | 6.11 Union of Polygons | 19 |
| 3.7 Min Mean Weight Cycle | 5 | 6.12 Union of Circles | 20 |
| 3.8 Block Cut Tree | 6 | 6.13 Tangent Lines of Circle and Point | 20 |
| 3.9 Dominator Tree | 6 | 6.14 Tangent Lines of Circles | 20 |
| 3.10 Matroid Intersection | 6 | 6.15 Convex Hull | 20 |
| 3.11 Generalized Series-Parallel Graph | 7 | 6.16 Convex Hull trick | 20 |
| 4 Data Structure | 7 | 6.17 Dynamic Convex Hull | 21 |
| 4.1 Lazy Segtree | 7 | 6.18 Half Plane Intersection | 21 |
| 4.2 Fenwick Tree | 8 | 6.19 Minkowski | 21 |
| 4.3 Interval Segtree | 8 | 6.20 Minimal Enclosing Circle | 21 |
| 4.4 PrefixMax Sum Segtree | 8 | 6.21 Point In Circumcircle | 21 |
| 4.5 Disjoint Set Union-undo | 8 | 6.22 Delaunay Triangulation | 21 |
| 4.6 PBDS | 9 | 6.23 Triangle Center | 22 |
| 4.7 Centroid Decomposition | 9 | 7 Stringology | 22 |
| 4.8 2D BIT | 9 | 7.1 KMP | 22 |
| 4.9 Big Binary | 9 | 7.2 Z-algorithm | 22 |
| 4.10 Big Integer | 10 | 7.3 Manacher | 22 |
| 4.11 Splay Tree | 11 | 7.4 Suffix Array Simple | 22 |
| 4.12 Link Cut Tree | 11 | 7.5 Suffix Array SAIS C++20 | 23 |
| 4.13 Static Top Tree | 12 | 7.6 Aho-Corasick | 23 |
| 5 Math | 13 | 7.7 Palindromic Tree | 23 |
| 5.1 Theorem | 13 | 7.8 Suffix Automaton | 24 |
| 5.2 Linear Sieve | 14 | 7.9 Lyndon Factorization | 24 |
| 5.3 Exgcd | 14 | 7.10 Smallest Rotation | 24 |
| 5.4 Chinese Remainder Theorem | 14 | 8 Misc | 24 |
| 5.5 Factorize | 14 | 8.1 Fraction Binary Search | 24 |
| 5.6 FloorBlock | 14 | 8.2 de Bruijn sequence | 25 |
| 5.7 FloorCeil | 14 | 8.3 Hilbert Curve | 25 |
| 5.8 NTT Prime List | 14 | 8.4 Grid Intersection | 25 |
| 5.9 NTT | 14 | 8.5 NextPerm | 25 |
| 5.10 FWT | 15 | 8.6 Python FastIO | 25 |
| 5.11 FWT | 15 | 8.7 HeapSize | 25 |
| 5.12 XOR Basis | 15 | 8.8 PyFrac | 25 |
| 5.13 Lucas | 16 | 8.9 Kotlin | 25 |
| 5.14 Min25 Sieve | 16 | | |

1 Basic

1.1 vimrc

```
set ts=4 sw=4 nu rnu et hls mouse=a
filetype indent on
sy on
imap jk <Esc>
imap {<CR> {<CR>}<C-o>0
nmap J 5j
nmap K 5k
nmap <F1> :w<bar>!g++ '%' -o run -std=c++20 -DLOCAL -
Wfatal-errors -fsanitize=address,undefined -g &&
echo done. && time ./run<CR>
```

1.2 default

```
#include <bits/stdc++.h>
using namespace std;
template<class F, class S>
ostream &operator<<(ostream &s, const pair<F, S> &v) {
    return s << "(" << v.first << ", " << v.second << ")";
};
```

```
}
template<ranges::range T> requires (!is_convertible_v<T,
    string_view>)
istream &operator>>(istream &s, T &&v) {
    for (auto &&x : v) s >> x;
    return s;
}
template<ranges::range T> requires (!is_convertible_v<T,
    string_view>)
ostream &operator<<(ostream &s, T &&v) {
    for (auto &&x : v) s << x << ' ';
    return s;
}
#ifdef LOCAL
template<class... T> void dbg(T... x) {
    char e{};
    ((cerr << e << x, e = ' '), ...);
}
#define debug(x...) dbg(#x, '=', x, '\n')
#else
#define debug(...) ((void)0)
#endif
#define all(v) (v).begin(), (v).end()
#define rall(v) (v).rbegin(), (v).rend()
#define ff first
#define ss second
template<class T> inline constexpr T inf =
    numeric_limits<T>::max() / 2;
bool chmin(auto &a, auto b) { return (b < a) and (a = b, true); }
bool chmax(auto &a, auto b) { return (a < b) and (a = b, true); }
using u32 = unsigned int;
using i64 = long long;
using u64 = unsigned long long;
using i128 = __int128;
```

1.3 optimize

```
#pragma GCC optimize("O3,unroll-loops")
#pragma GCC target("avx2,bmi,bmi2,lzcnt,popcnt")
```

1.4 judge

```
set -e
# g++ -O3 -DLOCAL -fsanitize=address,undefined -std=c++20 A.cpp -o a
g++ -O3 -DLOCAL -std=c++20 A.cpp -o a
g++ -O3 -DLOCAL -std=c++20 ac.cpp -o c

for ((i = 0; ; i++)); do
    echo "case $i"
    python3 gen.py > inp
    time ./a < inp > wa.out
    time ./c < inp > ac.out
    diff ac.out wa.out || break
done
```

1.5 Random

```
mt19937 rng(random_device{}());
i64 rand(i64 l = -lim, i64 r = lim) {
    return uniform_int_distribution<i64>(l, r)(rng);
}
double randr(double l, double r) {
    return uniform_real_distribution<double>(l, r)(rng);
}
```

1.6 Increase stack size

```
ulimit -s
```

2 Matching and Flow

2.1 Dinic

```
template<class Cap>
struct Flow {
    struct Edge { int v; Cap w; int rev; };
    vector<vector<Edge>> G;
    int n;
    Flow(int n) : n(n), G(n) {}
    void addEdge(int u, int v, Cap w) {
        G[u].push_back({v, w, (int)G[v].size()});
        G[v].push_back({u, 0, (int)G[u].size() - 1});
    }
};
```

```

vector<int> dep;
bool bfs(int s, int t) {
    dep.assign(n, 0);
    dep[s] = 1;
    queue<int> que;
    que.push(s);
    while (!que.empty()) {
        int u = que.front(); que.pop();
        for (auto [v, w, _] : G[u])
            if (!dep[v] and w) {
                dep[v] = dep[u] + 1;
                que.push(v);
            }
    }
    return dep[t] != 0;
}
Cap dfs(int u, Cap in, int t) {
    if (u == t) return in;
    Cap out = 0;
    for (auto &[v, w, rev] : G[u]) {
        if (w and dep[v] == dep[u] + 1) {
            Cap f = dfs(v, min(w, in), t);
            w -= f;
            G[v][rev].w += f;
            in -= f;
            out += f;
            if (!in) break;
        }
    }
    if (in) dep[u] = 0;
    return out;
}
Cap maxFlow(int s, int t) {
    Cap ret = 0;
    while (bfs(s, t)) {
        ret += dfs(s, inf<Cap>, t);
    }
    return ret;
}
};

```

2.2 MCMF

```

template<class T>
struct MCMF {
    struct Edge { int v; T f, w; int rev; };
    vector<vector<Edge>> G;
    const int n;
    MCMF(int n) : n(n), G(n) {}
    void addEdge(int u, int v, T f, T c) {
        G[u].push_back({v, f, c, ssize(G[v])});
        G[v].push_back({u, 0, -c, ssize(G[u]) - 1});
    }
    vector<T> dis;
    vector<bool> vis;
    bool spfa(int s, int t) {
        queue<int> que;
        dis.assign(n, inf<T>);
        vis.assign(n, false);
        que.push(s);
        vis[s] = 1;
        dis[s] = 0;
        while (!que.empty()) {
            int u = que.front(); que.pop();
            vis[u] = 0;
            for (auto [v, f, w, _] : G[u])
                if (f and chmin(dis[v], dis[u] + w))
                    if (!vis[v]) {
                        que.push(v);
                        vis[v] = 1;
                    }
        }
        return dis[t] != inf<T>;
    }
    T dfs(int u, T in, int t) {
        if (u == t) return in;
        vis[u] = 1;
        T out = 0;
        for (auto &[v, f, w, rev] : G[u])
            if (f and !vis[v] and dis[v] == dis[u] + w) {
                T x = dfs(v, min(in, f), t);
                in -= x;
                out += x;
            }
    }
};

```

```

        f -= x;
        G[v][rev].f += x;
        if (!in) break;
    }
    if (in) dis[u] = inf<T>;
    vis[u] = 0;
    return out;
}
pair<T, T> maxFlow(int s, int t) {
    T a = 0, b = 0;
    while (spfa(s, t)) {
        T x = dfs(s, inf<T>, t);
        a += x;
        b += x * dis[t];
    }
    return {a, b};
}
};

```

2.3 HopcroftKarp

```

// Complexity: O(m sqrt(n))
// edge (u \in A) -> (v \in B) : G[u].push_back(v);
struct HK {
    const int n, m;
    vector<int> l, r, a, p;
    int ans;
    HK(int n, int m) : n(n), m(m), l(n, -1), r(m, -1),
        ans{} {}
    void work(const auto &G) {
        for (bool match = true; match; ) {
            match = false;
            queue<int> q;
            a.assign(n, -1), p.assign(n, -1);
            for (int i = 0; i < n; i++)
                if (l[i] == -1) q.push(a[i] = p[i] = i);
            while (!q.empty()) {
                int z, x = q.front(); q.pop();
                if (l[a[x]] != -1) continue;
                for (int y : G[x]) {
                    if (r[y] == -1) {
                        for (z = y; z != -1; ) {
                            r[z] = x;
                            swap(l[x], z);
                            x = p[x];
                        }
                        match = true;
                        ans++;
                        break;
                    } else if (p[r[y]] == -1) {
                        q.push(z = r[y]);
                        p[z] = x;
                        a[z] = a[x];
                    }
                }
            }
        }
    }
};

```

2.4 KM

```

// max weight, for min negate the weights
template<class T>
T KM(const vector<vector<T>> &w) {
    const int n = w.size();
    vector<T> lx(n), ly(n);
    vector<int> mx(n, -1), my(n, -1), pa(n);
    auto augment = [&](int y) {
        for (int x, z; y != -1; y = z) {
            x = pa[y];
            z = mx[x];
            my[y] = x;
            mx[x] = y;
        }
    };
    auto bfs = [&](int s) {
        vector<T> sy(n, inf<T>);
        vector<bool> vx(n), vy(n);
        queue<int> q;
        q.push(s);
        while (true) {
            while (q.size()) {
                int x = q.front();

```

```

q.pop();
vx[x] = 1;
for (int y = 0; y < n; y++) {
    if (vy[y]) continue;
    T d = lx[x] + ly[y] - w[x][y];
    if (d == 0) {
        pa[y] = x;
        if (my[y] == -1) {
            augment(y);
            return;
        }
        vy[y] = 1;
        q.push(my[y]);
    } else if (chmin(sy[y], d)) {
        pa[y] = x;
    }
}
T cut = inf<T>;
for (int y = 0; y < n; y++)
    if (!vy[y])
        chmin(cut, sy[y]);
for (int j = 0; j < n; j++) {
    if (vx[j]) lx[j] -= cut;
    if (vy[j]) ly[j] += cut;
    else sy[j] -= cut;
}
for (int y = 0; y < n; y++)
    if (!vy[y] and sy[y] == 0) {
        if (my[y] == -1) {
            augment(y);
            return;
        }
        vy[y] = 1;
        q.push(my[y]);
    }
};
for (int x = 0; x < n; x++)
    lx[x] = ranges::max(w[x]);
for (int x = 0; x < n; x++)
    bfs(x);
T ans = 0;
for (int x = 0; x < n; x++)
    ans += w[x][mx[x]];
return ans;
}

```

2.5 SW

```

int w[kN][kN], g[kN], del[kN], v[kN];
void AddEdge(int x, int y, int c) {
    w[x][y] += c;
    w[y][x] += c;
}
pair<int, int> Phase(int n) {
    fill(v, v + n, 0), fill(g, g + n, 0);
    int s = -1, t = -1;
    while (true) {
        int c = -1;
        for (int i = 0; i < n; ++i) {
            if (del[i] || v[i]) continue;
            if (c == -1 || g[i] > g[c]) c = i;
        }
        if (c == -1) break;
        v[c] = 1, s = t, t = c;
        for (int i = 0; i < n; ++i) {
            if (del[i] || v[i]) continue;
            g[i] += w[c][i];
        }
    }
    return make_pair(s, t);
}
int GlobalMinCut(int n) {
    int cut = kInf;
    fill(del, 0, sizeof(del));
    for (int i = 0; i < n - 1; ++i) {
        int s, t; tie(s, t) = Phase(n);
        del[t] = 1, cut = min(cut, g[t]);
        for (int j = 0; j < n; ++j) {
            w[s][j] += w[t][j];
            w[j][s] += w[j][t];
        }
    }
}

```

```

}
return cut;
}

```

2.6 GeneralMatching

```

struct GeneralMatching { // n <= 500
    const int BLOCK = 10;
    int n;
    vector<vector<int>> > g;
    vector<int> hit, mat;
    std::priority_queue<pair<i64, int>, vector<pair<i64,
        int>>, greater<pair<i64, int>>> unmat;
    GeneralMatching(int _n) : n(_n), g(_n), mat(n, -1),
        hit(n) {}
    void add_edge(int a, int b) { // 0 <= a != b < n
        g[a].push_back(b);
        g[b].push_back(a);
    }
    int get_match() {
        for (int i = 0; i < n; i++) if (!g[i].empty()) {
            unmat.emplace(0, i);
        }
        // If WA, increase this
        // there are some cases that need >= 1.3*n^2 steps
        for BLOCK=1
        // no idea what the actual bound needed here is.
        const int MAX_STEPS = 10 + 2 * n + n * n / BLOCK / 2;
        mt19937 rng(random_device{}());
        for (int i = 0; i < MAX_STEPS; ++i) {
            if (unmat.empty()) break;
            int u = unmat.top().second;
            unmat.pop();
            if (mat[u] != -1) continue;
            for (int j = 0; j < BLOCK; j++) {
                ++hit[u];
                auto &e = g[u];
                const int v = e[rng() % e.size()];
                mat[u] = v;
                swap(u, mat[v]);
                if (u == -1) break;
            }
            if (u != -1) {
                mat[u] = -1;
                unmat.emplace(hit[u] * 100ULL / (g[u].size() + 1), u);
            }
        }
        int siz = 0;
        for (auto e : mat) siz += (e != -1);
        return siz / 2;
    }
};

```

3 Graph

3.1 2-SAT

```

struct TwoSat {
    int n;
    vector<vector<int>> G;
    vector<bool> ans;
    vector<int> id, dfn, low, stk;
    TwoSat(int n) : n(n), G(2 * n), ans(n),
        id(2 * n, -1), dfn(2 * n, -1), low(2 * n, -1) {}
    void addClause(int u, bool f, int v, bool g) { // (u = f) or (v = g)
        G[2 * u + !f].push_back(2 * v + g);
        G[2 * v + !g].push_back(2 * u + f);
    }
    void addImply(int u, bool f, int v, bool g) { // (u = f) -> (v = g)
        G[2 * u + f].push_back(2 * v + g);
        G[2 * v + !g].push_back(2 * u + !f);
    }
    int cur = 0, scc = 0;
    void dfs(int u) {
        stk.push_back(u);
        dfn[u] = low[u] = cur++;
        for (int v : G[u]) {
            if (dfn[v] == -1) {
                dfs(v);
            }
        }
    }
}

```

```

    chmin(low[u], low[v]);
} else if (id[v] == -1) {
    chmin(low[u], dfn[v]);
}
}
if (dfn[u] == low[u]) {
    int x;
    do {
        x = stk.back();
        stk.pop_back();
        id[x] = scc;
    } while (x != u);
    scc++;
}
}
bool satisfiable() {
    for (int i = 0; i < n * 2; i++)
        if (dfn[i] == -1) {
            dfs(i);
        }
    for (int i = 0; i < n; ++i) {
        if (id[2 * i] == id[2 * i + 1]) {
            return false;
        }
        ans[i] = id[2 * i] > id[2 * i + 1];
    }
    return true;
}
};

```

3.2 Tree

```

struct Tree {
    int n, lgN;
    vector<vector<int>> G;
    vector<vector<int>> st;
    vector<int> in, out, dep, pa, seq;
    Tree(int n) : n(n), G(n), in(n), out(n), dep(n), pa(n, -1) {}
    int cmp(int a, int b) {
        return dep[a] < dep[b] ? a : b;
    }
    void dfs(int u) {
        erase(G[u], pa[u]);
        in[u] = seq.size();
        seq.push_back(u);
        for (int v : G[u]) {
            dep[v] = dep[u] + 1;
            pa[v] = u;
            dfs(v);
        }
        out[u] = seq.size();
    }
    void build() {
        seq.reserve(n);
        dfs(0);
        lgN = __lg(n);
        st.assign(lgN + 1, vector<int>(n));
        st[0] = seq;
        for (int i = 0; i < lgN; i++)
            for (int j = 0; j + (2 << i) <= n; j++)
                st[i + 1][j] = cmp(st[i][j], st[i][j + (1 << i)]);
    }
    int inside(int x, int y) {
        return in[x] <= in[y] and in[y] < out[x];
    }
    int lca(int x, int y) {
        if (x == y) return x;
        if ((x = in[x] + 1) > (y = in[y] + 1))
            swap(x, y);
        int h = __lg(y - x);
        return pa[cmp(st[h][x], st[h][y - (1 << h)])];
    }
    int dist(int x, int y) {
        return dep[x] + dep[y] - 2 * dep[lca(x, y)];
    }
    int rootPar(int r, int x) {
        if (r == x) return -1;
        if (!inside(x, r)) return pa[x];
        return *--upper_bound(all(G[x]), r, [&](int a, int b) -> bool {
            return in[a] < in[b];
        });
    }
};

```

```

    });
}
int size(int x) { return out[x] - in[x]; }
int rootSiz(int r, int x) {
    if (r == x) return n;
    if (!inside(x, r)) return size(x);
    return n - size(rootPar(r, x));
}
int rootLca(int a, int b, int c) {
    return lca(a, b) ^ lca(b, c) ^ lca(c, a);
}
vector<int> virTree(vector<int> ver) {
    sort(all(ver), [&](int a, int b) {
        return in[a] < in[b];
    });
    for (int i = ver.size() - 1; i > 0; i--)
        ver.push_back(lca(ver[i], ver[i - 1]));
    sort(all(ver), [&](int a, int b) {
        return in[a] < in[b];
    });
    ver.erase(unique(all(ver)), ver.end());
    return ver;
}
void inplace_virTree(vector<int> &ver) { // 0(n),
    need sort before
    vector<int> ex;
    for (int i = 0; i + 1 < ver.size(); i++)
        if (!inside(ver[i], ver[i + 1]))
            ex.push_back(lca(ver[i], ver[i + 1]));
    vector<int> stk, pa(ex.size(), -1);
    for (int i = 0; i < ex.size(); i++) {
        int lst = -1;
        while (stk.size() and in[ex[stk.back()]] >= in[ex[i]]) {
            lst = stk.back();
            stk.pop_back();
        }
        if (lst != -1) pa[lst] = i;
        if (stk.size()) pa[i] = stk.back();
        stk.push_back(i);
    }
    vector<bool> vis(ex.size());
    auto dfs = [&](auto self, int u) -> void {
        vis[u] = 1;
        if (pa[u] != -1 and !vis[pa[u]])
            self(self, pa[u]);
        if (ex[u] != ver.back())
            ver.push_back(ex[u]);
    };
    const int s = ver.size();
    for (int i = 0; i < ex.size(); i++)
        if (!vis[i]) dfs(dfs, i);
    inplace_merge(ver.begin(), ver.begin() + s, ver.end(),
        [&](int a, int b) { return in[a] < in[b]; });
    ver.erase(unique(all(ver)), ver.end());
}
};

```

3.3 Functional Graph

```

// bel[x]: x is belong bel[x]-th jellyfish
// len[x]: cycle length of x-th jellyfish
// ord[x]: order of x in cycle (x == root[x])
struct FunctionalGraph {
    int n, _t = 0;
    vector<vector<int>> G;
    vector<int> f, bel, dep, ord, root, in, out, len;
    FunctionalGraph(int n) : n(n), G(n), root(n),
        bel(n, -1), dep(n), ord(n), in(n), out(n) {}
    void dfs(int u) {
        in[u] = _t++;
        for (int v : G[u]) if (bel[v] == -1) {
            dep[v] = dep[u] + 1;
            root[v] = root[u];
            bel[v] = bel[u];
            dfs(v);
        }
        out[u] = _t;
    };
    void build(const auto &f) {
        f = _f;
        for (int i = 0; i < n; i++) {

```

```

    G[f[i]].push_back(i);
}
vector<int> vis(n, -1);
for (int i = 0; i < n; i++) if (vis[i] == -1) {
    int x = i;
    while (vis[x] == -1) {
        vis[x] = i;
        x = f[x];
    }
    if (vis[x] != i) continue;
    int s = x, l = 0;
    do {
        bel[x] = len.size();
        ord[x] = l++;
        root[x] = x;
        x = f[x];
    } while (x != s);
    len.push_back(l);
}
for (int i = 0; i < n; i++)
    if (root[i] == i) {
        dfs(i);
    }
}
int dist(int x, int y) { // x -> y
    if (bel[x] != bel[y]) {
        return -1;
    }
    else if (dep[x] < dep[y]) {
        return -1;
    }
    else if (dep[y] != 0) {
        if (in[y] <= in[x] and in[x] < out[y]) {
            return dep[x] - dep[y];
        }
        return -1;
    }
    else {
        return dep[x] + (ord[y] - ord[root[x]]) + len[bel[x]] % len[bel[y]];
    }
}
};

```

3.4 Manhattan MST

```

// {w, u, v}
vector<tuple<int, int, int>> ManhattanMST(vector<Pt> P)
{
    vector<int> id(P.size());
    iota(all(id), 0);
    vector<tuple<int, int, int>> edg;
    for (int k = 0; k < 4; k++) {
        sort(all(id), [&](int i, int j) {
            return (P[i] - P[j]).ff < (P[j] - P[i]).ss;
        });
        map<int, int> sweep;
        for (int i : id) {
            auto it = sweep.lower_bound(-P[i].ss);
            while (it != sweep.end()) {
                int j = it->ss;
                Pt d = P[i] - P[j];
                if (d.ss > d.ff) {
                    break;
                }
                edg.emplace_back(d.ff + d.ss, i, j);
                it = sweep.erase(it);
            }
            sweep[-P[i].ss] = i;
        }
        for (Pt &p : P) {
            if (k % 2) {
                p.ff = -p.ff;
            }
            else {
                swap(p.ff, p.ss);
            }
        }
    }
    return edg;
}

```

3.5 Count Cycles

```

// ord = sort by deg decreasing, rk[ord[i]] = i
// D[i] = edge point from rk small to rk big
for (int x : ord) { // c3
    for (int y : D[x]) vis[y] = 1;
}

```

```

for (int y : D[x]) for (int z : D[y]) c3 += vis[z];
for (int y : D[x]) vis[y] = 0;
}
for (int x : ord) { // c4
    for (int y : D[x]) for (int z : adj[y])
        if (rk[z] > rk[x]) c4 += vis[z]++;
    for (int y : D[x]) for (int z : adj[y])
        if (rk[z] > rk[x]) --vis[z];
} // both are O(M*sqrt(M)), test @ 2022 CCPC guangzhou

```

3.6 Maximum Clique

```

constexpr size_t kN = 150;
using bits = bitset<kN>;
struct MaxClique {
    bits G[kN], cs[kN];
    int ans, sol[kN], q, cur[kN], d[kN], n;
    void init(int _n) {
        n = _n;
        for (int i = 0; i < n; ++i) G[i].reset();
    }
    void addEdge(int u, int v) {
        G[u][v] = G[v][u] = 1;
    }
    void preDfs(vector<int> &v, int i, bits mask) {
        if (i < 4) {
            for (int x : v) d[x] = (G[x] & mask).count();
            sort(all(v), [&](int x, int y) {
                return d[x] > d[y];
            });
        }
        vector<int> c(v.size());
        cs[1].reset(), cs[2].reset();
        int l = max(ans - q + 1, 1), r = 2, tp = 0, k;
        for (int p : v) {
            for (k = 1;
                (cs[k] & G[p]).any(); ++k);
            if (k >= r) cs[++r].reset();
            cs[k][p] = 1;
            if (k < l) v[tp++] = p;
        }
        for (k = l; k < r; ++k)
            for (auto p = cs[k]._Find_first(); p < kN; p = cs[k]._Find_next(p))
                v[tp] = p, c[tp] = k, ++tp;
        dfs(v, c, i + 1, mask);
    }
    void dfs(vector<int> &v, vector<int> &c, int i, bits mask) {
        while (!v.empty()) {
            int p = v.back();
            v.pop_back();
            mask[p] = 0;
            if (q + c.back() <= ans) return;
            cur[q++] = p;
            vector<int> nr;
            for (int x : v)
                if (G[p][x]) nr.push_back(x);
            if (!nr.empty()) preDfs(nr, i, mask & G[p]);
            else if (q > ans) ans = q, copy_n(cur, q, sol);
            c.pop_back();
            --q;
        }
    }
    int solve() {
        vector<int> v(n);
        iota(all(v), 0);
        ans = q = 0;
        preDfs(v, 0, bits(string(n, '1')));
        return ans;
    }
} cliq;

```

3.7 Min Mean Weight Cycle

```

// d[i][j] == 0 if {i,j} !in E
long long d[1003][1003], dp[1003][1003];

```

```

pair<long long, long long> MMWC() {
    memset(dp, 0x3f, sizeof(dp));
    for (int i = 1; i <= n; ++i) dp[0][i] = 0;
    for (int i = 1; i <= n; ++i) {
        for (int j = 1; j <= n; ++j) {
            for (int k = 1; k <= n; ++k) {

```

```

    dp[i][k] = min(dp[i - 1][j] + d[j][k], dp[i][k]);
}
}
}
long long au = 1ll << 31, ad = 1;
for (int i = 1; i <= n; ++i) {
    if (dp[n][i] == 0x3f3f3f3f3f3f3f3f) continue;
    long long u = 0, d = 1;
    for (int j = n - 1; j >= 0; --j) {
        if ((dp[n][i] - dp[j][i]) * d > u * (n - j)) {
            u = dp[n][i] - dp[j][i];
            d = n - j;
        }
    }
    if (u * ad < au * d) au = u, ad = d;
}
long long g = __gcd(au, ad);
return make_pair(au / g, ad / g);
}

```

3.8 Block Cut Tree

```

struct BlockCutTree {
    int n;
    vector<vector<int>> adj;
    BlockCutTree(int _n) : n(_n), adj(_n) {}
    void addEdge(int u, int v) {
        adj[u].push_back(v);
        adj[v].push_back(u);
    }
    pair<int, vector<pair<int, int>>> work() {
        vector<int> dfn(n, -1), low(n), stk;
        vector<pair<int, int>> edg;
        int cnt = 0, cur = 0;
        function<void(int)> dfs = [&](int x) {
            stk.push_back(x);
            dfn[x] = low[x] = cur++;
            for (auto y : adj[x]) {
                if (dfn[y] == -1) {
                    dfs(y);
                    low[x] = min(low[x], low[y]);
                    if (low[y] == dfn[x]) {
                        int v;
                        do {
                            v = stk.back();
                            stk.pop_back();
                            edg.emplace_back(n + cnt, v);
                        } while (v != y);
                        edg.emplace_back(x, n + cnt);
                        cnt++;
                    }
                } else {
                    low[x] = min(low[x], dfn[y]);
                }
            }
        };
        for (int i = 0; i < n; i++) {
            if (dfn[i] == -1) {
                stk.clear();
                dfs(i);
            }
        }
        return {cnt, edg};
    }
};

```

3.9 Dominator Tree

```

struct Dominator {
    vector<vector<int>> g, r, rdom; int tk;
    vector<int> dfn, rev, fa, sdom, dom, val, rp;
    int n;
    Dominator(int n) : n(n), g(n), r(n), rdom(n), tk(0),
        dfn(n, -1), rev(n, -1), fa(n, -1), sdom(n, -1),
        dom(n, -1), val(n, -1), rp(n, -1) {}
    void add_edge(int x, int y) { g[x].push_back(y); }
    void dfs(int x) {
        rev[dfn[x]] = tk;
        fa[tk] = sdom[tk] = val[tk] = tk; tk++;
        for (int u : g[x]) {
            if (dfn[u] == -1) dfs(u), rp[dfn[u]] = dfn[x];
            r[dfn[u]].push_back(dfnd[x]);
        }
    }
};

```

```

void merge(int x, int y) { fa[x] = y; }
int find(int x, int c = 0) {
    if (fa[x] == x) return c ? -1 : x;
    if (int p = find(fa[x], 1); p != -1) {
        if (sdom[val[x]] > sdom[val[fa[x]]])
            val[x] = val[fa[x]];
        fa[x] = p;
        return c ? p : val[x];
    }
    return c ? fa[x] : val[x];
}
vector<int> build(int s) {
    // return the father of each node in dominator tree
    // p[i] = -2 if i is unreachable from s
    dfs(s);
    for (int i = tk - 1; i >= 0; --i) {
        for (int u : r[i])
            sdom[i] = min(sdom[i], sdom[find(u)]);
        if (i) rdom[sdom[i]].push_back(i);
        for (int u : rdom[i]) {
            int p = find(u);
            dom[u] = (sdom[p] == i ? i : p);
        }
        if (i) merge(i, rp[i]);
    }
    vector<int> p(n, -2); p[s] = -1;
    for (int i = 1; i < tk; ++i)
        if (sdom[i] != dom[i]) dom[i] = dom[dom[i]];
    for (int i = 1; i < tk; ++i)
        p[rev[i]] = rev[dom[i]];
    return p;
}
};

```

3.10 Matroid Intersection

```

template<class Matroid1, class Matroid2>
vector<bool> MatroidIntersection(Matroid1 &m1, Matroid2
    &m2) {
    const int N = m1.size();
    vector<bool> I(N);
    while (true) {
        m1.set(I);
        m2.set(I);
        vector<vector<int>> E(N + 2);
        const int s = N, t = N + 1;
        for (int i = 0; i < N; i++) {
            if (I[i]) { continue; }
            auto c1 = m1.circuit(i);
            auto c2 = m2.circuit(i);
            if (c1.empty()) {
                E[s].push_back(i);
            } else {
                for (int y : c1) if (y != i) {
                    E[y].push_back(i);
                }
            }
            if (c2.empty()) {
                E[i].push_back(t);
            } else {
                for (int y : c2) if (y != i) {
                    E[i].push_back(y);
                }
            }
        }
        vector<int> pre(N + 2, -1);
        queue<int> que;
        que.push(s);
        while (que.size() and pre[t] == -1) {
            int u = que.front();
            que.pop();
            for (int v : E[u]) {
                if (pre[v] == -1) {
                    pre[v] = u;
                    que.push(v);
                }
            }
        }
        if (pre[t] == -1) { break; }
        for (int p = pre[t]; p != s; p = pre[p]) {
            I[p] = !I[p];
        }
    }
};

```



```

return I;
}

```

3.11 Generalized Series-Parallel Graph

```

/* Vertex: {u, -1}
 * Edge: {u, v}; u < v
 * Series: (e1, v1, e2) => e3; e1 < e2
 * Parallel: (e1, e2) => e3; e1 = e2
 * Dangling: (v1, e1, v2) => v3; e1 = {v1, v2}
 */
struct GSPGraph {
    int N;
    vector<pair<int, int>> S;
    vector<vector<int>> tree;
    vector<bool> isrt;
    int getv(int e, int u) { return S[e].ff ^ S[e].ss ^ u; }
    int newNode(pair<int, int> s, vector<int> sub) {
        S[N] = s, tree[N] = sub;
        for (int x : sub) isrt[x] = false;
        return N++;
    }
    GSPGraph(int n, const vector<pair<int, int>> &edge) {
        N = edge.size();
        S = edge;
        S.resize(N * 2 + n, {-1, -1});
        tree.resize(N * 2 + n);
        isrt.assign(N * 2 + n, true);
        vector<vector<int>> G(n);
        vector<int> vid(n, deg(n));
        unordered_map<pair<int, int>, int> eid;
        queue<int> que;
        auto add = [&](int e) {
            auto [u, v] = S[e];
            if (auto it = eid.find(S[e]); it != eid.end()) {
                it->ss = e = newNode(S[e], {e, it->ss});
                if (--deg[u] == 2) que.push(u);
                if (--deg[v] == 2) que.push(v);
            } else eid[S[e]] = e;
            G[u].push_back(e);
            G[v].push_back(e);
        };
        for (int i = N - 1; i >= 0; i--) {
            S[i] = minmax({S[i].ff, S[i].ss});
            add(i);
        }
        for (int i = 0; i < n; i++) {
            S[vid[i] = N++] = {i, -1};
            deg[i] += ssize(G[i]);
            if (deg[i] <= 2) que.push(i);
        }
        auto pop = [&](int x) {
            while (!isrt[G[x].back()]) G[x].pop_back();
            int e = G[x].back();
            isrt[e] = false;
            return e;
        };
        while (que.size()) {
            int u = que.front(); que.pop();
            if (deg[u] == 1) {
                int e = pop(u), v = getv(e, u);
                vid[v] = newNode(
                    {v, -1}, {vid[S[e].ff], e, vid[S[e].ss]}
                );
                if (--deg[v] == 2) que.push(v);
            } else if (deg[u] == 2) {
                int e1 = pop(u), e2 = pop(u);
                if (S[e1] > S[e2]) swap(e1, e2);
                add(newNode(
                    minmax(getv(e1, u), getv(e2, u)),
                    {e1, vid[u], e2}
                ));
            }
        }
        S.resize(N);
        tree.resize(N);
        isrt.resize(N);
    }
};

```

4 Data Structure

4.1 Lazy Segtree

```

template<class S, class T>
struct Seg {
    Seg *ls{}, *rs{};
    S sum{};
    T tag{};
    int l, r;
    Seg(int _l, int _r) : l(_l), r(_r) {
        if (r - l == 1) {
            return;
        }
        int m = (l + r) / 2;
        ls = new Seg(l, m);
        rs = new Seg(m, r);
        pull();
    }
    void pull() {
        sum = ls->sum + rs->sum;
    }
    void push() {
        ls->apply(tag);
        rs->apply(tag);
        tag = T{};
    }
    void apply(const T &f) {
        f(tag);
        f(sum);
    }
    S query(int x, int y) {
        if (y <= l or r <= x) {
            return {};
        }
        if (x <= l and r <= y) {
            return sum;
        }
        push();
        return ls->query(x, y) + rs->query(x, y);
    }
    void apply(int x, int y, const T &f) {
        if (y <= l or r <= x) {
            return;
        }
        if (x <= l and r <= y) {
            apply(f);
            return;
        }
        push();
        ls->apply(x, y, f);
        rs->apply(x, y, f);
        pull();
    }
    void set(int p, const S &e) {
        if (p < l or p >= r) {
            return;
        }
        if (r - l == 1) {
            sum = e;
            return;
        }
        push();
        ls->set(p, e);
        rs->set(p, e);
        pull();
    }
    pair<int, S> findFirst(int x, int y, auto &&pred, S
        cur = {}) {
        if (y <= l or r <= x) {
            return {-1, cur};
        }
        if (x <= l and r <= y and !pred(cur + sum)) {
            return {-1, cur + sum};
        }
        if (r - l == 1) {
            return {l, cur + sum};
        }
        push();
        auto L = ls->findFirst(x, y, pred, cur);
        if (L.ff != -1) {
            return L;
        }
    }
};

```

```

    return rs->findFirst(x, y, pred, L.ss);
}
pair<int, S> findLast(int x, int y, auto &&pred, S
    cur = {}) {
    if (y <= l or r <= x) {
        return {-1, cur};
    }
    if (x <= l and r <= y and !pred(sum + cur)) {
        return {-1, sum + cur};
    }
    if (r - l == 1) {
        return {l, sum + cur};
    }
    push();
    auto R = rs->findLast(x, y, pred, cur);
    if (R.ff != -1) {
        return R;
    }
    return ls->findLast(x, y, pred, R.ss);
}
};

```

4.2 Fenwick Tree

```

template<class T>
struct Fenwick {
    int n;
    vector<T> a;
    Fenwick(int _n) : n(_n), a(_n) {}
    int lob(int x) { return x & -x; }
    void add(int p, T x) {
        assert(p < n);
        for (int i = p + 1; i <= n; i += lob(i)) {
            a[i - 1] = a[i - 1] + x;
        }
    }
    T sum(int p) { // sum [0, p]
        T s{};
        for (int i = min(p, n) + 1; i > 0; i -= lob(i)) {
            s = s + a[i - 1];
        }
        return s;
    }
    int findFirst(auto &&pred) { // min{ k | pred(k) }
        T s{};
        int p = 0;
        for (int i = 1 << __lg(n); i; i >>= 1) {
            if (p + i <= n and !pred(s + a[p + i - 1])) {
                p += i;
                s = s + a[p - 1];
            }
        }
        return p == n ? -1 : p;
    }
};

```

4.3 Interval Segtree

```

struct Seg {
    Seg *ls, *rs;
    int l, r;
    vector<int> f, g;
    // f : intervals where covering [l, r]
    // g : intervals where interset with [l, r]
    Seg(int _l, int _r) : l{_l}, r{_r} {
        int mid = (l + r) >> 1;
        if (r - l == 1) return;
        ls = new Seg(l, mid);
        rs = new Seg(mid, r);
    }
    void insert(int x, int y, int id) {
        if (y <= l or r <= x) return;
        g.push_back(id);
        if (x <= l and r <= y) {
            f.push_back(id);
            return;
        }
        ls->insert(x, y, id);
        rs->insert(x, y, id);
    }
    void fix() {
        while (!f.empty() and use[f.back()]) f.pop_back();
        while (!g.empty() and use[g.back()]) g.pop_back();
    }
};

```

```

int query(int x, int y) {
    if (y <= l or r <= x) return -1;
    fix();
    if (x <= l and r <= y) {
        return g.empty() ? -1 : g.back();
    }
    return max({f.empty() ? -1 : f.back(), ls->query(x,
        y), rs->query(x, y)});
}
};

```

4.4 PrefixMax Sum Segtree

```

// O(Nlog^2N)!
const int kC = 1E6;
struct Seg {
    static Seg pool[kC], *top;
    Seg *ls{}, *rs{};
    int l, r;
    i64 sum = 0, rsum = 0, mx = 0;
    Seg() {}
    Seg(int _l, int _r, const vector<i64> &v) : l(_l), r(
        _r) {
        if (r - l == 1) {
            sum = mx = v[l];
            return;
        }
        int m = (l + r) / 2;
        ls = new (top++) Seg(l, m, v);
        rs = new (top++) Seg(m, r, v);
        pull();
    }
    i64 cal(i64 h) { // sigma i in [l, r) max(h, v[i])
        if (r - l == 1) {
            return max(mx, h);
        }
        if (mx <= h) {
            return h * (r - l);
        }
        if (ls->mx >= h) {
            return ls->cal(h) + rsum;
        }
        return h * (ls->r - ls->l) + rs->cal(h);
    }
    void pull() {
        rsum = rs->cal(ls->mx);
        sum = ls->sum + rsum;
        mx = max(ls->mx, rs->mx);
    }
    void set(int p, i64 h) {
        if (r - l == 1) {
            sum = mx = h;
            return;
        }
        int m = (l + r) / 2;
        if (p < m) {
            ls->set(p, h);
        } else {
            rs->set(p, h);
        }
        pull();
    }
    i64 query(int p, i64 h) { // sigma i in [0, p) max(h,
        v[i])
        if (p <= l) {
            return 0;
        }
        if (p >= r) {
            return cal(h);
        }
        return ls->query(p, h) + rs->query(p, max(h, ls->mx
            ));
    }
}; Seg::pool[kC], *Seg::top = Seg::pool;

```

4.5 Disjoint Set Union-undo

```

template<class T>
struct DSU {
    vector<T> tag;
    vector<int> f, siz, stk;
    int cc;
    DSU(int n) : f(n, -1), siz(n, 1), tag(n), cc(n) {}
    int find(int x) { return f[x] < 0 ? x : find(f[x]); }
};

```



```

bool merge(int x, int y) {
    x = find(x);
    y = find(y);
    if (x == y) return false;
    if (siz[x] > siz[y]) swap(x, y);
    f[x] = y;
    siz[y] += siz[x];
    tag[x] = tag[x] - tag[y];
    stk.push_back(x);
    cc--;
    return true;
}

void apply(int x, T s) {
    x = find(x);
    tag[x] = tag[x] + s;
}

void undo() {
    int x = stk.back();
    int y = f[x];
    stk.pop_back();
    tag[x] = tag[x] + tag[y];
    siz[y] -= siz[x];
    f[x] = -1;
    cc++;
}

bool same(int x, int y) { return find(x) == find(y); }

int size(int x) { return siz[find(x)]; }
};

```

4.6 PBDS

```

#include <bits/extc++.h>
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
#include <ext/pb_ds/hash_policy.hpp>
#include <ext/pb_ds/priority_queue.hpp>
using namespace __gnu_pbds;
template<class T>
using BST = tree<T, null_type, less<T>, rb_tree_tag,
    tree_order_statistics_node_update>;
// __gnu_pbds::priority_queue<node, decltype(cmp),
//     pairing_heap_tag> pq(cmp);
// gp_hash_table<int, gnu_pbds::priority_queue<node>::
//     point_iterator> pqPos;
// bst.insert((x << 20) + i);
// bst.erase(bst.lower_bound(x << 20));
// bst.order_of_key(x << 20) + 1;
// *bst.find_by_order(x - 1) >> 20;
// *--bst.lower_bound(x << 20) >> 20;
// *bst.upper_bound((x + 1) << 20) >> 20;

```

4.7 Centroid Decomposition

```

struct CenDec {
    vector<vector<pair<int, i64>>> G;
    vector<vector<i64>> pdis;
    vector<int> pa, ord, siz;
    vector<bool> vis;
    int getsiz(int u, int f) {
        siz[u] = 1;
        for (auto [v, w] : G[u]) if (v != f and !vis[v])
            siz[u] += getsiz(v, u);
        return siz[u];
    }
    int find(int u, int f, int s) {
        for (auto [v, w] : G[u]) if (v != f and !vis[v])
            if (siz[v] * 2 >= s) return find(v, u, s);
        return u;
    }
    void caldis(int u, int f, i64 dis) {
        pdis[u].push_back(dis);
        for (auto [v, w] : G[u]) if (v != f and !vis[v]) {
            caldis(v, u, dis + w);
        }
    }
    int build(int u = 0) {
        u = find(u, u, getsiz(u, u));
        ord.push_back(u);
        vis[u] = 1;
        for (auto [v, w] : G[u]) if (!vis[v]) {
            pa[build(v)] = u;
        }
        caldis(u, -1, 0); // if need
    }
};

```

```

vis[u] = 0;
return u;
};
CenDec(int n) : G(n), pa(n, -1), vis(n), siz(n), pdis
(n) {}
};

```

4.8 2D BIT

```

template<class T>
struct BIT2D {
    vector<vector<T>> val;
    vector<vector<int>> Y;
    vector<int> X;
    int lowbit(int x) { return x & -x; }
    int getp(const vector<int> &v, int x) {
        return upper_bound(all(v), x) - v.begin();
    }
    BIT2D(vector<pair<int, int>> pos) {
        for (auto &[x, y] : pos) {
            X.push_back(x);
            swap(x, y);
        }
        sort(all(pos));
        sort(all(X));
        X.erase(unique(all(X)), X.end());
        Y.resize(X.size() + 1);
        val.resize(X.size() + 1);
        for (auto [y, x] : pos) {
            for (int i = getp(X, x); i <= X.size(); i +=
                lowbit(i))
                if (Y[i].empty() or Y[i].back() != y)
                    Y[i].push_back(y);
        }
        for (int i = 1; i <= X.size(); i++) {
            val[i].assign(Y[i].size() + 1, T{});
        }
    }
    void add(int x, int y, T v) {
        for (int i = getp(X, x); i <= X.size(); i += lowbit
            (i))
            for (int j = getp(Y[i], y); j <= Y[i].size(); j
                += lowbit(j))
                val[i][j] += v;
    }
    T qry(int x, int y) {
        T r{};
        for (int i = getp(X, x); i > 0; i -= lowbit(i))
            for (int j = getp(Y[i], y); j > 0; j -= lowbit(j))
                r += val[i][j];
        return r;
    }
};

```

4.9 Big Binary

```

struct BigBinary : map<int, int> {
    void split(int x) {
        auto it = lower_bound(x);
        if (it != begin()) {
            it--;
            if (it->ss > x) {
                (*this)[x] = it->ss;
                it->ss = x;
            }
        }
    }
    void add(int x) {
        split(x);
        auto it = find(x);
        while (it != end() and it->ff == x) {
            x = it->ss;
            it = erase(it);
        }
        (*this)[x] = x + 1;
    }
    void sub(int x) {
        split(x);
        auto it = lower_bound(x);
        // assert(it != end());
        auto [l, r] = *it;
        erase(it);
    }
};

```

```

    if (l + 1 < r) {
        (*this)[l + 1] = r;
    }
    if (x < l) {
        (*this)[x] = l;
    }
}
};

```

4.10 Big Integer

// 暴力乘法，只能做到 10^5 位數
 // 只加減不做乘法 Base 可到 $1E18$

```

struct uBig {
    static const i64 Base = 1E15;
    static const i64 Log = 15;
    vector<i64> d;
    uBig() : d{0} {}
    uBig(i64 x) {
        d = {x % Base};
        if (x >= Base) {
            d.push_back(x / Base);
        }
        fix();
    }
    uBig(string_view s) {
        i64 c = 0, pw = 1;
        for (int i = s.size() - 1; i >= 0; i--) {
            c += pw * (s[i] - '0');
            pw *= 10;
            if (pw == Base or i == 0) {
                d.push_back(c);
                c = 0;
                pw = 1;
            }
        }
    }
    void fix() {
        i64 c = 0;
        for (int i = 0; i < d.size(); i++) {
            d[i] += c;
            c = (d[i] < 0 ? (d[i] - 1 - Base) / Base : d[i] / Base);
            d[i] -= c * Base;
        }
        while (c) {
            d.push_back(c % Base);
            c /= Base;
        }
        while (d.size() >= 2 and d.back() == 0) {
            d.pop_back();
        }
    }
    bool isZero() const {
        return d.size() == 1 and d[0] == 0;
    }
    uBig &operator+=(const uBig &rhs) {
        if (d.size() < rhs.d.size()) {
            d.resize(rhs.d.size());
        }
        for (int i = 0; i < rhs.d.size(); i++) {
            d[i] += rhs.d[i];
        }
        fix();
        return *this;
    }
    uBig &operator-=(const uBig &rhs) {
        if (d.size() < rhs.d.size()) {
            d.resize(rhs.d.size());
        }
        for (int i = 0; i < rhs.d.size(); i++) {
            d[i] -= rhs.d[i];
        }
        fix();
        return *this;
    }
    friend uBig operator*(const uBig &lhs, const uBig &rhs) {
        const int a = lhs.d.size(), b = rhs.d.size();
        uBig res(0);
        res.d.resize(a + b);
        for (int i = 0; i < a; i++) {
            for (int j = 0; j < b; j++) {

```

```

                i128 x = (i128)lhs.d[i] * rhs.d[j];
                res.d[i + j] += x % Base;
                res.d[i + j + 1] += x / Base;
            }
        }
        res.fix();
        return res;
    };
    friend uBig &operator+(uBig lhs, const uBig &rhs) {
        return lhs += rhs;
    }
    friend uBig &operator-(uBig lhs, const uBig &rhs) {
        return lhs -= rhs;
    }
    uBig &operator*=(const uBig &rhs) {
        return *this = *this * rhs;
    }
    friend int cmp(const uBig &lhs, const uBig &rhs) {
        if (lhs.d.size() != rhs.d.size()) {
            return lhs.d.size() < rhs.d.size() ? -1 : 1;
        }
        for (int i = lhs.d.size() - 1; i >= 0; i--) {
            if (lhs.d[i] != rhs.d[i]) {
                return lhs.d[i] < rhs.d[i] ? -1 : 1;
            }
        }
        return 0;
    }
    friend ostream &operator<<(ostream &os, const uBig &rhs) {
        os << rhs.d.back();
        for (int i = ssize(rhs.d) - 2; i >= 0; i--) {
            os << setfill('0') << setw(Log) << rhs.d[i];
        }
        return os;
    }
    friend istream &operator>>(istream &is, uBig &rhs) {
        string s;
        is >> s;
        rhs = uBig(s);
        return is;
    }
};

struct sBig : uBig {
    bool neg{false};
    sBig() : uBig() {}
    sBig(i64 x) : uBig(abs(x)), neg(x < 0) {}
    sBig(string_view s) : uBig(s[0] == '-' ? s.substr(1) : s), neg(s[0] == '-') {}
    sBig(const uBig &x) : uBig(x) {}
    sBig operator-() const {
        if (isZero()) {
            return *this;
        }
        sBig res = *this;
        res.neg ^= 1;
        return res;
    }
    sBig &operator+=(const sBig &rhs) {
        if (rhs.isZero()) {
            return *this;
        }
        if (neg == rhs.neg) {
            uBig::operator+=(rhs);
        } else {
            int s = cmp(*this, rhs);
            if (s == 0) {
                *this = {};
            } else if (s == 1) {
                uBig::operator-=(rhs);
            } else {
                uBig tmp = rhs;
                tmp -= static_cast<uBig>(*this);
                *this = tmp;
                neg = rhs.neg;
            }
        }
        return *this;
    }
    sBig &operator-=(const sBig &rhs) {
        neg ^= 1;

```

```

    *this += rhs;
    neg ^= 1;
    if (isZero()) {
        neg = false;
    }
    return *this;
}
sBig &operator*=(const sBig &rhs) {
    if (isZero() or rhs.isZero()) {
        return *this = {};
    }
    neg ^= rhs.neg;
    uBig::operator*=(rhs);
    return *this;
}
friend sBig operator+(sBig lhs, const sBig &rhs) {
    return lhs += rhs;
}
friend sBig &operator-(sBig lhs, const sBig &rhs) {
    return lhs -= rhs;
}
friend sBig operator*(sBig lhs, const sBig &rhs) {
    return lhs *= rhs;
}
friend ostream &operator<<(ostream &os, const sBig &
    rhs) {
    if (rhs.neg) {
        os << '-';
    }
    return os << static_cast<uBig>(rhs);
}
friend istream &operator>>(istream &is, sBig &rhs) {
    string s;
    is >> s;
    rhs = sBig(s);
    return is;
}
};

```

4.11 Splay Tree

```

struct Node {
    Node *ch[2]{}; *p{};
    Info info{}; sum{};
    Tag tag{};
    int size{};
    bool rev{};
} pool[int(1E5 + 10)], *top = pool;
Node *newNode(Info a) {
    Node *t = top++;
    t->info = t->sum = a;
    t->size = 1;
    return t;
}
int size(const Node *x) { return x ? x->size : 0; }
Info get(const Node *x) { return x ? x->sum : Info{}; }
int dir(const Node *x) { return x->p->ch[1] == x; }
bool nroot(const Node *x) { return x->p and x->p->ch[
    dir(x)] == x; }
void reverse(Node *x) { if (x) x->rev = !x->rev; }
void update(Node *x, const Tag &f) {
    if (!x) return;
    f(x->tag);
    f(x->info);
    f(x->sum);
}
void push(Node *x) {
    if (x->rev) {
        swap(x->ch[0], x->ch[1]);
        reverse(x->ch[0]);
        reverse(x->ch[1]);
        x->rev = false;
    }
    update(x->ch[0], x->tag);
    update(x->ch[1], x->tag);
    x->tag = Tag{};
}
void pull(Node *x) {
    x->size = size(x->ch[0]) + 1 + size(x->ch[1]);
    x->sum = get(x->ch[0]) + x->info + get(x->ch[1]);
}
void rotate(Node *x) {
    Node *y = x->p, *z = y->p;

```

```

    push(y);
    int d = dir(x);
    push(x);
    Node *w = x->ch[d ^ 1];
    if (nroot(y)) {
        z->ch[dir(y)] = x;
    }
    if (w) {
        w->p = y;
    }
    (x->ch[d ^ 1] = y)->ch[d] = w;
    (y->p = x)->p = z;
    pull(y);
    pull(x);
}
void splay(Node *x) {
    while (nroot(x)) {
        Node *y = x->p;
        if (nroot(y)) {
            rotate(dir(x) == dir(y) ? y : x);
        }
        rotate(x);
    }
}
Node *nth(Node *x, int k) {
    assert(size(x) > k);
    while (true) {
        push(x);
        int left = size(x->ch[0]);
        if (left > k) {
            x = x->ch[0];
        } else if (left < k) {
            k -= left + 1;
            x = x->ch[1];
        } else {
            break;
        }
    }
    splay(x);
    return x;
}
Node *split(Node *x) {
    assert(x);
    push(x);
    Node *l = x->ch[0];
    if (l) l->p = x->ch[0] = nullptr;
    pull(x);
    return l;
}
Node *join(Node *x, Node *y) {
    if (!x or !y) return x ? x : y;
    y = nth(y, 0);
    push(y);
    y->ch[0] = x;
    if (x) x->p = y;
    pull(y);
    return y;
}
Node *find_first(Node *x, auto &&pred) {
    Info pre{};
    while (true) {
        push(x);
        if (pred(pre + get(x->ch[0]))) {
            x = x->ch[0];
        } else if (pred(pre + get(x->ch[0]) + x->info) or !
            x->ch[1]) {
            break;
        } else {
            pre = pre + get(x->ch[0]) + x->info;
            x = x->ch[1];
        }
    }
    splay(x);
    return x;
}

```

4.12 Link Cut Tree

```

namespace lct {
Node *access(Node *x) {
    Node *last = {};
    while (x) {
        splay(x);

```

```

    push(x);
    x->ch[0] = last;
    pull(x);
    last = x;
    x = x->p;
}
return last;
}
void make_root(Node *x) {
    access(x);
    splay(x);
    reverse(x);
}
Node *find_root(Node *x) {
    push(x = access(x));
    while (x->ch[1]) {
        push(x = x->ch[1]);
    }
    splay(x);
    return x;
}
bool link(Node *x, Node *y) {
    if (find_root(x) == find_root(y)) {
        return false;
    }
    make_root(x);
    x->p = y;
    return true;
}
bool cut(Node *a, Node *b) {
    make_root(a);
    access(b);
    splay(a);
    if (a->ch[0] == b) {
        split(a);
        return true;
    }
    return false;
}
Info query(Node *a, Node *b) {
    make_root(b);
    return get(access(a));
}
void set(Node *x, Info v) {
    splay(x);
    push(x);
    x->info = v;
    pull(x);
}
}

```

4.13 Static Top Tree

```

template<class Vertex, class Path>
struct StaticTopTree {
    enum Type { Rake, Compress, Combine, Convert };
    int stt_root;
    vector<vector<int>> &G;
    vector<int> P, L, R, S;
    vector<Type> T;
    vector<Vertex> f;
    vector<Path> g;
    int buf;
    int dfs(int u) {
        int s = 1, big = 0;
        for (int &v : G[u]) {
            erase(G[v], u);
            int t = dfs(v);
            s += t;
            if (chmax(big, t)) swap(G[u][0], v);
        }
        return s;
    }
    int add(int l, int r, Type t) {
        int x = buf++;
        P[x] = -1, L[x] = l, R[x] = r, T[x] = t;
        if (l != -1) P[l] = x, S[x] += S[l];
        if (r != -1) P[r] = x, S[x] += S[r];
        return x;
    }
    int merge(auto l, auto r, Type t) {
        if (r - l == 1) return *l;
        int s = 0;
        for (auto i = l; i != r; i++) s += S[*i];
    }
}

```

```

    auto m = l;
    while (s > S[*m]) s -= 2 * S[*m++];
    return add(merge(l, m, t), merge(m, r, t), t);
}
int pathCluster(int u) {
    vector<int> chs{pointCluster(u)};
    while (!G[u].empty()) chs.push_back(pointCluster(u
= G[u][0]));
    return merge(all(chs), Type::Compress);
}
int pointCluster(int u) {
    vector<int> chs;
    for (int v : G[u] | views::drop(1))
        chs.push_back(add(pathCluster(v), -1, Type::
Convert));
    if (chs.empty()) return add(u, -1, Type::Convert);
    return add(u, merge(all(chs), Type::Rake), Type::
Combine);
}
StaticTopTree(vector<vector<int>> &G, int root = 0)
: G(G) {
    const int n = G.size();
    P.assign(4 * n, -1);
    L.assign(4 * n, -1);
    R.assign(4 * n, -1);
    S.assign(4 * n, 1);
    T.assign(4 * n, Type::Rake);
    buf = n;
    dfs(root);
    stt_root = pathCluster(root);
    f.resize(buf);
    g.resize(buf);
}
void update(int x) {
    if (T[x] == Rake) f[x] = f[L[x]] * f[R[x]];
    else if (T[x] == Compress) g[x] = g[L[x]] + g[R[x
]];
    else if (T[x] == Combine) g[x] = f[L[x]] + f[R[x]];
    else if (T[L[x]] == Rake) g[x] = Path(f[L[x]]);
    else f[x] = Vertex(g[L[x]]);
}
void set(int x, const Vertex &v) {
    f[x] = v;
    for (x = P[x]; x != -1; x = P[x])
        update(x);
}
Vertex get() { return g[stt_root]; }
};
struct Path;
struct Vertex {
    Vertex() {}
    Vertex(const Path &);
};
struct Path {
    Path() {}
    Path(const Vertex &);
};
Vertex operator*(const Vertex &a, const Vertex &b) {
    return {};
}
Path operator+(const Vertex &a, const Vertex &b) {
    return {};
}
Path operator+(const Path &a, const Path &b) {
    return {};
}
Vertex::Vertex(const Path &x) {}
Path::Path(const Vertex &x) {}
/*
* (root) 1 - 2 (heavy)
*   /\ \
*  3 4 5
* type V: subtree DP info (Commutative Semigroup)
* type P: path DP info (Semigroup)
* V(2) + V(5) -> P(2)
* V(1) + (V(3) * V(4)) -> P(1)
* ans: V(P(1) + P(2))
*/

```

5 Math

5.1 Theorem

- Pick's Theorem

$$A = i + \frac{b}{2} - 1$$

A : Area, i : grid number in the inner, b : grid number on the side

- Matrix-Tree theorem

undirected graph

$$D_{ii}(G) = \deg(i), D_{ij} = 0, i \neq j$$

$$A_{ij}(G) = A_{ji}(G) = \#e(i, j), i \neq j$$

$$L(G) = D(G) - A(G)$$

$$t(G) = \det L(G)_{(1,2,\dots,i-1,i+1,\dots,n)}$$

leaf to root

$$D_{ii}^{out}(G) = \deg^{out}(i), D_{ij}^{out} = 0, i \neq j$$

$$A_{ij}(G) = \#e(i, j), i \neq j$$

$$L^{out}(G) = D^{out}(G) - A(G)$$

$$t^{root}(G, k) = \det L^{out}(G)_{(1,2,\dots,k-1,k+1,\dots,n)}$$

root to leaf

$$L^{in}(G) = D^{in}(G) - A(G)$$

$$t^{leaf}(G, k) = \det L^{in}(G)_{(1,2,\dots,k-1,k+1,\dots,n)}$$

- Derangement

$$D_n = (n-1)(D_{n-1} + D_{n-2}) = nD_{n-1} + (-1)^n$$

- Möbius Inversion

$$f(n) = \sum_{d|n} g(d) \Leftrightarrow g(n) = \sum_{d|n} \mu\left(\frac{n}{d}\right) f(d)$$

- Euler Inversion

$$\sum_{i|n} \varphi(i) = n$$

- Binomial Inversion

$$f(n) = \sum_{i=0}^n \binom{n}{i} g(i) \Leftrightarrow g(n) = \sum_{i=0}^n (-1)^{n-i} \binom{n}{i} f(i)$$

- Subset Inversion

$$f(S) = \sum_{T \subseteq S} g(T) \Leftrightarrow g(S) = \sum_{T \subseteq S} (-1)^{|S|-|T|} f(T)$$

- Min-Max Inversion

$$\max_{i \in S} x_i = \sum_{T \subseteq S} (-1)^{|T|-1} \min_{j \in T} x_j$$

- Ex Min-Max Inversion

$$\text{kthmax}_{i \in S} x_i = \sum_{T \subseteq S} (-1)^{|T|-k} \binom{|T|-1}{k-1} \min_{j \in T} x_j$$

- Lcm-Gcd Inversion

$$\text{lcm}_{i \in S} x_i = \prod_{T \subseteq S} (\gcd_{j \in T} x_j)^{(-1)^{|T|-1}}$$

- Sum of powers

$$\sum_{k=1}^n k^m = \frac{1}{m+1} \sum_{k=0}^m \binom{m+1}{k} B_k^+ n^{m+1-k}$$

$$\sum_{j=0}^m \binom{m+1}{j} B_j^- = 0$$

$$\text{note: } B_1^+ = -B_1^-, B_i^+ = B_i^-$$

- Cayley's formula

number of trees on n labeled vertices: n^{n-2}

Let $T_{n,k}$ be the number of labelled forests on n vertices with k connected components, such that vertices $1, 2, \dots, k$ all belong to different connected components. Then $T_{n,k} = kn^{n-k-1}$.

- High order residue

$$\left[d^{\frac{p-1}{n(p-1)}} \equiv 1 \right]$$

- Packing and Covering

$$|\text{maximum independent set}| + |\text{minimum vertex cover}| = |V|$$

- König's theorem

$$|\text{maximum matching}| = |\text{minimum vertex cover}|$$

- Dilworth's theorem

$$\text{width} = |\text{largest antichain}| = |\text{smallest chain decomposition}|$$

- Mirsky's theorem

$$\text{height} = |\text{longest chain}| = |\text{smallest antichain decomposition}| = |\text{minimum antichain partition}|$$

- Lucas' Theorem

For $n, m \in \mathbb{Z}^*$ and prime P , $\binom{m}{n} \pmod{P} = \prod \binom{m_i}{n_i}$ where m_i is the i -th digit of m in base P .

- Stirling approximation

$$n! \approx \sqrt{2\pi n} \left(\frac{n}{e}\right)^n e^{\frac{1}{12n}}$$

- 1st Stirling Numbers(permutation $|P| = n$ with k cycles)

$$S(n, k) = \text{coefficient of } x^k \text{ in } \prod_{i=0}^{n-1} (x+i)$$

$$S(n+1, k) = nS(n, k) + S(n, k-1)$$

- 2nd Stirling Numbers(Partition n elements into k non-empty set)

$$S(n, k) = \frac{1}{k!} \sum_{j=0}^k (-1)^{k-j} \binom{k}{j} j^n$$

$$S(n+1, k) = kS(n, k) + S(n, k-1)$$

- Catalan number

$$C_n = \frac{1}{n+1} \binom{2n}{n} = \binom{2n}{n} - \binom{2n}{n-1}$$

$$\binom{n+m}{n} - \binom{n+m}{n+1} = (m+n)! \frac{n-m+1}{n+1} \quad \text{for } n \geq m$$

$$C_n = \frac{1}{n+1} \binom{2n}{n} = \frac{(2n)!}{(n+1)n!}$$

$$C_0 = 1 \quad \text{and} \quad C_{n+1} = 2 \left(\frac{2n+1}{n+2} \right) C_n$$

$$C_0 = 1 \quad \text{and} \quad C_{n+1} = \sum_{i=0}^n C_i C_{n-i} \quad \text{for } n \geq 0$$

- Extended Catalan number

$$\frac{1}{(k-1)n+1} \binom{kn}{n}$$

- Calculate $c[i-j]+ = a[i] \times b[j]$ for $a[n], b[m]$

1. $a = \text{reverse}(a)$; $c = \text{mul}(a, b)$; $c = \text{reverse}(c[1:n])$;

2. $b = \text{reverse}(b)$; $c = \text{mul}(a, b)$; $c = \text{rshift}(c, m-1)$;

- Eulerian number (permutation $1 \sim n$ with m $a[i] > a[i-1]$)

$$A(n, m) = \sum_{i=0}^m (-1)^i \binom{n+1}{i} (m+1-i)^n$$

$$A(n, m) = (n-m)A(n-1, m-1) + (m+1)A(n-1, m)$$

- Hall's theorem

Let $G = (X+Y, E)$ be a bipartite graph. For $W \subseteq X$, let $N(W) \subseteq Y$ denotes the adjacent vertices set of W . Then, G has a X' -perfect matching (matching contains $X' \subseteq X$) iff $\forall W \subseteq X', |W| \leq |N(W)|$.

- Tutte Matrix:

For a graph $G = (V, E)$, its maximum matching = $\frac{\text{rank}(A)}{2}$ where

$A_{ij} = ((i, j) \in E ? (i < j ? x_{ij} : -x_{ji}) : 0)$ and x_{ij} are random numbers.

- Erdős-Gallai theorem

There exists a simple graph with degree sequence $d_1 \geq \dots \geq d_n$ iff

$$\sum_{i=1}^n d_i \text{ is even and } \sum_{i=1}^k d_i \leq k(k-1) + \sum_{i=k+1}^n \min(d_i, k), \forall 1 \leq k \leq n$$

- Euler Characteristic

planar graph: $V - E + F - C = 1$

convex polyhedron: $V - E + F = 2$

V, E, F, C : number of vertices, edges, faces(regions), and components

- Burnside Lemma

$$|X/G| = \frac{1}{|G|} \sum_{g \in G} |X^g|$$

- Polya theorem

$$|Y^x/G| = \frac{1}{|G|} \sum_{g \in G} m^{c(g)}$$

$m = |Y|$: num of colors, $c(g)$: num of cycle

- Cayley's Formula

Given a degree sequence d_1, \dots, d_n of a labeled tree, there are $\frac{(n-2)!}{(d_1-1) \dots (d_n-1)!}$ spanning trees.

- Find a Primitive Root of n :

n has primitive roots iff $n = 2, 4, p^k, 2p^k$ where p is an odd prime.

1. Find $\phi(n)$ and all prime factors of $\phi(n)$, says $P = \{p_1, \dots, p_m\}$

2. $\forall g \in [2, n]$, if $g^{\frac{\phi(n)}{p_i}} \neq 1, \forall p_i \in P$, then g is a primitive root.

3. Since the smallest one isn't too big, the algorithm runs fast.

4. n has exactly $\phi(\phi(n))$ primitive roots.

- Taylor series

$$f(x) = f(c) + f'(c)(x-c) + \frac{f''(c)}{2!}(x-c)^2 + \frac{f^{(3)}(c)}{3!}(x-c)^3 + \dots$$

- Lagrange Multiplier

$\min f(x, y)$, subject to $g(x, y) = 0$

$$\frac{\partial f}{\partial x} + \lambda \frac{\partial g}{\partial x} = 0$$

$$\frac{\partial f}{\partial y} + \lambda \frac{\partial g}{\partial y} = 0$$

$$g(x, y) = 0$$

- Calculate $f(x+n)$ where $f(x) = \sum_{i=0}^{n-1} a_i x^i$

$$f(x+n) = \sum_{i=0}^{n-1} a_i (x+n)^i = \sum_{i=0}^{n-1} x^i \cdot \frac{1}{i!} \sum_{j=i}^{n-1} \frac{a_j}{j!} \cdot \frac{n^{j-i}}{(j-i)!}$$

- Bell 數 (有 n 個人, 把他們拆組的方法總數)

$$B_0 = 1$$

$$B_n = \sum_{k=0}^n s(n, k) \quad (\text{second - stirling})$$

$$B_{n+1} = \sum_{k=0}^n \binom{n}{k} B_k$$

- Wilson's theorem

$$(p-1)! \equiv -1 \pmod{p}$$

$$(p^q!)_p \equiv \begin{cases} 1, & (p=2) \wedge (q \geq 3), \\ -1, & \text{otherwise.} \end{cases} \pmod{p^q}$$

- Fermat's little theorem

$$a^p \equiv a \pmod{p}$$

- Euler's theorem

$$a^b \equiv \begin{cases} a^{b \bmod \varphi(m)}, & \gcd(a, m) = 1, \\ a^b, & \gcd(a, m) \neq 1, b < \varphi(m), \\ a^{(b \bmod \varphi(m)) + \varphi(m)}, & \gcd(a, m) \neq 1, b \geq \varphi(m). \end{cases} \pmod{m}$$

- 環狀著色 (相鄰塗異色)

$$(k-1)(-1)^n + (k-1)^n$$

5.2 Linear Sieve

```
vector<int> primes, minp;
vector<int> mu, phi;
vector<bool> isp;
void Sieve(int n) {
    minp.assign(n + 1, 0);
    primes.clear();
    isp.assign(n + 1, 0);
    mu.resize(n + 1);
    phi.resize(n + 1);
    mu[1] = 1;
    phi[1] = 1;
    for (int i = 2; i <= n; i++) {
        if (minp[i] == 0) {
            minp[i] = i;
            isp[i] = 1;
            primes.push_back(i);
            mu[i] = -1;
            phi[i] = i - 1;
        }
        for (i64 p : primes) {
            if (p * i > n) {
                break;
            }
            minp[i * p] = p;
            if (p == minp[i]) {
                phi[p * i] = phi[i] * p;
                break;
            }
            phi[p * i] = phi[i] * (p - 1);
            mu[p * i] = mu[p] * mu[i];
        }
    }
}
```

5.3 Exgcd

```
// ax + by = gcd(a, b)
i64 exgcd(i64 a, i64 b, i64 &x, i64 &y) {
    if (b == 0) {
        x = 1, y = 0;
        return a;
    }
    i64 g = exgcd(b, a % b, y, x);
    y -= a / b * x;
    return g;
}
```

5.4 Chinese Remainder Theorem

```
// O(NlogC)
// E = {(m, r), ...}: x mod m_i = r_i
// return {M, R} x mod M = R
// return {-1, -1} if no solution
pair<i64, i64> CRT(vector<pair<i64, i64>> E) {
    i128 R = 0, M = 1;
    for (auto [m, r] : E) {
        i64 g, x, y, d;
        g = exgcd(M, m, x, y);
        d = r - R;
        if (d % g != 0) {
            return {-1, -1};
        }
        R += d / g * M * x;
        M = M * m / g;
        R = (R % M + M) % M;
    }
    return {M, R};
}
```

5.5 Factorize

```
u64 mul(u64 a, u64 b, u64 M) {
    i64 r = a * b - M * u64(1.L / M * a * b);
    return r + M * ((r < 0) - (r >= (i64)M));
}
u64 power(u64 a, u64 b, u64 M) {
    u64 r = 1;
    for (; b; b /= 2, a = mul(a, a, M))
        if (b & 1) r = mul(r, a, M);
    return r;
}
bool isPrime(u64 n) {
    if (n < 2 or n % 6 % 4 != 1) return (n | 1) == 3;
```

```
auto magic = {2, 325, 9375, 28178, 450775, 9780504,
1795265022};
u64 s = __builtin_ctzll(n - 1), d = n >> s;
for (u64 x : magic) {
    u64 p = power(x % n, d, n), i = s;
    while (p != 1 and p != n - 1 and x % n && i--)
        p = mul(p, p, n);
    if (p != n - 1 and i != s) return 0;
}
return 1;
}
u64 pollard(u64 n) {
    u64 c = 1;
    auto f = [&](u64 x) { return mul(x, x, n) + c; };
    u64 x = 0, y = 0, p = 2, q, t = 0;
    while (t++ % 128 or gcd(p, n) == 1) {
        if (x == y) c++, y = f(x = 2);
        if (q = mul(p, x > y ? x - y : y - x, n)) p = q;
        x = f(x); y = f(f(y));
    }
    return gcd(p, n);
}
u64 primeFactor(u64 n) {
    return isPrime(n) ? n : primeFactor(pollard(n));
}
```

5.6 FloorBlock

```
vector<i64> floorBlock(i64 x) { // x >= 0
    vector<i64> itv;
    for (i64 l = 1, r; l <= x; l = r) {
        r = x / (x / l) + 1;
        itv.push_back(l);
    }
    itv.push_back(x + 1);
    return itv;
}
```

5.7 FloorCeil

```
i64 ifloor(i64 a, i64 b) {
    if (b < 0) a = -a, b = -b;
    if (a < 0) return (a - b + 1) / b;
    return a / b;
}
i64 iceil(i64 a, i64 b) {
    if (b < 0) a = -a, b = -b;
    if (a > 0) return (a + b - 1) / b;
    return a / b;
}
```

5.8 NTT Prime List

| Prime | Root | Prime | Root |
|---------------------|------|---------------------|------|
| 7681 | 17 | 167772161 | 3 |
| 12289 | 11 | 104857601 | 3 |
| 40961 | 3 | 985661441 | 3 |
| 65537 | 3 | 998244353 | 3 |
| 786433 | 10 | 1107296257 | 10 |
| 5767169 | 3 | 2013265921 | 31 |
| 7340033 | 3 | 2810183681 | 11 |
| 23068673 | 3 | 2885681153 | 3 |
| 469762049 | 3 | 605028353 | 3 |
| 2748779069441 | 3 | 6597069766657 | 5 |
| 39582418599937 | 5 | 79164837199873 | 5 |
| 1231453023109121 | 3 | 1337006139375617 | 3 |
| 4179340454199820289 | 3 | 1945555039024054273 | 3 |
| 9223372036737335297 | 3 | | |

5.9 NTT

```
template<i64 M, i64 root>
struct NTT {
    static const int Log = 21;
    array<i64, Log + 1> e{}, ie{};
    NTT() {
        static_assert(__builtin_ctz(M - 1) >= Log);
        e[Log] = power(root, (M - 1) >> Log, M);
        ie[Log] = power(e[Log], M - 2, M);
        for (int i = Log - 1; i >= 0; i--) {
            e[i] = e[i + 1] * e[i + 1] % M;
            ie[i] = ie[i + 1] * ie[i + 1] % M;
        }
    }
    void operator()(vector<i64> &v, bool inv) {
        int n = v.size();
        for (int i = 0, j = 0; i < n; i++) {
```



```

    if (i < j) swap(v[i], v[j]);
    for (int k = n / 2; (j ^= k) < k; k /= 2);
}
for (int m = 1; m < n; m *= 2) {
    i64 w = (inv ? ie : e)[_lg(m) + 1];
    for (int i = 0; i < n; i += m * 2) {
        i64 cur = 1;
        for (int j = i; j < i + m; j++) {
            i64 g = v[j], t = cur * v[j + m] % M;
            v[j] = (g + t) % M;
            v[j + m] = (g - t + M) % M;
            cur = cur * w % M;
        }
    }
}
if (inv) {
    i64 in = power(n, M - 2, M);
    for (int i = 0; i < n; i++) v[i] = v[i] * in % M;
}
};
template<int M, int G>
vector<i64> convolution(vector<i64> f, vector<i64> g) {
    static NTT<M, G> ntt;
    int n = ssize(f) + ssize(g) - 1;
    int len = bit_ceil(1ull * n);
    f.resize(len);
    g.resize(len);
    ntt(f, 0), ntt(g, 0);
    for (int i = 0; i < len; i++) {
        (f[i] *= g[i]) %= M;
    }
    ntt(f, 1);
    f.resize(n);
    return f;
}
vector<i64> inv(vector<i64> f) {
    const int n = f.size();
    int k = 1;
    vector<i64> g{inv(f[0])}, t;
    for (i64 &x : f) {
        x = (mod - x) % mod;
    }
    t.reserve(n);
    while (k < n) {
        k = min(k * 2, n);
        g.resize(k);
        t.assign(f.begin(), f.begin() + k);
        auto h = g * t;
        h.resize(k);
        (h[0] += 2) %= mod;
        g = g * h;
        g.resize(k);
    }
    g.resize(n);
    return g;
}
// CRT
vector<i64> convolution_ll(const vector<i64> &f, const
vector<i64> &g) {
    constexpr i64 M1 = 998244353, G1 = 3;
    constexpr i64 M2 = 985661441, G2 = 3;
    constexpr i64 M1M2 = M1 * M2;
    constexpr i64 M1m1 = M2 * power(M2, M1 - 2, M1);
    constexpr i64 M2m2 = M1 * power(M1, M2 - 2, M2);
    auto c1 = convolution<M1, G1>(f, g);
    auto c2 = convolution<M2, G2>(f, g);
    for (int i = 0; i < c1.size(); i++) {
        c1[i] = ((i128)c1[i] * M1m1 + (i128)c2[i] * M2m2) %
M1M2;
    }
    return c1;
}
// 2D convolution
vector<vector<i64>> operator*(vector<vector<i64>> f,
vector<vector<i64>> g) {
    const int n = f.size() + g.size() - 1;
    const int m = f[0].size() + g[0].size() - 1;
    int len = bit_ceil(1ull * max(n, m));
    f.resize(len);
    g.resize(len);
    for (auto &v : f) {

```

```

        v.resize(len);
        ntt(v, 0);
    }
    for (auto &v : g) {
        v.resize(len);
        ntt(v, 0);
    }
    for (int i = 0; i < len; i++)
        for (int j = 0; j < i; j++) {
            swap(f[i][j], f[j][i]);
            swap(g[i][j], g[j][i]);
        }
    for (int i = 0; i < len; i++) {
        ntt(f[i], 0);
        ntt(g[i], 0);
    }
    for (int i = 0; i < len; i++)
        for (int j = 0; j < len; j++) {
            f[i][j] = mul(f[i][j], g[i][j]);
        }
    for (int i = 0; i < len; i++) {
        ntt(f[i], 1);
    }
    for (int i = 0; i < len; i++)
        for (int j = 0; j < i; j++) {
            swap(f[i][j], f[j][i]);
        }
    for (auto &v : f) {
        ntt(v, 1);
        v.resize(m);
    }
    f.resize(n);
    return f;
}

```

5.10 FWT

1. XOR Convolution

- $f(A) = (f(A_0) + f(A_1), f(A_0) - f(A_1))$
- $f^{-1}(A) = (f^{-1}(\frac{A_0 + A_1}{2}), f^{-1}(\frac{A_0 - A_1}{2}))$

2. OR Convolution

- $f(A) = (f(A_0), f(A_0) + f(A_1))$
- $f^{-1}(A) = (f^{-1}(A_0), f^{-1}(A_1) - f^{-1}(A_0))$

3. AND Convolution

- $f(A) = (f(A_0) + f(A_1), f(A_1))$
- $f^{-1}(A) = (f^{-1}(A_0) - f^{-1}(A_1), f^{-1}(A_1))$

5.11 FWT

```

void ORop(i64 &x, i64 &y) { y = (y + x) % mod; }
void ORinv(i64 &x, i64 &y) { y = (y - x + mod) % mod; }

void ANDop(i64 &x, i64 &y) { x = (x + y) % mod; }
void ANDinv(i64 &x, i64 &y) { x = (x - y + mod) % mod; }

void XORop(i64 &x, i64 &y) { tie(x, y) = pair{(x + y) %
mod, (x - y + mod) % mod}; }
void XORinv(i64 &x, i64 &y) { tie(x, y) = pair{(x + y)
* inv2 % mod, (x - y + mod) * inv2 % mod}; }

void FWT(vector<i64> &f, auto &op) {
    const int s = f.size();
    for (int i = 1; i < s; i *= 2)
        for (int j = 0; j < s; j += i * 2)
            for (int k = 0; k < i; k++)
                op(f[j + k], f[i + j + k]);
}
// FWT(f, XORop), FWT(g, XORop)
// f[i] *= g[i]
// FWT(f, XORinv)

```

5.12 Xor Basis

```

struct Basis {
    array<int, kD> bas{}; tim{};
    void insert(int x, int t) {
        for (int i = kD - 1; i >= 0; i--)
            if (x >> i & 1) {
                if (!bas[i]) {
                    bas[i] = x;
                    tim[i] = t;
                    return;
                }
            }
    }
};

```

```

    }
    if (t > tim[i]) {
        swap(x, bas[i]);
        swap(t, tim[i]);
    }
    x ^= bas[i];
}
}
bool query(int x) {
    for (int i = kD - 1; i >= 0; i--)
        chmin(x, x ^ bas[i]);
    return x == 0;
}
};

```

5.13 Lucas

```

// comb(n, m) % M, M = p^k
// O(M)-O(log(n))
struct Lucas {
    const i64 p, M;
    vector<i64> f;
    Lucas(int p, int M) : p(p), M(M), f(M + 1) {
        f[0] = 1;
        for (int i = 1; i <= M; i++) {
            f[i] = f[i - 1] * (i % p == 0 ? 1 : i) % M;
        }
    }
    i64 CountFact(i64 n) {
        i64 c = 0;
        while (n) c += (n /= p);
        return c;
    }
    // (n! without factor p) % p^k
    i64 ModFact(i64 n) {
        i64 r = 1;
        while (n) {
            r = r * power(f[M], n / M % 2, M) % M * f[n % M] % M;
            n /= p;
        }
        return r;
    }
    i64 ModComb(i64 n, i64 m) {
        if (m < 0 or n < m) return 0;
        i64 c = CountFact(n) - CountFact(m) - CountFact(n - m);
        i64 r = ModFact(n) * power(ModFact(m), M / p * (p - 1) - 1, M) % M
            * power(ModFact(n - m), M / p * (p - 1) - 1, M) % M;
        return r * power(p, c, M) % M;
    }
};

```

5.14 Min25 Sieve

```

// Prefix Sums of Multiplicative Functions
// O(N^0.75 / log N)
// calc f(1) + ... + f(N)
// where f is multiplicative function
// construct completely multiplicative functions
// g_i s.t. for all prime x, f(x) = sigma c_i * g_i(x)
// def gsum(x) = g(1) + ... + g(x)
// call apply(g_i, gsum_i, c_i) and call work(f)
struct Min25 {
    const i64 N, sqrtN;
    vector<i64> Q;
    vector<i64> Fp, S;
    int id(i64 x) { return x <= sqrtN ? Q.size() - x : N / x - 1; }
    Min25(i64 N) : N(N), sqrtN(isqrt(N)) {
        // sieve(sqrtN);
        for (i64 l = 1, r; l <= N; l = r + 1) {
            Q.push_back(N / l);
            r = N / (N / l);
        }
        Fp.assign(Q.size(), 0);
        S.assign(Q.size(), 0);
    }
    void apply(const auto &f, const auto &fsum, i64 coef) {
        vector<i64> F(Q.size());
        for (int i = 0; i < Q.size(); i++) {

```

```

            F[i] = fsum(Q[i]) - 1;
        }
        for (i64 p : primes) {
            auto t = F[id(p - 1)];
            for (int i = 0; i < Q.size(); i++) {
                if (Q[i] < p * p) {
                    break;
                }
                F[i] -= (F[id(Q[i] / p)] - t) * f(p);
            }
            for (int i = 0; i < Q.size(); i++) {
                Fp[i] += F[i] * coef;
            }
        }
    }
    i64 work(const auto &f) {
        S = Fp;
        for (i64 p : primes | views::reverse) {
            i64 t = Fp[id(p)];
            for (int i = 0; i < Q.size(); i++) {
                if (Q[i] < p * p) {
                    break;
                }
                for (i64 pw = p; pw * p <= Q[i]; pw *= p) {
                    S[i] += (S[id(Q[i] / pw)] - t) * f(p, pw);
                    S[i] += f(p, pw * p);
                }
            }
            for (int i = 0; i < Q.size(); i++) {
                S[i]++;
            }
            return S[0];
        }
    }
};

```

5.15 Berlekamp Massey

```

template<int P>
vector<int> BerlekampMassey(vector<int> x) {
    vector<int> cur, ls;
    int lf = 0, ld = 0;
    for (int i = 0; i < (int)x.size(); ++i) {
        int t = 0;
        for (int j = 0; j < (int)cur.size(); ++j)
            t += 1LL * cur[j] * x[i - j - 1] % P;
        if (t == x[i]) continue;
        if (cur.empty()) {
            cur.resize(i + 1);
            lf = i, ld = (t + P - x[i]) % P;
            continue;
        }
        int k = 1LL * fpow(ld, P - 2, P) * (t + P - x[i]) % P;
        vector<int> c(i - lf - 1);
        c.push_back(k);
        for (int j = 0; j < (int)ls.size(); ++j)
            c.push_back(1LL * k * (P - ls[j]) % P);
        if (c.size() < cur.size()) c.resize(cur.size());
        for (int j = 0; j < (int)cur.size(); ++j)
            c[j] = (c[j] + cur[j]) % P;
        if (i - lf + (int)ls.size() >= (int)cur.size()) {
            ls = cur, lf = i;
            ld = (t + P - x[i]) % P;
        }
        cur = c;
    }
    return cur;
}

```

5.16 Gauss Elimination

```

double Gauss(vector<vector<double>> &d) {
    int n = d.size(), m = d[0].size();
    double det = 1;
    for (int i = 0; i < m; ++i) {
        int p = -1;
        for (int j = i; j < n; ++j) {
            if (fabs(d[j][i]) < kEps) continue;
            if (p == -1 || fabs(d[j][i]) > fabs(d[p][i])) p = j;
        }
        if (p == -1) continue;
        if (p != i) det *= -1;
        for (int j = 0; j < m; ++j) swap(d[p][j], d[i][j]);
    }

```

```

for (int j = 0; j < n; ++j) {
    if (i == j) continue;
    double z = d[j][i] / d[i][i];
    for (int k = 0; k < m; ++k) d[j][k] -= z * d[i][k];
}
for (int i = 0; i < n; ++i) det *= d[i][i];
return det;
}

```

5.17 LinearRec

```

template <int P>
int LinearRec(const vector<int> &s, const vector<int> &coeff, int k) {
    int n = s.size();
    auto Combine = [&](const auto &a, const auto &b) {
        vector<int> res(n * 2 + 1);
        for (int i = 0; i <= n; ++i) {
            for (int j = 0; j <= n; ++j)
                (res[i + j] += 1LL * a[i] * b[j] % P) %= P;
        }
        for (int i = 2 * n; i > n; --i) {
            for (int j = 0; j < n; ++j)
                (res[i - 1 - j] += 1LL * res[i] * coeff[j] % P) %= P;
        }
        res.resize(n + 1);
        return res;
    };
    vector<int> p(n + 1), e(n + 1);
    p[0] = e[1] = 1;
    for (; k > 0; k >= 1) {
        if (k & 1) p = Combine(p, e);
        e = Combine(e, e);
    }
    int res = 0;
    for (int i = 0; i < n; ++i) (res += 1LL * p[i + 1] * s[i] % P) %= P;
    return res;
}

```

5.18 SubsetConv

```

vector<i64> SubsetConv(vector<i64> f, vector<i64> g) {
    const int n = f.size();
    const int U = __lg(n) + 1;
    vector F(U, vector<i64>(n));
    auto G = F, H = F;
    for (int i = 0; i < n; i++) {
        F[popcount<u64>(i)][i] = f[i];
        G[popcount<u64>(i)][i] = g[i];
    }
    for (int i = 0; i < U; i++) {
        FWT(F[i], ORop);
        FWT(G[i], ORop);
    }
    for (int i = 0; i < U; i++)
        for (int j = 0; j <= i; j++)
            for (int k = 0; k < n; k++)
                H[i][k] = (H[i][k] + F[i - j][k] * G[j][k]) % mod;
    for (int i = 0; i < U; i++) FWT(H[i], ORinv);
    for (int i = 0; i < n; i++) f[i] = H[popcount<u64>(i)][i];
    return f;
}

```

5.19 SqrtMod

```

// 0 <= x < p, s.t. x^2 mod p = n
int SqrtMod(int n, int P) {
    if (P == 2 or n == 0) return n;
    if (power(n, (P - 1) / 2, P) != 1) return -1;
    mt19937 rng(12312);
    i64 z = 0, w;
    while (power(w = (z * z - n + P) % P, (P - 1) / 2, P) != P - 1)
        z = rng() % P;
    const auto M = [P, w](auto &u, auto &v) {
        return pair{
            (u.ff * v.ff + u.ss * v.ss % P * w) % P,
            (u.ff * v.ss + u.ss * v.ff) % P
        };
    };
}

```

```

};
pair<i64, i64> r{1, 0}, e{z, 1};
for (int w = (P + 1) / 2; w; w >= 1, e = M(e, e))
    if (w & 1) r = M(r, e);
return r.ff;
}

```

5.20 DiscreteLog

```

template<class T>
T BSGS(T x, T y, T M) {
    // x^? \equiv y (mod M)
    T t = 1, c = 0, g = 1;
    for (T M_ = M; M_ > 0; M_ >= 1) g = g * x % M;
    for (g = gcd(g, M); t % g != 0; ++c) {
        if (t == y) return c;
        t = t * x % M;
    }
    if (y % g != 0) return -1;
    t /= g, y /= g, M /= g;
    T h = 0, gs = 1;
    for (; h * h < M; ++h) gs = gs * x % M;
    unordered_map<T, T> bs;
    for (T s = 0; s < h; bs[y] = ++s) y = y * x % M;
    for (T s = 0; s < M; s += h) {
        t = t * gs % M;
        if (bs.count(t)) return c + s + h - bs[t];
    }
    return -1;
}

```

5.21 FloorSum

```

// sigma 0 ~ n-1: (a * i + b) / m
i64 floorSum(i64 n, i64 m, i64 a, i64 b) {
    u64 ans = 0;
    if (a < 0) {
        u64 a2 = (a % m + m) % m;
        ans -= 1ULL * n * (n - 1) / 2 * ((a2 - a) / m);
        a = a2;
    }
    if (b < 0) {
        u64 b2 = (b % m + m) % m;
        ans -= 1ULL * n * ((b2 - b) / m);
        b = b2;
    }
    while (true) {
        if (a >= m) {
            ans += n * (n - 1) / 2 * (a / m);
            a %= m;
        }
        if (b >= m) {
            ans += n * (b / m);
            b %= m;
        }
        u64 y_max = a * n + b;
        if (y_max < m) break;
        n = y_max / m;
        b = y_max % m;
        swap(m, a);
    }
    return ans;
}

```

5.22 Linear Programming Simplex

```

// max{cx} subject to {Ax<=b, x>=0}
// n: constraints, m: vars !!!
// x[] is the optimal solution vector
// usage :
// x = simplex(A, b, c); (A <= 100 x 100)
vector<double> simplex(
    const vector<vector<double>> &a,
    const vector<double> &b,
    const vector<double> &c) {
    int n = (int)a.size(), m = (int)a[0].size() + 1;
    vector val(n + 2, vector<double>(m + 1));
    vector<int> idx(n + m);
    iota(all(idx), 0);
    int r = n, s = m - 1;
    for (int i = 0; i < n; ++i) {
        for (int j = 0; j < m - 1; ++j)
            val[i][j] = -a[i][j];
    }
}

```

```

    val[i][m - 1] = 1;
    val[i][m] = b[i];
    if (val[r][m] > val[i][m])
        r = i;
}
copy(all(c), val[n].begin());
val[n + 1][m - 1] = -1;
for (double num; ; ) {
    if (r < n) {
        swap(idx[s], idx[r + m]);
        val[r][s] = 1 / val[r][s];
        for (int j = 0; j <= m; ++j) if (j != s)
            val[r][j] *= -val[r][s];
        for (int i = 0; i <= n + 1; ++i) if (i != r) {
            for (int j = 0; j <= m; ++j) if (j != s)
                val[i][j] += val[r][j] * val[i][s];
            val[i][s] *= val[r][s];
        }
    }
    r = s = -1;
    for (int j = 0; j < m; ++j)
        if (s < 0 || idx[s] > idx[j])
            if (val[n + 1][j] > eps || val[n + 1][j] > -eps
                && val[n][j] > eps)
                s = j;
    if (s < 0) break;
    for (int i = 0; i < n; ++i) if (val[i][s] < -eps) {
        if (r < 0
            || (num = val[r][m] / val[r][s] - val[i][m] /
                val[i][s]) < -eps
            || num < eps && idx[r + m] > idx[i + m])
            r = i;
    }
    if (r < 0) {
        // Solution is unbounded.
        return vector<double>{};
    }
}
if (val[n + 1][m] < -eps) {
    // No solution.
    return vector<double>{};
}
vector<double> x(m - 1);
for (int i = m; i < n + m; ++i)
    if (idx[i] < m - 1)
        x[idx[i]] = val[i - m][m];
return x;
}

```

5.23 Lagrange Interpolation

```

struct Lagrange {
    int deg{};
    vector<i64> C;
    Lagrange(const vector<i64> &P) {
        deg = P.size() - 1;
        C.assign(deg + 1, 0);
        for (int i = 0; i <= deg; i++) {
            i64 q = comb(-i) * comb(i - deg) % mod;
            if ((deg - i) % 2 == 1) {
                q = mod - q;
            }
            C[i] = P[i] * q % mod;
        }
    }
    i64 operator()(i64 x) { // 0 <= x < mod
        if (0 <= x and x <= deg) {
            i64 ans = comb(x) * comb(deg - x) % mod;
            if ((deg - x) % 2 == 1) {
                ans = (mod - ans);
            }
            return ans * C[x] % mod;
        }
        vector<i64> pre(deg + 1), suf(deg + 1);
        for (int i = 0; i <= deg; i++) {
            pre[i] = (x - i);
            if (i) {
                pre[i] = pre[i] * pre[i - 1] % mod;
            }
        }
        for (int i = deg; i >= 0; i--) {
            suf[i] = (x - i);
            if (i < deg) {

```

```

                suf[i] = suf[i] * suf[i + 1] % mod;
            }
        }
        i64 ans = 0;
        for (int i = 0; i <= deg; i++) {
            ans += (i == 0 ? 1 : pre[i - 1]) * (i == deg ? 1
                : suf[i + 1]) % mod * C[i];
            ans %= mod;
        }
        if (ans < 0) ans += mod;
        return ans;
    }
};

```

6 Geometry

6.1 Point

```

using numbers::pi;
template<class T> inline constexpr T eps =
    numeric_limits<T>::epsilon() * 1E6;
using Real = long double;
struct Pt {
    Real x{}, y{};
    Pt operator+(Pt a) const { return {x + a.x, y + a.y}; }
    Pt operator-(Pt a) const { return {x - a.x, y - a.y}; }
    Pt operator*(Real k) const { return {x * k, y * k}; }
    Pt operator/(Real k) const { return {x / k, y / k}; }
    Real operator*(Pt a) const { return x * a.x + y * a.y; }
    Real operator^(Pt a) const { return x * a.y - y * a.x; }
    auto operator<=(const Pt&) const = default;
    bool operator==(const Pt&) const = default;
};
int sgn(Real x) { return (x > -eps<Real>) - (x < eps<
    Real>); }
Real ori(Pt a, Pt b, Pt c) { return (b - a) ^ (c - a); }
bool argcmp(const Pt &a, const Pt &b) { // arg(a) < arg
    (b)
    int f = (Pt{a.y, -a.x} > Pt{} ? 1 : -1) * (a != Pt{});
    ;
    int g = (Pt{b.y, -b.x} > Pt{} ? 1 : -1) * (b != Pt{});
    ;
    return f == g ? (a ^ b) > 0 : f < g;
}
Pt rotate(Pt u) { return {-u.y, u.x}; }
Real abs2(Pt a) { return a * a; }
// floating point only
Pt rotate(Pt u, Real a) {
    Pt v{sinl(a), cosl(a)};
    return {u ^ v, u * v};
}
Real abs(Pt a) { return sqrtl(a * a); }
Real arg(Pt x) { return atan2l(x.y, x.x); }
Pt unit(Pt x) { return x / abs(x); }

```

6.2 Line

```

struct Line {
    Pt a, b;
    Pt dir() const { return b - a; }
};
int PtSide(Pt p, Line L) {
    return sgn(ori(L.a, L.b, p)); // for int
    return sgn(ori(L.a, L.b, p) / abs(L.a - L.b));
}
bool PtOnSeg(Pt p, Line L) {
    return PtSide(p, L) == 0 and sgn((p - L.a) * (p - L.b
        )) <= 0;
}
Pt proj(Pt p, Line l) {
    Pt dir = unit(l.b - l.a);
    return l.a + dir * (dir * (p - l.a));
}

```

6.3 Circle

```

struct Cir {
    Pt o;
    double r;

```

```
};
bool disjunct(const Cir &a, const Cir &b) {
    return sgn(abs(a.o - b.o) - a.r - b.r) >= 0;
}
bool contain(const Cir &a, const Cir &b) {
    return sgn(a.r - b.r - abs(a.o - b.o)) >= 0;
}
```

6.4 Point to Segment Distance

```
double PtSegDist(Pt p, Line l) {
    double ans = min(abs(p - l.a), abs(p - l.b));
    if (sgn(abs(l.a - l.b)) == 0) return ans;
    if (sgn((l.a - l.b) * (p - l.b)) < 0) return ans;
    if (sgn((l.b - l.a) * (p - l.a)) < 0) return ans;
    return min(ans, abs(ori(p, l.a, l.b)) / abs(l.a - l.b));
}
double SegDist(Line l, Line m) {
    return PtSegDist({0, 0}, {l.a - m.a, l.b - m.b});
}
```

6.5 Point in Polygon

```
int inPoly(Pt p, const vector<Pt> &P) {
    const int n = P.size();
    int cnt = 0;
    for (int i = 0; i < n; i++) {
        Pt a = P[i], b = P[(i + 1) % n];
        if (PtOnSeg(p, {a, b})) return 1; // on edge
        if ((sgn(a.y - p.y) == 1) ^ (sgn(b.y - p.y) == 1))
            cnt += sgn(ori(a, b, p));
    }
    return cnt == 0 ? 0 : 2; // out, in
}
```

6.6 Intersection of Lines

```
bool isInter(Line l, Line m) {
    if (PtOnSeg(m.a, l) or PtOnSeg(m.b, l) or
        PtOnSeg(l.a, m) or PtOnSeg(l.b, m))
        return true;
    return PtSide(m.a, l) * PtSide(m.b, l) < 0 and
        PtSide(l.a, m) * PtSide(l.b, m) < 0;
}
Pt LineInter(Line l, Line m) {
    double s = ori(m.a, m.b, l.a), t = ori(m.a, m.b, l.b);
    return (l.b * s - l.a * t) / (s - t);
}
bool strictInter(Line l, Line m) {
    int la = PtSide(m.a, l);
    int lb = PtSide(m.b, l);
    int ma = PtSide(l.a, m);
    int mb = PtSide(l.b, m);
    if (la == 0 and lb == 0) return false;
    return la * lb < 0 and ma * mb < 0;
}
```

6.7 Intersection of Circle and Line

```
vector<Pt> CircleLineInter(Cir c, Line l) {
    Pt H = proj(c.o, l);
    Pt dir = unit(l.b - l.a);
    double h = abs(H - c.o);
    if (sgn(h - c.r) > 0) return {};
    double d = sqrt(max((double)0., c.r * c.r - h * h));
    if (sgn(d) == 0) return {H};
    return {H - dir * d, H + dir * d};
    // Counterclockwise
}
```

6.8 Intersection of Circles

```
vector<Pt> CircleInter(Cir a, Cir b) {
    double d2 = abs2(a.o - b.o), d = sqrt(d2);
    if (d < max(a.r, b.r) - min(a.r, b.r) || d > a.r + b.r)
        return {};
    Pt u = (a.o + b.o) / 2 + (a.o - b.o) * ((b.r * b.r - a.r * a.r) / (2 * d2));
    double A = sqrt((a.r + b.r + d) * (a.r - b.r + d) * (a.r + b.r - d) * (-a.r + b.r + d));
    Pt v = rotate(b.o - a.o) * A / (2 * d2);
    if (sgn(v.x) == 0 and sgn(v.y) == 0) return {u};
    return {u - v, u + v}; // counter clockwise of a
}
```

6.9 Area of Circle and Polygon

```
double CirclePoly(Cir C, const vector<Pt> &P) {
    auto arg = [&](Pt p, Pt q) { return atan2(p ^ q, p * q); };
    double r2 = C.r * C.r / 2;
    auto tri = [&](Pt p, Pt q) {
        Pt d = q - p;
        auto a = (d * p) / abs2(d), b = (abs2(p) - C.r * C.r) / abs2(d);
        auto det = a * a - b;
        if (det <= 0) return arg(p, q) * r2;
        auto s = max(0., -a - sqrt(det)), t = min(1., -a + sqrt(det));
        if (t < 0 or 1 <= s) return arg(p, q) * r2;
        Pt u = p + d * s, v = p + d * t;
        return arg(p, u) * r2 + (u ^ v) / 2 + arg(v, q) * r2;
    };
    double sum = 0.0;
    for (int i = 0; i < P.size(); i++)
        sum += tri(P[i] - C.o, P[(i + 1) % P.size()] - C.o);
    return sum;
}
```

6.10 Area of Sector

```
//  $\square AOB * r^2 / 2$ 
double Sector(Pt a, Pt b, double r) {
    double theta = atan2(a.y, a.x) - atan2(b.y, b.x);
    while (theta <= 0) theta += 2 * pi;
    while (theta >= 2 * pi) theta -= 2 * pi;
    theta = min(theta, 2 * pi - theta);
    return r * r * theta / 2;
}
```

6.11 Union of Polygons

```
// Area[i] : area covered by at least i polygon
vector<double> PolyUnion(const vector<vector<Pt>> &P) {
    const int n = P.size();
    vector<double> Area(n + 1);
    vector<Line> Ls;
    for (int i = 0; i < n; i++)
        for (int j = 0; j < P[i].size(); j++)
            Ls.push_back({P[i][j], P[i][(j + 1) % P[i].size()]});
    auto cmp = [&](Line &l, Line &r) {
        Pt u = l.b - l.a, v = r.b - r.a;
        if (argcmp(u, v)) return true;
        if (argcmp(v, u)) return false;
        return PtSide(l.a, r) < 0;
    };
    sort(all(Ls), cmp);
    for (int l = 0, r = 0; l < Ls.size(); l = r) {
        while (r < Ls.size() and !cmp(Ls[l], Ls[r])) r++;
        Line L = Ls[l];
        vector<pair<Pt, int>> event;
        for (auto [c, d] : Ls) {
            if (sgn((L.a - L.b) ^ (c - d)) != 0) {
                int s1 = PtSide(c, L) == 1;
                int s2 = PtSide(d, L) == 1;
                if (s1 ^ s2) event.emplace_back(LineInter(L, {c, d}), s1 ? 1 : -1);
            } else if (PtSide(c, L) == 0 and sgn((L.a - L.b) * (c - d)) > 0) {
                event.emplace_back(c, 2);
                event.emplace_back(d, -2);
            }
        }
        sort(all(event), [&](auto i, auto j) {
            return (L.a - i.ff) * (L.a - L.b) < (L.a - j.ff) * (L.a - L.b);
        });
        int cov = 0, tag = 0;
        Pt lst{0, 0};
        for (auto [p, s] : event) {
            if (cov >= tag) {
                Area[cov] += lst ^ p;
                Area[cov - tag] -= lst ^ p;
            }
            if (abs(s) == 1) cov += s;
            else tag += s / 2;
            lst = p;
        }
    }
}
```



```

    }
}
for (int i = n - 1; i >= 0; i--) Area[i] += Area[i + 1];
for (int i = 1; i <= n; i++) Area[i] /= 2;
return Area;
};

```

6.12 Union of Circles

```

// Area[i] : area covered by at least i circle
vector<double> CircleUnion(const vector<Cir> &C) {
    const int n = C.size();
    vector<double> Area(n + 1);
    auto check = [&](int i, int j) {
        if (!contain(C[i], C[j]))
            return false;
        return sgn(C[i].r - C[j].r) > 0 or (sgn(C[i].r - C[j].r) == 0 and i < j);
    };
    struct Teve {
        double ang; int add; Pt p;
        bool operator<(const Teve &b) { return ang < b.ang; }
    };
    auto ang = [&](Pt p) { return atan2(p.y, p.x); };
    for (int i = 0; i < n; i++) {
        int cov = 1;
        vector<Teve> event;
        for (int j = 0; j < n; j++) if (i != j) {
            if (check(j, i)) cov++;
            else if (!check(i, j) and !disjunct(C[i], C[j])) {
                auto I = CircleInter(C[i], C[j]);
                assert(I.size() == 2);
                double a1 = ang(I[0] - C[i].o), a2 = ang(I[1] - C[i].o);
                event.push_back({a1, 1, I[0]});
                event.push_back({a2, -1, I[1]});
                if (a1 > a2) cov++;
            }
        }
        if (event.empty()) {
            Area[cov] += pi * C[i].r * C[i].r;
            continue;
        }
        sort(all(event));
        event.push_back(event[0]);
        for (int j = 0; j + 1 < event.size(); j++) {
            cov += event[j].add;
            Area[cov] += (event[j].p ^ event[j + 1].p) / 2.;
            double theta = event[j + 1].ang - event[j].ang;
            if (theta < 0) theta += 2 * pi;
            Area[cov] += (theta - sin(theta)) * C[i].r * C[i].r / 2.;
        }
    }
    return Area;
}

```

6.13 TangentLines of Circle and Point

```

vector<Line> CircleTangent(Cir c, Pt p) {
    vector<Line> z;
    double d = abs(p - c.o);
    if (sgn(d - c.r) == 0) {
        Pt i = rotate(p - c.o);
        z.push_back({p, p + i});
    } else if (d > c.r) {
        double o = acos(c.r / d);
        Pt i = unit(p - c.o);
        Pt j = rotate(i, o) * c.r;
        Pt k = rotate(i, -o) * c.r;
        z.push_back({c.o + j, p});
        z.push_back({c.o + k, p});
    }
    return z;
}

```

6.14 TangentLines of Circles

```

vector<Line> CircleTangent(Cir c1, Cir c2, int sign1) {
    // sign1 = 1 for outer tang, -1 for inter tang
    vector<Line> ret;

```

```

    double d_sq = abs2(c1.o - c2.o);
    if (sgn(d_sq) == 0) return ret;
    double d = sqrt(d_sq);
    Pt v = (c2.o - c1.o) / d;
    double c = (c1.r - sign1 * c2.r) / d;
    if (c * c > 1) return ret;
    double h = sqrt(max(0.0, 1.0 - c * c));
    for (int sign2 = 1; sign2 >= -1; sign2 -= 2) {
        Pt n = Pt(v.x * c - sign2 * h * v.y, v.y * c + sign2 * h * v.x);
        Pt p1 = c1.o + n * c1.r;
        Pt p2 = c2.o + n * (c2.r * sign1);
        if (sgn(p1.x - p2.x) == 0 && sgn(p1.y - p2.y) == 0)
            p2 = p1 + rotate(c2.o - c1.o);
        ret.push_back({p1, p2});
    }
    return ret;
}

```

6.15 Convex Hull

```

vector<Pt> Hull(vector<Pt> P) {
    sort(all(P));
    P.erase(unique(all(P)), P.end());
    if (P.size() <= 1) return P;
    P.insert(P.end(), P.rbegin() + 1, P.rend());
    vector<Pt> stk;
    for (auto p : P) {
        auto it = stk.rbegin();
        while (stk.rend() - it >= 2 and \
            ori(*next(it), *it, p) <= 0 and \
            (*next(it) < *it) == (*it < p)) {
            it++;
        }
        stk.resize(stk.rend() - it);
        stk.push_back(p);
    }
    stk.pop_back();
    return stk;
}

```

6.16 Convex Hull trick

```

struct Convex {
    int n;
    vector<Pt> A, V, L, U;
    Convex(const vector<Pt> &A) : A(A), n(A.size()) {
        // n >= 3
        auto it = max_element(all(A));
        L.assign(A.begin(), it + 1);
        U.assign(it, A.end()), U.push_back(A[0]);
        for (int i = 0; i < n; i++) {
            V.push_back(A[(i + 1) % n] - A[i]);
        }
    }
    int inside(Pt p, const vector<Pt> &h, auto f) {
        auto it = lower_bound(all(h), p, f);
        if (it == h.end()) return 0;
        if (it == h.begin()) return p == *it;
        return 1 - sgn(ori(*prev(it), p, *it));
    }
    // 0: out, 1: on, 2: in
    int inside(Pt p) {
        return min(inside(p, L, less{}), inside(p, U, greater{}));
    }
    static bool cmp(Pt a, Pt b) { return sgn(a ^ b) > 0; }
    // A[i] is a far/closer tangent point
    int tangent(Pt v, bool close = true) {
        assert(v != Pt{});
        auto l = V.begin(), r = V.begin() + L.size() - 1;
        if (v < Pt{}) l = r, r = V.end();
        if (close) return (lower_bound(l, r, v, cmp) - V.begin()) % n;
        return (upper_bound(l, r, v, cmp) - V.begin()) % n;
    }
    // closer tangent point
    array<int, 2> tangent2(Pt p) {
        array<int, 2> t{-1, -1};
        if (inside(p) == 2) return t;
        if (auto it = lower_bound(all(L), p); it != L.end()
            and p == *it) {
            int s = it - L.begin();

```



```

    return {(s + 1) % n, (s - 1 + n) % n};
}
if (auto it = lower_bound(all(U), p, greater{}); it
    != U.end() and p == *it) {
    int s = it - U.begin() + L.size() - 1;
    return {(s + 1) % n, (s - 1 + n) % n};
}
for (int i = 0; i != t[0]; i = tangent((A[t[0] = i]
    - p), 0));
for (int i = 0; i != t[1]; i = tangent((p - A[t[1]
    = i]), 1));
return t;
}
int find(int l, int r, Line L) {
    if (r < l) r += n;
    int s = PtSide(A[l % n], L);
    return *ranges::partition_point(views::iota(l, r),
        [&](int m) {
            return PtSide(A[m % n], L) == s;
        }) - 1;
};
// Line A_x A_x+1 intersect with L
vector<int> intersect(Line L) {
    int l = tangent(L.a - L.b), r = tangent(L.b - L.a);
    if (PtSide(A[l], L) * PtSide(A[r], L) >= 0) return
    {};
    return {find(l, r, L) % n, find(r, l, L) % n};
}
};

```

6.17 Dynamic Convex Hull

```

template<class T, class Comp = less<T>>
struct DynamicHull {
    set<T, Comp> H;
    void insert(T p) {
        if (inside(p)) return;
        auto it = H.insert(p).ff;
        while (it != H.begin() and prev(it) != H.begin() \
            and ori(*prev(it), 2), *prev(it), *it) <= 0) {
            it = H.erase(--it);
        }
        while (it != --H.end() and next(it) != --H.end() \
            and ori(*it, *next(it), *next(it), 2)) <= 0) {
            it = --H.erase(++it);
        }
    }
    int inside(T p) { // 0: out, 1: on, 2: in
        auto it = H.lower_bound(p);
        if (it == H.end()) return 0;
        if (it == H.begin()) return p == *it;
        return 1 - sgn(ori(*prev(it), p, *it));
    }
};
// DynamicHull<Pt> D;
// DynamicHull<Pt, greater<>> U;
// D.inside(p) and U.inside(p)

```

6.18 Half Plane Intersection

```

bool cover(Line L, Line P, Line Q) {
    // return PtSide(LineInter(P, Q), L) <= 0; for double
    i128 u = (Q.a - P.a) ^ Q.dir();
    i128 v = P.dir() ^ Q.dir();
    i128 x = P.dir().x * u + (P.a - L.a).x * v;
    i128 y = P.dir().y * u + (P.a - L.a).y * v;
    return sgn(x * L.dir().y - y * L.dir().x) * sgn(v) >=
    0;
}
vector<Line> HPI(vector<Line> P) {
    sort(all(P), [&](Line l, Line m) {
        if (argcmp(l.dir(), m.dir()) return true;
        if (argcmp(m.dir(), l.dir()) return false;
        return ori(m.a, m.b, l.a) > 0;
    });
    int n = P.size(), l = 0, r = -1;
    for (int i = 0; i < n; i++) {
        if (i and !argcmp(P[i - 1].dir(), P[i].dir()))
            continue;
        while (l < r and cover(P[i], P[r - 1], P[r])) r--;
        while (l < r and cover(P[i], P[l], P[l + 1])) l++;
        P[++r] = P[i];
    }
    while (l < r and cover(P[l], P[r - 1], P[r])) r--;
}

```

```

while (l < r and cover(P[r], P[l], P[l + 1])) l++;
if (r - l <= 1 or !argcmp(P[l].dir(), P[r].dir()))
    return {}; // empty
if (cover(P[l + 1], P[l], P[r]))
    return {}; // infinity
return vector(P.begin() + l, P.begin() + r + 1);
}

```

6.19 Minkowski

```

// P, Q, R(return) are counterclockwise order convex
// polygon
vector<Pt> Minkowski(vector<Pt> P, vector<Pt> Q) {
    assert(P.size() >= 2 and Q.size() >= 2);
    auto cmp = [&](Pt a, Pt b) {
        return Pt{a.y, a.x} < Pt{b.y, b.x};
    };
    auto reorder = [&](auto &R) {
        rotate(R.begin(), min_element(all(R), cmp), R.end());
        R.push_back(R[0]), R.push_back(R[1]);
    };
    const int n = P.size(), m = Q.size();
    reorder(P), reorder(Q);
    vector<Pt> R;
    for (int i = 0, j = 0, s; i < n or j < m; ) {
        R.push_back(P[i] + Q[j]);
        s = sgn((P[i + 1] - P[i]) ^ (Q[j + 1] - Q[j]));
        if (s >= 0) i++;
        if (s <= 0) j++;
    }
    return R;
}

```

6.20 Minimal Enclosing Circle

```

Pt Center(Pt a, Pt b, Pt c) {
    Pt x = (a + b) / 2;
    Pt y = (b + c) / 2;
    return LineInter({x, x + rotate(b - a)}, {y, y +
        rotate(c - b)});
}
Cir MEC(vector<Pt> P) {
    mt19937 rng(time(0));
    shuffle(all(P), rng);
    Cir C{};
    for (int i = 0; i < P.size(); i++) {
        if (C.inside(P[i])) continue;
        C = {P[i], 0};
        for (int j = 0; j < i; j++) {
            if (C.inside(P[j])) continue;
            C = {(P[i] + P[j]) / 2, abs(P[i] - P[j]) / 2};
            for (int k = 0; k < j; k++) {
                if (C.inside(P[k])) continue;
                C.o = Center(P[i], P[j], P[k]);
                C.r = abs(C.o - P[i]);
            }
        }
    }
    return C;
}

```

6.21 Point In Circumcircle

```

// p[0], p[1], p[2] should be counterclockwise order
int inCC(const array<Pt, 3> &p, Pt a) {
    i128 det = 0;
    for (int i = 0; i < 3; i++)
        det += i128(abs2(p[i]) - abs2(a)) * ori(a, p[(i +
            1) % 3], p[(i + 2) % 3]);
    return (det > 0) - (det < 0); // in:1, on:0, out:-1
}

```

6.22 Delaunay Triangulation

```

bool inCC(const array<Pt, 3> &p, Pt a) {
    i128 det = 0;
    for (int i = 0; i < 3; i++)
        det += i128(abs2(p[i]) - abs2(a)) * ori(a, p[(i +
            1) % 3], p[(i + 2) % 3]);
    return det > 0;
}
struct Edge {
    int id;
    list<Edge>::iterator rit;
}

```

```

};
vector<list<Edge>> Delaunay(const vector<Pt> &P) {
    assert(is_sorted(all(P))); // need sorted before!
    const int n = P.size();
    vector<list<Edge>> E(n);
    auto addEdge = [&](int u, int v, auto a, auto b) {
        a = E[u].insert(a, {v});
        b = E[v].insert(b, {u});
        return array{b->rit = a, a->rit = b};
    };
    auto divide = [&](auto &&self, int l, int r) -> int {
        if (r - l <= 1) return l;
        int m = (l + r) / 2;
        array<int, 2> t{self(self, l, m), self(self, m, r)};
        int w = t[P[t[1]].y < P[t[0]].y];
        auto low = [&](int s) {
            for (Edge e : E[t[s]]) {
                if (ori(P[t[1]], P[t[0]], P[e.id]) > 0 or
                    PtOnSeg(P[e.id], {P[t[0]], P[t[1]]})) {
                    t[s] = e.id;
                    return true;
                }
            }
            return false;
        };
        while (low(0) or low(1));
        array its = addEdge(t[0], t[1], E[t[0]].begin(), E[t[1]].end());
        while (true) {
            Line l{P[t[0]], P[t[1]]};
            auto cand = [&](int s) -> optional<list<Edge>::
            iterator> {
                auto nxt = [&](auto it) {
                    if (s == 0) return (++it == E[t[0]].end() ? E[t[0]].begin() : it);
                    return --(it == E[t[1]].begin() ? E[t[1]].end() : it);
                };
                if (E[t[s]].empty()) return {};
                auto lst = nxt(its[s]), it = nxt(lst);
                while (PtSide(P[it->id], L) > 0 and inCC({L.a, L.b, P[lst->id]}, P[it->id])) {
                    E[t[s ^ 1]].erase(lst->rit);
                    E[t[s]].erase(lst);
                    it = nxt(lst = it);
                }
                return PtSide(P[lst->id], L) > 0 ? optional{lst} : nullopt;
            };
            auto lc = cand(0), rc = cand(1);
            if (!lc and !rc) break;
            int sd = !lc or (rc and inCC({L.a, L.b, P[*lc->id]}, P[*rc->id]));
            auto lst = *(sd ? rc : lc);
            t[sd] = lst->id;
            its[sd] = lst->rit;
            its = addEdge(t[0], t[1], ++its[0], its[1]);
        }
        return w;
    };
    divide(divide, 0, n);
    return E;
};

```

6.23 Triangle Center

```

Pt TriangleCircumCenter(Pt a, Pt b, Pt c) {
    Pt res;
    double a1 = atan2(b.y - a.y, b.x - a.x) + pi / 2;
    double a2 = atan2(c.y - b.y, c.x - b.x) + pi / 2;
    double ax = (a.x + b.x) / 2;
    double ay = (a.y + b.y) / 2;
    double bx = (c.x + b.x) / 2;
    double by = (c.y + b.y) / 2;
    double r1 = (sin(a2) * (ax - bx) + cos(a2) * (by - ay)) / (sin(a1) * cos(a2) - sin(a2) * cos(a1));
    return Pt(ax + r1 * cos(a1), ay + r1 * sin(a1));
}
Pt TriangleMassCenter(Pt a, Pt b, Pt c) {
    return (a + b + c) / 3.0;
}
Pt TriangleOrthoCenter(Pt a, Pt b, Pt c) {

```

```

    return TriangleMassCenter(a, b, c) * 3.0 -
        TriangleCircumCenter(a, b, c) * 2.0;
}
Pt TriangleInnerCenter(Pt a, Pt b, Pt c) {
    Pt res;
    double la = abs(b - c);
    double lb = abs(a - c);
    double lc = abs(a - b);
    res.x = (la * a.x + lb * b.x + lc * c.x) / (la + lb + lc);
    res.y = (la * a.y + lb * b.y + lc * c.y) / (la + lb + lc);
    return res;
}

```

7 Stringology

7.1 KMP

```

vector<int> buildFail(string s) {
    const int len = s.size();
    vector<int> f(len, -1);
    for (int i = 1, p = -1; i < len; i++) {
        while (~p and s[p + 1] != s[i]) p = f[p];
        if (s[p + 1] == s[i]) p++;
        f[i] = p;
    }
    return f;
}

```

7.2 Z-algorithm

```

vector<int> zalgo(string s) {
    if (s.empty()) return {};
    int len = s.size();
    vector<int> z(len);
    z[0] = len;
    for (int i = 1, l = 1, r = 1; i < len; i++) {
        z[i] = i < r ? min(z[i - l], r - i) : 0;
        while (i + z[i] < len and s[i + z[i]] == s[z[i]]) z[i]++;
        if (i + z[i] > r) l = i, r = i + z[i];
    }
    return z;
}

```

7.3 Manacher

```

vector<int> manacher(string_view s) {
    string p = "@#";
    for (char c : s) {
        p += c;
        p += '#';
    }
    p += '$';
    vector<int> dp(p.size());
    int mid = 0, r = 1;
    for (int i = 1; i < p.size() - 1; i++) {
        auto &k = dp[i];
        k = i < mid + r ? min(dp[mid * 2 - i], mid + r - i) : 0;
        while (p[i + k + 1] == p[i - k - 1]) k++;
        if (i + k > mid + r) mid = i, r = k;
    }
    return vector<int>(dp.begin() + 2, dp.end() - 2);
}

```

7.4 SuffixArray Simple

```

struct SuffixArray {
    int n;
    vector<int> suf, rk, S;
    SuffixArray(vector<int> _S) : S(_S) {
        n = S.size();
        suf.assign(n, 0);
        rk.assign(n * 2, -1);
        iota(all(suf), 0);
        for (int i = 0; i < n; i++) rk[i] = S[i];
        for (int k = 2; k < n + n; k *= 2) {
            auto cmp = [&](int a, int b) -> bool {
                return rk[a] == rk[b] ? (rk[a + k / 2] < rk[b + k / 2]) : (rk[a] < rk[b]);
            };
            sort(all(suf), cmp);
            auto tmp = rk;

```

```

    tmp[suf[0]] = 0;
    for (int i = 1; i < n; i++) {
        tmp[suf[i]] = tmp[suf[i - 1]] + cmp(suf[i - 1],
        suf[i]);
    }
    rk.swap(tmp);
}
};

```

7.5 SuffixArray SAIS C++20

```

auto sais(const auto &s) {
    const int n = (int)s.size(), z = ranges::max(s) + 1;
    if (n == 1) return vector{0};
    vector<int> c(z); for (int x : s) ++c[x];
    partial_sum(all(c), begin(c));
    vector<int> sa(n); auto I = views::iota(0, n);
    vector<bool> t(n); t[n - 1] = true;
    for (int i = n - 2; i >= 0; i--)
        t[i] = (s[i] == s[i + 1] ? t[i + 1] : s[i] < s[i + 1]);
    auto is_lms = views::filter([&t](int x) {
        return x && t[x] & !t[x - 1];
    });
    auto induce = [&] {
        for (auto x = c; int y : sa)
            if (y-- and !t[y]) sa[x[s[y] - 1]++] = y;
        for (auto x = c; int y : sa | views::reverse)
            if (y-- and t[y]) sa[--x[s[y]]] = y;
    };
    vector<int> lms, q(n); lms.reserve(n);
    for (auto x = c; int i : I | is_lms) {
        q[i] = int(lms.size());
        lms.push_back(sa[--x[s[i]]] = i);
    }
    induce(); vector<int> ns(lms.size());
    for (int j = -1, nz = 0; int i : sa | is_lms) {
        if (j >= 0) {
            int len = min({n - i, n - j, lms[q[i] + 1] - i});
            ns[q[i]] = nz += lexicographical_compare(
                s.begin() + j, s.begin() + j + len,
                s.begin() + i, s.begin() + i + len
            );
        }
        j = i;
    }
    ranges::fill(sa, 0); auto nsa = sais(ns);
    for (auto x = c; int y : nsa | views::reverse)
        y = lms[y], sa[--x[s[y]]] = y;
    return induce(), sa;
}
// sa[i]: sa[i]-th suffix is the
// i-th lexicographically smallest suffix.
// lcp[i]: LCP of suffix sa[i] and suffix sa[i + 1].
struct Suffix {
    int n;
    vector<int> sa, rk, lcp;
    Suffix(const auto &s) : n(s.size()),
        lcp(n - 1), rk(n) {
        vector<int> t(n + 1); // t[n] = 0
        copy(all(s), t.begin()); // s shouldn't contain 0
        sa = sais(t); sa.erase(sa.begin());
        for (int i = 0; i < n; i++) rk[sa[i]] = i;
        for (int i = 0, h = 0; i < n; i++) {
            if (!rk[i]) { h = 0; continue; }
            for (int j = sa[rk[i] - 1];
                i + h < n and j + h < n
                and s[i + h] == s[j + h];) ++h;
            lcp[rk[i] - 1] = h ? h-- : 0;
        }
    }
};

```

7.6 Aho-Corasick

```

const int sigma = ;

struct Node {
    Node *ch[sigma]{};
    Node *fail{}, *next{};
    bool end{};
} pool[i64(1E6)]{};

```

```

struct ACauto {
    int top;
    Node *root;
    ACauto() {
        top = 0;
        root = new (pool + top++) Node();
    }
    int add(string_view s) {
        auto p = root;
        for (char c : s) {
            c -= ;
            if (!p->ch[c]) {
                p->ch[c] = new (pool + top++) Node();
            }
            p = p->ch[c];
        }
        p->end = true;
        return p - pool;
    }
    vector<Node*> ord;
    void build() {
        queue<Node*> que;
        root->fail = root;
        for (auto &p : root->ch) {
            if (p) {
                p->fail = root;
                que.push(p);
            } else {
                p = root;
            }
        }
        while (!que.empty()) {
            auto p = que.front();
            que.pop();
            ord.push_back(p);
            p->next = (p->fail->end ? p->fail : p->fail->next);
            for (int i = 0; i < sigma; i++) {
                if (p->ch[i]) {
                    p->ch[i]->fail = p->fail->ch[i];
                    que.push(p->ch[i]);
                } else {
                    p->ch[i] = p->fail->ch[i];
                }
            }
        }
    }
};

```

7.7 Palindromic Tree

```

// 迴文樹的每個節點代表一個迴文串
// len[i] 表示第 i 個節點的长度
// fail[i] 表示第 i 個節點的失配指針
// fail[i] 是 i 的次長迴文後綴
// dep[i] 表示第 i 個節點有幾個迴文後綴
// nxt[i][c] 表示在節點 i 兩邊加上字元 c 得到的點
// nxt 邊構成了兩顆分別以 odd 和 even 為根的向下的樹
// len[odd] = -1, len[even] = 0
// fail 邊構成了一顆以 odd 為根的向上的樹
// fail[even] = odd
// 0 ~ node size 是一個好的 dp 順序
// walk 是構建迴文樹時 lst 經過的節點
struct PAM {
    vector<array<int, 26>> nxt;
    vector<int> fail, len, dep, walk;
    int odd, even, lst;
    string S;
    int newNode(int l) {
        fail.push_back(0);
        nxt.push_back({});
        len.push_back(l);
        dep.push_back(0);
        return fail.size() - 1;
    }
    PAM() : odd(newNode(-1)), even(newNode(0)) {
        lst = fail[even] = odd;
    }
    void reserve(int l) {
        fail.reserve(l + 2);
        len.reserve(l + 2);
        nxt.reserve(l + 2);
        dep.reserve(l + 2);
    }
};

```

```

    walk.reserve(1);
}
void build(string_view s) {
    reserve(s.size());
    for (char c : s) {
        walk.push_back(add(c));
    }
}
int up(int p) {
    while (S.rbegin()[len[p] + 1] != S.back()) {
        p = fail[p];
    }
    return p;
}
int add(char c) {
    S += c;
    lst = up(lst);
    c -= 'a';
    if (!nxt[lst][c]) {
        nxt[lst][c] = newNode(len[lst] + 2);
    }
    int p = nxt[lst][c];
    fail[p] = (lst == odd ? even : nxt[up(fail[lst])][c]);
    lst = p;
    dep[lst] = dep[fail[lst]] + 1;
    return lst;
}
};

```

7.8 Suffix Automaton

```

struct SAM {
    vector<array<int, 26>> nxt;
    vector<int> fail, len;
    int lst = 0;
    int newNode() {
        fail.push_back(0);
        len.push_back(0);
        nxt.push_back({});
        return fail.size() - 1;
    }
    SAM() : lst(newNode()) {}
    void reset() {
        lst = 0;
    }
    int add(int c) {
        if (nxt[lst][c] and len[nxt[lst][c]] == len[lst] + 1) { // 廣義
            return lst = nxt[lst][c];
        }
        int cur = newNode();
        len[cur] = len[lst] + 1;
        while (lst and nxt[lst][c] == 0) {
            nxt[lst][c] = cur;
            lst = fail[lst];
        }
        int p = nxt[lst][c];
        if (p == 0) {
            fail[cur] = 0;
            nxt[0][c] = cur;
        } else if (len[p] == len[lst] + 1) {
            fail[cur] = p;
        } else {
            int t = newNode();
            nxt[t] = nxt[p];
            fail[t] = fail[p];
            len[t] = len[lst] + 1;
            while (nxt[lst][c] == p) {
                nxt[lst][c] = t;
                lst = fail[lst];
            }
            fail[p] = fail[cur] = t;
        }
        return lst = cur;
    }
    vector<int> order() { // 長度遞減
        vector<int> cnt(len.size());
        for (int i = 0; i < len.size(); i++)
            cnt[len[i]]++;
        partial_sum(rall(cnt), cnt.rbegin());
        vector<int> ord(cnt[0]);
        for (int i = len.size() - 1; i >= 0; i--)

```

```

        ord[--cnt[len[i]]] = i;
        return ord;
    }
};

```

7.9 Lyndon Factorization

```

// partition s = w[0] + w[1] + ... + w[k-1],
// w[0] >= w[1] >= ... >= w[k-1]
// each w[i] strictly smaller than all its suffix
// min rotate: last < n of duval_min(s + s)
// max rotate: last < n of duval_max(s + s)
// min suffix: last of duval_min(s)
// max suffix: last of duval_max(s + -1)
vector<int> duval(const auto &s) {
    int n = s.size(), i = 0;
    vector<int> pos;
    while (i < n) {
        int j = i + 1, k = i;
        while (j < n and s[k] <= s[j]) { // >=
            if (s[k] < s[j]) k = i; // >
            else k++;
            j++;
        }
        while (i <= k) {
            pos.push_back(i);
            i += j - k;
        }
    }
    pos.push_back(n);
    return pos;
}

```

7.10 SmallestRotation

```

string Rotate(const string &s) {
    int n = s.length();
    string t = s + s;
    int i = 0, j = 1;
    while (i < n && j < n) {
        int k = 0;
        while (k < n && t[i + k] == t[j + k]) ++k;
        if (t[i + k] <= t[j + k]) j += k + 1;
        else i += k + 1;
        if (i == j) ++j;
    }
    int pos = (i < n ? i : j);
    return t.substr(pos, n);
}

```

8 Misc

8.1 Fraction Binary Search

```

// Binary search on Stern-Brocot Tree
// Parameters: n, pred
// n: Q_n is the set of all rational numbers whose
// denominator does not exceed n
// pred: pair<i64, i64> -> bool, pred({0, 1}) must be true
// Return value: {{a, b}, {x, y}}
// a/b is bigger value in Q_n that satisfy pred()
// x/y is smaller value in Q_n that not satisfy pred()
// Complexity: O(log^2 n)
using Pt = pair<i64, i64>;
Pt operator+(Pt a, Pt b) { return {a.ff + b.ff, a.ss + b.ss}; }
Pt operator*(i64 a, Pt b) { return {a * b.ff, a * b.ss}; }
pair<pair<i64, i64>, pair<i64, i64>> FractionSearch(i64
    n, const auto &pred) {
    pair<i64, i64> low{0, 1}, hei{1, 0};
    while (low.ss + hei.ss <= n) {
        bool cur = pred(low + hei);
        auto &fr{cur ? low : hei}, &to{cur ? hei : low};
        u64 L = 1, R = 2;
        while ((fr + R * to).ss <= n and pred(fr + R * to)
            == cur) {
            L *= 2;
            R *= 2;
        }
        while (L + 1 < R) {
            u64 M = (L + R) / 2;
            ((fr + M * to).ss <= n and pred(fr + M * to) ==
                cur ? L : R) = M;

```

```

    }
    fr = fr + L * to;
}
return {low, hei};
}

```

8.2 de Bruijn sequence

```

constexpr int MAXC = 10, MAXN = 1e5 + 10;
struct DBSeq {
    int C, N, K, L;
    int buf[MAXC * MAXN];
    void dfs(int *out, int t, int p, int &ptr) {
        if (ptr >= L) return;
        if (t > N) {
            if (N % p) return;
            for (int i = 1; i <= p && ptr < L; ++i)
                out[ptr++] = buf[i];
        } else {
            buf[t] = buf[t - p], dfs(out, t + 1, p, ptr);
            for (int j = buf[t - p] + 1; j < C; ++j)
                buf[t] = j, dfs(out, t + 1, t, ptr);
        }
    }
    void solve(int _c, int _n, int _k, int *out) { //
        alphabet, len, k
        int p = 0;
        C = _c, N = _n, K = _k, L = N + K - 1;
        dfs(out, 1, 1, p);
        if (p < L) fill(out + p, out + L, 0);
    }
} dbs;

```

8.3 HilbertCurve

```

i64 hilbert(int n, int x, int y) {
    i64 pos = 0;
    for (int s = (1 << n) / 2; s; s /= 2) {
        int rx = (x & s) > 0;
        int ry = (y & s) > 0;
        pos += 1LL * s * s * ((3 * rx) ^ ry);
        if (ry == 0) {
            if (rx == 1) x = s - 1 - x, y = s - 1 - y;
            swap(x, y);
        }
    }
    return pos;
}

```

8.4 Grid Intersection

```

int det(Pt a, Pt b) { return a.ff * b.ss - a.ss * b.ff;
}
// find p s.t (d1 * p, d2 * p) = x
Pt gridInter(Pt d1, Pt d2, Pt x) {
    swap(d1.ss, d2.ff);
    int s = det(d1, d2);
    int a = det(x, d2);
    int b = det(d1, x);
    assert(s != 0);
    if (a % s != 0 or b % s != 0) {
        return {-1, -1};
    }
    return {a / s, b / s};
}

```

8.5 NextPerm

```

i64 next_perm(i64 x) {
    i64 y = x | (x - 1);
    return (y + 1) | (((~y & ~y) - 1) >> (__builtin_ctz(
        x) + 1));
}

```

8.6 Python FastIO

```

import sys
sys.stdin.readline()
sys.stdout.write()

```

8.7 HeapSize

```

pair<i64, i64> Split(i64 x) {
    if (x == 1) return {0, 0};
    i64 h = __lg(x);
    i64 fill = (1LL << (h + 1)) - 1;
    i64 l = (1LL << h) - 1 - max(0LL, fill - x - (1LL <<
        (h - 1)));
    i64 r = x - 1 - l;
    return {l, r};
}

```

8.8 PyFrac

```

from decimal import *
setcontext(Context(prec=MAX_PREC, Emax=MAX_EMAX,
    rounding=ROUND_FLOOR))
print(Decimal(input()) * Decimal(input()))
from fractions import Fraction
Fraction('3.14159').limit_denominator(10).numerator #22

```

8.9 Kotlin

```

import java.util.*
import java.math.BigInteger;
import kotlin.math.*
private class Scanner {
    val lines = java.io.InputStreamReader(System.`in`).
        readLines()
    var curLine = 0
    var st = StringTokenizer(lines[0])
    fun next(): String {
        while(!st.hasMoreTokens())
            st = StringTokenizer(lines[++curLine])
        return st.nextToken()
    }
    fun nextInt() = next().toInt()
    fun nextLong() = next().toLong()
}
fun Long.toBigInteger() = BigInteger.valueOf(this)
fun Int.toBigInteger() = BigInteger.valueOf(toLong())
fun main() {
    val sc = Scanner()
    val buf = StringBuilder()

    val mp = Array(5) { Array(5) { -1 } }
    val dx = intArrayOf(1, 0)
    val dy = intArrayOf(0, 1)
    val v = ArrayList<Int>()

    fun dfs(x: Int, y: Int, s: Int = 0) {
        for((dx,dy) in dx zip dy) dfs(x+dx, y+dy, s)
    }
    dfs(0,0)

    val st = v.toSet().toIntArray().sorted()
    println("${st.joinToString()}\\n") // st.sort()

    for(i in 1..sc.nextInt()) {
        val x = st.binarySearch(sc.nextInt())
        buf.append("$x\\n")
    }

    val a = BigInteger(sc.next())
    val b = sc.nextLong().toBigInteger()
    println(a * b)
    print(buf)
}

```