Pagerank in Apache Flink

Author: Ward Schodts Supervisor: Juan Soto

Datenbanksysteme und Informationsmanagement Technische Universität Berlin



July 8, 2016



Agenda

Introduction



Introduction

The experiment

The different algorithm implementations


Results

Conclusion



Pagerank






PageRank example 1 [6]

- ► A page has a high PageRank R if
 - there are many pages linking to it
 - or, if there are some pages with a high PageRank linking to it



$$R(P_i) = \sum_{P_j \in B_i} \frac{R(P_j)}{L_j}$$

- where
 - B_i is the set of pages that link to page P_i
 - L_j is the number of outgoing links for page P_j linking to it



PageRank example 2 [6]







Apache Flink

Introduction



- ► Open source framework for distributed Big Data Analytics
- Exploits:
 - data streaming
 - in-memory processing
 - iteration operators

to improve performance

- Formerly Stratosphere (Flink means agile)
- Developped here at TUB



Introduction

The different algorithm implementations

Apache Flink: 2 possible setups



```
<dependencies>
   <dependency>
       <groupId>org.apache.flink</groupId>
       <artifactId>flink-java</artifactId>
       <version>${flink.version}</version>
   </dependency>
   <dependency>
       <groupId>org.apache.flink</groupId>
       <artifactId>flink-streaming-java 2.10</artifactId>
       <version>${flink.version}
   </dependency>
   <dependency>
       <groupId>org.apache.flink</groupId>
       <artifactId>flink-gelly 2.10</artifactId>
       <version>${flink.version}</version>
   </dependency>
   <dependency>
       <groupId>org.apache.flink</groupId>
       <artifactId>flink-table 2.10</artifactId>
       <version>${flink.version}
   </dependency>
```

```
| Note |
```


Binary version (self compiled)

Maven



Apache Flink: Gelly





Gelly



Introduction

- ► Large-scale graph processing API
- ► On top of Flink's Java API
- Off-the shelf library methods (e.g. pagerank)
- Iterative algorithms

10

Agenda

Introduction



Introduction

The experiment

The different algorithm implementations

Results

Conclusion



General experiment setup



Experiment 1:

- Data file with graph (and pagerank solution)
 ...
- 2. Use Flink and Graphlab implemention to compute pagerank
- 3. Compare with solution



General experiment setup

Experiment 1:

- 1. Data file with graph (and pagerank solution)
 - $\downarrow \downarrow$
- 2. Use Flink and Graphlab implemention to compute pagerank
- 3. Compare with solution

Experiment 2:

- 1. Data file with huge graph (no solution yet)
 - 1
- Use Flink and Graphlab implemention to compute pagerank
- 3. Compare with each other



Experiment 1 data

Introduction



Data from a former Hadoop toolkit (Cloud9, now Bespin):

Name	# vertices	# edges
Small	93	195
Medium	316	430
Large	1458	3545



Experiment 2 data

Introduction



Webgraph from snap.stanford.edu/data/

Name	# vertices	# edges
web-Google	875713	5105039



Agenda

Introduction



Introduction

The experiment

The different algorithm implementations

Results

Conclusion



Flink algorithm 1



dataArtisans

dataArtisians logo, [1]

- ▶ An exercise from dataArtisians
- Uses the standard Gelly implementation
- ▶ # input nodes = # output nodes



data Artisans

- A case study implementation from dataArtisians
- ► A custom implementation
- # input nodes = # output nodes





- An example from the Apache Flink repository
- ► A custom implementation
- # input nodes != # output nodes → filters



Turi pagerank algorithm





Turi logo, [8]

- Used the standard implementation
- ► Builds a graph out of the edges dataset



Agenda

Introduction



Introduction

The experiment

The different algorithm implementations

Results

Conclusion



Results



22

To compare I implemented a comparer that:

- ► could handle list of diffrence sizes.
- took care of equal pagerank values (they maybe sorted in different way),
- ▶ had a modifyable window to compare with.



Results: experiment 1




23

Any expectations?



Results: experiment 1









Results: experiment 1
































Speed of experiment 1











Agenda

Introduction



Introduction

The experiment

The different algorithm implementations

Results

Conclusion



Conclusion



Thank you for your attention



Questions?



35

References I





Data Artisians. Data Artisians logo. URL:

%5Curl%7Bhttps://www.mapr.com/sites/default/files/data_artisans_logo.png%7D.



Slim Baltagi. Overview of Apache Flink: Next-Gen Big Data Analytics Framework. 2015. URL: %5Curl%7Bhttp:

//www.slideshare.net/sbaltagi/overview-ofapacheflinkbyslimbaltagi?qid=5f0b5424-d1874c79-a6006cae794c686e&v=&b=&from search=3%7D.



Apache Flink. Apache Flink Squirrel. URL:

%5Curl%7Bhttps://flink.apache.org/img/logo/png/1000/flink squirrel 1000.png%7D.



References II





Lawrence Page et al. "The PageRank citation ranking: bringing order to the web." In: (1999).

Beat signer. Google PageRank. 2009. URL: %5Curl%7Bhttp://www.slideshare.net/signer/google-pagerank-presentation?qid=18af8836-30e7-41cd-9edb-956bd7ca324d&v=&b=&from search=2%7D.

References III



38



Mathias Spahlinger. There is no repetition. URL:

%5Curl%7Bhttps://www.google.com/search?q=repeat&source=lnms&tbm=isch&sa=X&ved=0ahUKEwi4laH2tuLNAhVnB8AKHTPQCU4Q_AUICCgB&biw=1590&bih=765#tbm=isch&q=no+repetition&imgrc=h1qwLbEEezv8SM:%7D.



Inc Turi. Turi. URL: %5Curl%7Bhttps://www.google.
com/search?q=repeat&source=lnms&tbm=isch&
sa=X&ved=0ahUKEwi4laH2tuLNAhVnB8AKHTPQCU4Q_
AUICCgB&biw=1590&bih=765#tbm=isch&q=no+
repetition&imgrc=h1qwLbEEezv8SM:%7D.

