Department of Computer

EngineeringAcademic

Term: Jan-Apr 2022

Class : T.E Computer Sem -VII
Subject: System Programming and Compiler Construction

Practical No:	**6**
Title:	**Design of top Down Parser- Recursive Descent Parser.**
Date of Performance:	11/04/2022
Date of Submission:	11/04/2022
Roll No:	**8940**
Name of the Student:	**Warren Fernandes**

Evaluation:

Sr. No	Rubric	Grade
1	On time Completion & Submission (2)	
2	Output (3)	
3	Code Optimization (3)	
4	Knowledge of the topic (2)	
5	Total (10)	

Signature of the Teacher:

CODE

```
#include<stdio.h>

#include<conio.h>

#include<string.h>

char input[100];

int i,l;

void main()

{

printf("\nRecursive descent parsing for the following grammar\n"); printf("\nE->TE'\nE'->+TE'/@\nT->FT'\nT'->*FT'/@\nF->(E)/ID\n"); printf("\nEnter the string to be checked:"); gets(input);

if(E())

{

if(input[i+1]=='\0')

printf("\nString is accepted");

else

printf("\nString is not accepted");

}

else

printf("\nString not accepted");

getch();
```

```
}
E()
{
if(T())
{
if(EP())
return(1);
else
return(0);
}
else
return(0);
}
EP()
{
if(input[i]=='+')
{
i++;
if(T())
{
```

```
if(EP())
return(1);
else
return(0);
}
else
return(0);
}
else
return(1);
}
T()
{
if(F())
{
if(TP())
return(1);
else
return(0);
}
```

```
else
return(0);
}
TP()
{
if(input[i]=='*')
{
i++;
if(F())
{
if(TP())
return(1);
else
return(0);
}
else
return(0);
}
else
return(1);
```

```
}
F()
{
if(input[i]=='(')
{
i++;
if(E())
{
if(input[i]==')')
{
i++;
return(1);
}
else
return(0);
}
else
return(0);
}
else if(input[i]>='a'&&input[i]<='z'||input[i]>='A'&&input[i]<='Z')
```

```
{

i++;

return(1);

}

else

return(0);

}
```

OUTPUT