Reservations

	createAt	TIMESTAMP
	resDate	DATE
	resTime	DATETIME
	partySize	INT
PK	RID	INT

Waitlist

PK	WID	INT
	joinAt	TIMESTAMP
	partySize	INT

menu

PK	FID	INT
	foodName	VARCHAR
	price	INT

Customers

	firstName	VARCHAR
	lastName	VARCHAR
PK	phoneNumber	VARCHAR
FK	RID	INT
FK	WID	INT
	children	INT

CheckIn

FK	TID	INT
FK	phone#	VARCHAR
	firstName	VARCHAR
	lastName	VARCHAR
	partySize	INT
	createdAt	TIMESTAMP
	comment	VARCHAR
FK	waiterID	INT
FK	OID	INT

orders_item

FK	OID	INT
FK	FID	INT
	quantity	INT

Tables

PK	TID	INT
	size	INT

Waiters

PK	waiterID	INT
	firstName	VARCHAR
	lastName	VARCHAR

orders

PK	OID	INT
	total	INT

rHistory

Key	createAt	Type
Key	TID	Type
Key	Field	Type
Key	Field	Type
Key	Field	Type
Key	Field	Type
Key	Field	Type
Key	Field	Type
Key	Field	Type
Key	Field	Type
Key	Field	Type

Name: Warren Huang
Course: CIS 98
Instructor: Lakisha Brooks

rHistory is used to store a backup from other tables

Legend:

——+	ONE
——<	Many
——++	One and only one
——○+	Zeor or one
——○<	Zero or many
——+<	One or many